MILITARY SPECIFICATION

HOUSING, MOLDED, FOR ANTI-PERSONNEL MINE M131 SYSTEM

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by drawings and provides quality assurance provisions for the fabrication of parts, assemblies and packing of the metal and plastic parts for the antipersonnel mine for the M131 System.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifictions and standards of the issue listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116	-	Methods of Preservation.
MIL-B-117	-	Bag, Sleeve and Tubing-Interior Packaging.
MIL-S-45743	-	Soldering, Manual Type, High Reliability, Electrical and Electronic For.
MIL-A-48078	-	Ammunition Standard Quality Assurance. Provisions, General Specification For.
MIL-P-50884	-	Printed Wiring, Flexible General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

9337402 - Clip, Sensor Locating.
9337403 - Wiring, Printed, Flexible.
9337404 - Bracket, Sensor.
9337405 - Manifold.
9337407 - Plug, Manifold.
9337417 - Manifold Assembly.
9337418 - Preform and Sensors Assembly.
9337419 - Housing, Molded.
9337432 - Tubing, Manifold.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B117 STANDARD METHOD OF SALT SPRAY (FOG) TESTING

(Application for copies of ASTM publication should be addressed to American Soceity for Testing and Materials, 1917 Race Street, Philadelphia, Pennsylvania 19103).

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on applicable drawings, associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 Housing function. The housing molded, 9337419 shall deploy sensors when given a voltage of 1.6 volts discharged from a 100 microfarad capacitor. The housing shall deploy sensors with either the three-sensor side up or the four-sensor side up. All sensors on the top side only shall deploy.

3.4 Soldering. All soldered electrical connections shall comply with MIL-S-45743.

3.4.1 Solderability. Electronic and electric assembly parts that are to be soldered shall comply with the solderability requirements of MIL-S-45743 except the flexible printed wiring shall comply with the solderability requirements of MIL-P-50884.

3.4.2 Quality assurance soldering plan. The contractor shall generate a Quality Assurance Soldering Plan that will detail the overall soldering procedure. The plan shall include detailed information for handling, cleaning, hand soldering, tool maintenance, training, flagging procedures for avoiding excessive defects, and all other pertinent QA procedures relative to soldering. This plan shall be generated and submitted to ARDEC, AMSMC-QAT-M(D).

3.5 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough workmanship manner, and all manufacturing, processings, and assembly operations shall be correctly performed. Metal parts shall be free of burrs, chips, sharp edges, cracks, crazes, unblended radii, porosity, warpage, burn marks, checks, chipped edges, blisters, excess flash, dirt, grease, rust, salt deposits, corrosion products, and other defects or foreign matter which would affect their serviceability. The cleaning method used shall not be injurious to any part or assembly, nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection

b. Quality conformance inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Housing Molded	9337419	25

A sample of 10 for other components listed in Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and paragraphs 4.4.2, testing per paragraph 4.4.3, and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE M131 AP Mine System Molded Housing Components		SHEET 1 OF 2		DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Housing, Molded (Dwg. 9337419)				
	Examination for defects	25	-	3.2	4.4.2.1
	Function test	25	-	3.3	4.5.1
	Preform & Sensors Assembly (Dwg.9337418)				
	Examination for defects	10	-	3.2	4.4.2.2
	Bracket Sensor (Dwg. 9337404)				
	Examination for defects	10	-	3.2	4.4.2.3
	Wiring, Printed, Flexible (Dwg. 9337403)				
	Examination for defects	10	-	3.2	4.4.2.4
	Clip, Sensor Locating (Dwg. 9337402)				
	Examination for defects	10	-	3.2	4.4.2.5

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-H-64033(AR)

PARAGRAPH	TITLE M131 AP Mine System Molded Housing Components		SHEET 2 OF 2		DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Tubing, Manifold (Dwg. 9337432) Examination for defects	10	-	3.2	4.4.2.6
	Plug Manifold (Dwg. 9337407) Examination for defects	10	-	3.2	4.4.2.7
	Manifold (Dwg. 9337405) Examination for defects	10	-	3.2	4.4.2.8
	Manifold Assembly (Dwg. 9337417) Examination for defects	10	-	3.2	4.4.2.9
NOTES:					

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation of MIL-A-48078. In addition, inspection lots of housing assemblies shall contain tripline sensors, extended range (9292972) of one lot interfix from one manufactured.

Maximum lot size shall be no more than one (1) months production (30 calender day period).

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordnce with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Housing, Molded	1 OF 2	9337419
			NEXT HIGHER ASSEMBLY: 9337430

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
Major					
101	Housing, function		.40% 1/	3.3	4.5.1
102	Pressure cartridge circuit resistance		100%	3.2	Gage
103	Tripline circuit resistance		100%	3.2	Gage
104	Potting voids in excess of .025 on surfaces "X" and "Y" within .25" of sensor opening		.40%	3.2	Visual
105	Evidence of potting material on open end of triplines		.40%	3.2	Visual
106	Density of potting material		.40%	3.2	Certificate of Conformance
107	True position of lead holes		.40%	3.2	Gage
108	True position of S&A cavity		.40%	3.2	Gage
109	Diameter of small S&A cavity		.40%	3.2	Gage
110	Distance from center to S&A locating boss		.40%	3.2	Gage
111	Depth from surface "X" to centerline of explosive lead holes		.40%	3.2	Gage
112	True position of rectangular locating recess		.40%	3.2	Gage
113	Length of rectangular locating recess		.40%	3.2	Gage

NOTES:

1/ Sample as per MIL-STD-105 General Inspection Level 1, single sample, normal inspection.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.1	Housing, Molded				9337419
					NEXT HIGHER ASSEMBLY 9337430
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
114	Diameter of round locating recess		.40%	3.2	Gage
115	Outside Diameter		.40%	3.2	Gage
116	True position of outside diameter		.40%	3.2	Gage
117	Width of locating slot		.40%	3.2	Gage
118	True position of locating slot		.40%	3.2	Gage
119	True position of trip line outside diameter (7 places)		.40%	3.2	Gage
120	Aimpoint of trip line (7 places)		.40%	3.2	Gage
Minor					
201	Potting bulges above surface "X" and "Y" in center area of housing		.65%	3.2	Gage
202	Height of housing		.65%	3.2	Gage
203	Width of rectangular locating recess		.65%	3.2	Gage
204	Spacing from housing to edge of flex circuit		.65%	3.2	Gage
205	Evidence of poor workmanship		.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Preform and Sensors Assembly	1	1	9337418
				NEXT HIGHER ASSEMBLY: 9337419

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None				
Major					
101	Shrink tubing in area indicated		.40%	3.2	Visual
102	End of tube 9337435 not shrunk		.40%	3.2	Visual
103	Pressure cartridge circuit resistance		.40%	3.2	Ohmmeter
104	Trip line circuit resistance		.40%	3.2	Ohmmeter
105	Wires routed properly		.40%	3.2	Visual
106	Trip line sensor sealed		.40%	3.2	Visual
107	Diaphragm sealed both sides around crimp		.40%	3.2	Visual
108	Wires proper		.40%	3.2	Gage
109	Solder workmanship		.40%	3.2	Visual
110	Wires or tubing extending beyond envelope diameter		.40%	3.2	Gage
Minor					
201	Location of manifold tubing to pressure cartridge		.65%	3.2	Gage
202	Protrusion of sensor from sensor clip		.65%	3.2	Gage
203	Evidence of poor workmanship		.65%	3.5	Visual
204	Adhesive proper		.65%	3.2	Certification

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH 4.4.2.3	TITLE Bracket, Sensor		SHEET 1 OF 1		DRAWING NUMBER 9337404
					NEXT HIGHER ASSEMBLY 9337418
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Tabs twisted proper		.40%	3.2	Visual
102	Overall width (after formed)		.40%	3.2	Gage
103	Overall length (after formed)		.40%	3.2	Gage
104	Diameter of sensor clip holes		.40%	3.2	Gage
105	True position of sensor clip locating holes (7 places)		.40%	3.2	Gage
106	True position of explosive lead holes (7 places)		.40%	3.2	Gage
Minor					
201	Material proper		.65%	3.2	Certification of Conformance
202	Finish proper & complete		.65%	3.2	Visual
203	Overall Height (after forming)		.65%	3.2	Gage
204	Evidence of poor workmanship		.65%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Wiring, Printed, Flexible				9337403
					NEXT HIGHER ASSEMBLY 9337418
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Visual and Dimensional Examination		.40%	3.2	MIL-P-50884 1/
102	Missing or improperly mounted terminals		.40%	3.2	Visual
103	Hole Locations		.40%	3.2	Gage
104	Solderability	20 2/	-	3.4.1	MIL-P-50884
Minor					
201	Evidence of poor workmanship		.65%	3.5	Visual

NOTES:
1/ Paragraph 4.8 Methods of Examination and test.
2/ Reject for one or more defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Clip, Sensor Locating				9337402
					NEXT HIGHER ASSEMBLY 9337418
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	True position of the sensor holding boss		.40%	3.2	Gage
102	Inside Diameter of the Clip Mounting Hole		.40%	3.2	Gage
103	Angle of clip board		.40%	3.2	Gage
104	True position of sensor smallest width		.40%	3.2	Gage
105	Height of sensor hole		.40%	3.2	Gage
Minor					
201	Thickness		.65%	3.2	Gage
202	Material proper		.65%	3.2	Certification
203	True Position of Sensor Hole		.65%	3.2	Gage
204	Evidence of poor workmanship		.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.6	Tubing, Manifold	1	1	9337432
				NEXT HIGHER ASSEMBLY 9337417

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major	None Defined				
Minor					
201	Material proper		-	3.2	Certification
202	Length		.65%	3.2	Gage
203	Evidence of poor workmanship		.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Plug Manifold				9337407
					NEXT HIGHER ASSEMBLY 9337417
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	True position of locating tab		.40%	3.2	Gage
102	True position of tripline tube holes		.40%	3.2	Gage
Minor					
201	Presence of mold flash		.65%	3.2	Visual
202	Evidence of poor workmanship		.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Manifold	1 OF 1	9337405
			NEXT HIGHER ASSEMBLY 9337417

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Plugged tube holes		.40%	3.2	Visual
102	Outside diameter of tube retaining lip		.40%	3.2	Gage
103	True position of the four right tube holes		.40%	3.2	Gage
104	Outside diameter of the gas generator port		.40%	3.2	Gage
105	True position of the manifold plug locating slot		.40%	3.2	Gage
106	Inside diameter of the manifold plug cavity		.40%	3.2	Gage
107	Depth of the manifold plug cavity		.40%	3.2	Gage
Minor					
201	Height of tripline tube ports		.65%	3.2	Gage
202	Evidence of poor workmanship		.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-H-64033(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Manifold Assembly	1 OF 1	9337417
			NEXT HIGHER ASSEMBLY 9337418

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Verify open ports per Note 2		.40%	3.2	Visual
102	Verify tubing ends anchored on manifold per Note 4.		.40%	3.2	Visual
103	Verify coverage of adhesive between manifold and manifold plug per Note 5		.40%	3.2	Visual
104	Verify free ball movement per Note 6		.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.3.1 Dimensional control of molded or plastic parts. This paragraph applies to the following parts:

Molding Housing	9337419	Ref Para 4.4.2.1
Plug, Manifold	9337407	Ref Para 4.4.2.7
Manifold	9337405	Ref Para 4.4.2.8

In place of normal sampling and inspections associated with the Classification of Defects, and after a curing time for the parts has been approved (see Note 1) a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in the reference paragraphs for the above parts after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of ispection frequency providing he presents objective evidence to the contracting officer to substantiate the request.

NOTE 1: In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60, etc. mins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to, ARDEC, Dover, New Jersey 07801-5001, ATTN: AMSMC-QAT-M(D). If there is a change in material, or in the cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed in this specification is identified either directly or by reference, in the "paragraph reference/inspection method" column of the First Article or Quality Conformance Inspection Tables herein. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.4 herein.

4.5 Test methods and procedures.

4.5.1 Housing function. After conditioning a 100 microfarad (± 5%) capacitor charged to 1.6 volts (± 0.1 volt) shall be applied across terminals A and B of the flexible cable. One-half of the sensors shall be tested with the three (3) sensor side up and one-half shall be tested with the four (4) sensor side up. Failure to have all sensors on the top side only release and deploy shall be cause to classify the housing assembly defective. Trip line circuit resistance shall be monitored after deployment in accordance with 9337419.

5.0 PACKAGING

5.1 Housing, Molded 9337419.

5.1.1 Cleaning. Item listed in para 5.1 shall be cleaned in accordance with process C-1 of MIL-P-116, if required.

5.1.2 Drying. Item listed in para 5.1 shall be dried in accordance with MIL-P-116, if required.

5.1.3 Preservation. Not applicable.

5.1.4 Unit and intermediate packaging.

5.1.4.1 Level C. The item listed in para 5.1 shall be unit and intermediate packaged in accordance with applicable parts of the Code of Federal Regulations (CFR) Title 49. In addition, each item shall be separated by appropriate partitioning and supported by appropriate cushioning to prevent physical damage. Also, unit or intermediate package shall be enclosed in a barrier bag in accordance with Type I, Class F of MIL-B-117. Evacuate excess air in barrier bag prior to heat sealing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

5.1.5 Packing.

5.1.5.1 Level C. The package in 5.1.4.3 shall be packed in accordance with applicable parts of the Code of Federal Regulations (CFR) Title 49. Sufficient filler shall be added to pack to prevent tearing of bag and insure a tight pack.

5.1.6 Marking.

5.1.6.1 Level A. Marking shall be in accordance with MIL-STD-129 and CFR 49.

5.1.6.2 Level B. Marking shall be in accordance with MIL-STD-129 and CFR 49.

5.1.6.3 Level C. Marking shall be in accordance with MIL-STD-129 and CFR 49.

5.2 Shipping. When parts from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of lots in transit.

6. NOTES

6.1 Intended use. These parts are designed for use in the M131 Mine System Antipersonnel Mine.

6.2 Ordering data. See MIL-A-48078.

6.3 First article. Provisions for first article as specified in Section 3 and 4.

6.4 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander: USARDEC, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.5 Data submissions. Results of all tests performed by the contractor shall be submitted in accordance with Data Item DI-R-1721 on the DD Form 1423 for the contract. Distribution shall include the following:

Commander
ARDEC
ATTN: AMSMC-QAT-M(D)
Dover, NJ 07801-5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

6.6 Distribution of ammunition data cards, inspection and test results. Distribution of ammunition data cards, inspection, and test results shall include Commander: ARDEC, Dover, NJ 07801-5001, ATTN: AMSMC-QAT-M(D).

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as, US Army Armament Research and Development Command, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.8 Definition of packaging and packing levels.

6.8.1 Level A. Full military protection for unrestricted (OCONUS) shipment and storage.

6.8.2 Level B. Limited military protection for limited shipment and storage.

6.8.3 Level C. For interplant shipment and very limited storage.

6.8.4 For further detailed information concerning packaging and packing levels, consult AR-700-15.

6.9 Subject term (key word) listing.

Mine, Anti-Personnel
Molded Housing

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A245)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT MUNITIONS & CHEMICAL COMMAND
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-64033	HOUSING, MOLDED, FOR ANTI-PERSONNEL MINE M131 SYSTEM

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.