MILITARY SPECIFICATION

IGNITER, ELECTRIC MATCH
PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the US Armny Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of parts for and loading, assembling and packing for one type of device designated as Igniter, Electric Match.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116	Preservation - Packaging, Methods of
MIL-P-223	Black Powder
MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1370

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

MIL-STD-331	-	Fuze and Fuze Components, Environmental and Performance Test For.
MIL-STD-810	-	Environmental Test Methods.
MIL-STD-1234	-	pyrotechnics, Sampling, Inspection and Testing.

2.1.2 Other Government documents, drawings, and publications. ıe following other Government documents, drawings, and publications ›rm a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

PRODUCT AND PACKAGING DRAWINGS

9390399	-	Igniter, Electric Match Assembly
9392395	-	Packing and Marking for Box, Fiberboard, For Igniter, Electric Match Assembly
9392394	-	Packing and Marking for Box, Outer For Igniter, Electric Match Assembly

Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific aquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between ıe text of this specification and the references cited herein, the ext of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings, specifications and standards.

3.2 Assembly. The igniter, electric match assembly shall comply with all requirements specified on Drawing (dwg.) 9390399, and all associated-drawings , and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

3.2.1 Item definition. This item consists of an electric squib/match charge to be used for igniting a standard a 155MM (HC) Hexachloroethane Smoke Canister.

3.3 Moisture content.

3.3.1 Paper and paper products. The moisture content of the paper and paper products components of the igniter, electric match assembly at the loading station at the time of loading shall not exceed 6.0 percent.

3.4 Functioning (Ambient temperature, 21 ± 3°C, 70 ± 5°F, Hot 51.5 ± 3°C, 125 ± 5°F, Cold -32 ± 3°C, -25 ± 5°F). The assembly shall function and comply with the following requirements after conditioning at specified temperature.

3.4.1 Performance. The igniter, electric match shall function with a soft ignition and burn for a duration of 19±5 seconds producing a high energy flame capable of igniting a 155MM HC Smoke Canister.

3.4.2 Functioning time. The time from application of twenty-four (24) plus or minus (±) two (2) Volts Direct Current (VDC), with minimum ignition current of 3.0 milliwatt seconds/ohm, to initiation of the assembly shall not be greater than 0.20 seconds,

3.5 Environmental conditions.

3.5.1 Low temperature. The igniters, shall be capable of withstanding low temperature conditions as specified in 4.5.4.1 and shall meet the performance requirements when-test fired as specified in 4.5.3.

3.5.2 High and ambient temperature. The igniters, shall be capable of withstanding high and ambient temperature conditions as specified in 4.5.4.2 and meeting the performance requirements when test fired as specified in 4.5.3.

3.5.3 Leak test. The igniter shall not leak when tested as specified in 4.5.4.3. Leakage shall constitute a failure.

3.5.4 Leakage test. The igniters, when packaged, shall be capable of withstanding exposure to the leakage test as specified in 4.5.4.4 and meeting the performance requirements when test fired.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

3.5.5 Jumble. The electric match igniter shall comply with the following requirements when tested as specified in 4.5.4.5.

a. The igniter shall not function during test.

b. There shall be no powder leakage.

c. The igniter components shall not separate during test.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, crazes, porosity, warpage, burn marks, blisters, excess flash, scratches, dirt, grease and other defects and foreign matter which would affect appearance or serviceability. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined. All packing components shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

Part Description	Drawings
Igniter, Match, Electric	9390399
Tube and Cap	9390400
Igniter Composition	9390401
Starter Composition	9390402
Labe 1	9390403
Match, Electric	9354514
Match and Cable Assembly	9354515

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70534(AR)

PARAGRAPH	TITLE: Igniter, Electric Match Assembly		SHEET 1 OF 2		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Tube and Cap (Dwg. 9390400) Examination of defects	32		3.2	4.4.2.1
	Igniter Composition (Dwg. 9390401) Examination for defects	32		3.2	4.4.2.2
	Cable, Electrical (Dwg. 9342153) Examination for defects	32		3.2	4.4.2.3
	Starter Composition (Dwg. 9390402) Examination for defects	32		3.2	4.4.2.4
	Match and Cable Assembly (Dwg. 9354515) Examination for defects	32		3.2	4.4.2.5
	Igniter, Electric Match, Assembly (Dwg. 9390399) Examination for defects	32		3.2	4.4.2.6

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-I-70534(AR)

PARAGRAPH	TITLE: Igniter, Electric Match Assembly		SHEET 2 OF 2		DRAWING NUMBER: See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Resistance Test	32		3.2	4.5.5
	Sequential Test				
	Leakage test +70 ± 5°F	1 Box		3.5.3	4.5.4.3
	Jumble	32		3.5.4	4.5.4.5, 4.5.3
	Hot	32	Note 1	3.5.2	4.5.4.2, 4.5.3
	Cold	32	Note 1	3.5.1	4.5.4.1, 4.5.3
	Ambient	32	Note 1	3.5.2	4.5.4.2, 4.5.3

NOTES:
1. Cold minus 25 ± 5°F, Ambient 70 ± 5°F, Hot +125 ± 5°F. Function igniters after each test.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot format on provisions of MIL-A-48078. In addition, inspection lots of Igniter Assemblies shall contain:

a. Parts of one kind from one manufacturer.

b. Electric igniters from not more than one lot interfix number from one manufacturer.

c. Composition ingredients from not more than one lot or batch.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Tube and Cap			9390400
				NEXT HIGHER ASSEMBLY 9390399

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wall thickness		0.40%	3.2	Gage
102	I.D. of cap		0.40%	3.2	Gage
103	Large O.D.		0.40%	3.2	Gage
104	Small hole diameter of cap		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70534(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Igniter Composition				93 90401
					NEXT HIGHER ASSEMBLY
					93 90 902
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Composition analysis			3.2	4.4.4
102	Moisture content			3.2	4.5.2.2
Minor	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70534 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Cable, Electrical				9342153
					NEXT HIGHER ASSEMBLY
					9354515
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of wire		0.40%	3.2	Gage
102	Length of stripped wire (2 places)		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026/10-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Starter Composition				93 90402
					NEXT HIGHER ASSEMBLY
					93 903 99
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weight analysis	10		3.2	4.4.4
102	Moisture composition			3.2	4.5.2.1
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70534 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Match and Cable Assembly				9354515
					NEXT HIGHER ASSEMBLY
					9390399
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of cable attachment		0.40%	3.2	Gage
102	Electrical resistance test		0.40%	3.2	Ohmmeter
103	Match insecure or improperly assembled (soldered)		0.40%	3.2	Visual/Manual
Minor					
201	Poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Igniter, Electric Match Assembly	1 OF 1	93 903 99
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height (max.)		0.40%	3.2	Gage
102	Sealant not 360° (2 places)		0.40%	3.2	Visual
103	Shunt wires not twisted or in correctly		0.40%	3.2	Visual
104	Ribbon missing or incorrectly applied		0.40%	3.2	Visual
105	Leak test	182	0-1	3.5.3	4.5.4.3
106	Jumble	32	0-1	3.5.5	4.5.4.5
107	Hot	50	Note 1	3.5.2	4.5.4.1, 4.5.3
108	Cold	50	Note 1	3.5.1	4.5.4.2, 4.5.3
109	Ambient	50	Note 1	3.5.2	4.5.4.1, 4.5.3
Minor					
201	Poor workmanship		1.0%	3.7	Visual

NOTES: 1. Cold minus 25 ± 5°F, Ambient 70 ± 5°F, Hot +125 ± 5°F. Function igniters after each test and observation for compliance to para. 3.4.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70534 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Sealed Packed Barrier Bag, Prior to Packing Into Box				9392395
					NEXT HIGHER ASSEMBLY 9392394
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Waterproofness of bag destroyed by rupture, puncture, or separation of seal		0.40%	3.2	Visual
102	Heat seal of barrier bag incorrect	10	0-1	3.2	4.5.4.5
103	Leakage test	15/ sub pack	0-1	3.5.4	4.5.4.4
Minor					
201	Heat seal of bag located so that two subsequent seals cannot be made		0.65%	3.2	Visual
202	Marking on bag missing, misleading or unidentifiable		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70534(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Box, Fiberboard, For Igniter, Electric Match (Prior to Sealing Top in Flaps)				93 923 95
					NEXT HIGHER ASSEMBLY 93 923 94
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Component(s) missing		0.40%	3.2	Visual
102	Filler(s) missing or inadequate		0.40%	3.2	Visual
103	Packaging components obviously damp or wet		0.40%	3.2	Visual/Manual
Minor					
201	Label missing		0.65%	3.2	Visual
202	Marking incorrect, misleading or unidentifiable		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Box, Wood, Packing, For Igniter, Electric Match				9392394
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
102	Box broken or split		0.40%	3.2	Visual
103	DOT symbol misleading or unidentifiable		0.40%	3.2	Visual
Minor					
201	Marking incomplete or incorrect		0.65%	3.2	Visual
202	Hardware improperly engaged		0.65%	3.2	Visual
203	Strapping improperly assembled		0.65%	3.2	Visual
204	Metallic Seal missing, unsealed or improperly positioned		0.65%	3.2	Visual
205	Contents loose		0.65%	3.2	Manual
206	Poor workmanship		1.0%	3.7	Visual

NOTES:

...dition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

4 .4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.3.1 Moisture Content (see Table II) - Major Defects

TABLE II

Starter composition	(see Dwg. 9390402)
Igniter composition	(see Dwg. 9390401)
Paper and paper products	(see 3.3.1)

The Contractor shall provide adequate controls to insure that the materials comply with the requirements. For verification, the contractor shall select and subject to test, one sample of each material from each eight (8) hours production. If a composite sample exceeds the requirement, that quantity or sub-lot material represented by the sample shall not be used in loading and packing, the remaining unloaded and unpacked material shall not be used in production, and the loaded and packed simulators shall be rejected. Test shall be performed as specified in 4.5.2.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.4.5 Functioning Test

4.4.5.1 Hot and ambient temperature. Beginning with the first Lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria of 4.4.2.6, fifty (50) igniter assemblies shall be selected from each lot for test. The lot shall be rejected if four (4) or more major defects occur. After three (3) consecutive lots have met the acceptance criteria specified, thirty-two (32) igniters shall be selected from each lot for test. The lot shall be reject if three (3) or more major defects occur, and lot sampling shall revert to fifty (50) samples per lot.

4.4.5.2 Cold temperature Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria of 4.4.2.6, fifty (50) igniters assemblies shall be selected from each lot for test. The lot shall be rejected of six (6) or more major defects occur. After three (3) consecutive lots have met the acceptance criteria specified, thirty-two (32) igniters shall be selected from each lot for test. The lot shall be ejected if four (4) or more major defects occur, and lot sampling shall revert to fifty (50) samples per lot.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:38Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Dimensional control of molded or plastic parts. In place of normal sampling and inspections associated with the Classification of Defects, and after a curing time for the parts has been approved (see Note 1) a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. Each molded part shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraphs 4.4.2.1, after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and and AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request. Contractor design of gages and test equipment required to perform the inspections listed herein shall be submitted per 6.3 for approval prior to manufacture of equipment. The noted subparagraphs identify those items and minimum inspections subject to the requirements of this paragraph.

NOTE 1: In establishing a curing time, dimensionally check ten (10 parts from each cavity at periodic intervals (e.g. every 30, 60, etc. reins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determing the curing time shall be sent to ARDC, Dover, New Jersey 07801, ATTN: AMSMC-QAT-M(D). If there is a change in material, or in the cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

4.5.2 Moisture content.

4.5.2.1 Starter composition. The method of determining the percentage of moisture in the starter composition shall be in accordance with MIL-P-223, heated until a constant weight is obtained for four (4) hrs. at 70°C. Observation shall be made for compliance with the applicable requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

4.5.2.2 Igniter composition. The method of determining the percentage of moisture in the igniter composition shall be in accordance with MIL-P-223 except to be heated until constant weight is obtained for four (4) hrs. at 70±3°C. Observation shall be made for compliance with applicable requirement.

4.5.2.3 Paper and paper products. The moisture content shall be determined in accordance with Method 102.1.1 of Standard MIL-STD-1234 except that a ten (10) gram sample shall be used and the drying time shall be for two (2) hours.

4.5.3 Functioning. (Ambient temperature, 21 ± 3°C, 70 ± 5°F, Hot, 51.5 ± 3°C, 125 ± 5°F, Cold, -32 ± 3°C, -25 ± 5°F). The igniter assemblies shall be conditioned for 12 hours min. at the specified temperatures and fired within 5 minutes after removal from the conditioning chamber. The igniter shall be positioned on a rigid support and fired by means of an approved power source specified in accordance with 3.4.2. observation shall be made for compliance with the applicable requirement. (Destructive test)

4.5.3.1 Functioning time. The time from initiation of the VDC shall be measured with approved metering equipment in accordance with para. 4.4.4. The assembly shall be observed for compliance with the requirements of 3.4.2.

4.5.4 Environmental tests. Environmental testing shall be conducted to determine compliance with the requirements of 3.5.

4.5.4.1 Low temperature. This test shall be conducted in accordance with Method 502.2, Procedure I of MIL-STD-810, except that the simulator shall be exposed to a temperature of -25 ± 5°F until thermal stabilization is reached and maintained for a period of 6 hours. (min.). Then the igniter shall be test fired. When necessary, the test specimens may be removed from the conditioning cabinet, set up, and fired within 5 minutes. observation shall be made for compliance with the applicable requirement.

4.5.4.2 High and ambient temperature. This test shall be conducted in accordance with Method 501.2, Procedure I of MIL-STD-810 except that the igniters shall be exposed to a temperature of 125 ± 5±F until thermal stabilization is reached, and maintained at that temperature for a period of 6 hours (min.). Then the igniter shall be test fired. When necessary, the test specimens may be removed from the conditioning cabinet, set up, and fired within 5 minutes. observation shall be made for compliance with the applicable requirement.

4.5.4.3 Leak test. The test shall be performed in accordance with the procedure specified in para. 4.4.3.1 and 4.4.3.2 of MIL-P-116H. Test samples shall be tested at a differential pressure of 1.3 P.S.I for 30 seconds minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

4.5.4.3 Leakage test. The test shall be performed in accordance with the procedure specified in para. 4.4.3.1 and 4.4.3.2 or 4.4.3.6 of MIL-P-116H. After the test, the seal shall be examined for compliance with the requirements of 3.5.3. (Non-Destructive Test.)

4.5.4.4 Heat seal of barrier bag. The test shall be performed in accordance with the procedure specified in para. 4.4.4.3 of MIL-P-116H. After the test, the seal shall be examined for compliance with the applicable requirements (Destructive Test).

4.5.4.5 Jumble. The igniter assemblies shall be tested in accordance with procedures specified in MIL-STD-331, Test 102, except that the duration of the test shall be a minimum of 20 minutes. The assemblies and equipment shall be observed for compliance with 3.5.4 (Destructive Test) .

4.5.6 Bridge wire resistance test. The igniter shall be tested for the required bridge wire resistance with an approved ohmmeter in accordance with para. 4.4.4. Observation shall be made for compliance with applicable requirements. (Non-Destructive Test)

5. PACKAGING

5.1 Packaging.

5.1.1 Packaging shall be in accordance with drawing 9392395.

5.2 Packing.

5.2.1 Packaging shall be in accordance with drawing 9392394.

5.3 Marking.

5.3.1 Marking shall be in accordance with drawings 9392395 and 9392394.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the Igniter, Electric Match.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research and Development Center, ATTN: AMSMC-QAT-I (D), Dover, NJ 07801-5001.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

6.4 Distribution of ammunition data cards. Distribution of data cards include the following: Commander, US Army Armament Research and Development Center, ATTN: AMSMC-QAT-M(D), Dover, NJ 07801-5001.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1370-A189)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US ARmy Armament Research &
Development Center
ATTN: AMSMC-QA
Dover, NJ 07801-5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-I-70534 (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*. _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.