MILITARY SPECIFICATION

MINE, ANTI-TANK: HE, XM75
METAL PARTS FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of the metal parts for the XM75 AT Mine.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitiation for bids or request for proposals, form a part of this specification of the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-5541	-	Chemical Coversion Coatings on Aluminum and Aluminum Alloys.
MIL-S-48078	-	Ammunition, Standard Qualtiy Assurance Provisions, General Specifications For

FEDERAL

QQ-P-35	-	Passivation Treatments for Corrosion Resisting Steel
TT-C-490	-	Cleaning Method and Pretreatment of Ferrous Surfaces for Organic Coatings

FSC: 1345

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1188	-	Commerical Packaging of Supplies and Equipment

DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9292106	-	Cover Electronics
9292112	-	Pressure Ring
9292120	-	Spacer End Bracket Assembly
9292121	-	Electronic End Bracket Assembly
9292122	-	Spacer End Cover Assembly
9292142	-	Case, Mine
9292169	-	Cup, Outer, Electronics
9292176	-	Cup, Outer, Spacer

(Copies of specifications, standards, drawings and publications listed above required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on the drawings listed in paragraph 2.1 and associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. The parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the part be contamined by the cleaning agents. All markings and stampings shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsiblity for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The following types of inspections shall be conducted on this item.

a. First Article Inspection.
b. Quality Conformance Inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in the quantities as indicated.

Part Description	Drawings	Quantity
Cover, Electronics	9292106	10
Ring, Pressure	9292112	10
Case, Mine	9292142	10
Cup Outer, Electronics	9292169	10
Cup Outer, Spacer	9292176	10
Cover, Spacer	9292113	10
Spacer Lens	9292193	10
Spacer End Cover Assembly	9292122	10
Spacer End Bracket Assembly	9292120	10
Cup, Slotted, Spacer	9292117	10
Bracket, Spacer End	9292119	10
Elect End Bracket Assy	9292121	10
Bracket, Elect End	9292118	10
Cup, Slotted, Elect	9292185	10

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63394(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Metal Parts, Anti-Tank: HE, XM75				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cover, Electronics (Dwg. 9292106) Examination for defects	10		3.2	4.4.2.1
	Ring, Pressure (Dwg. 9292112) Examination for defects	10		3.2	4.4.2.2
	Case, Mine (Dwg. 9292142) Examination for defects	10		3.2	4.4.2.3
	Cup, Outer, Elect (Dwg. 9292169) Examination for defects	10		3.2	4.4.2.4
	Cup, Outer, Spacer (Dwg. 9292176) Examination for defects	10		3.2	4.4.2.5
	Cover, Spacer (Dwg. 9292113) Examination for defects	10		3.2	4.4.2.6
	Spacer, Lens (Dwg. 9292193) Examination for defects	10		3.2	4.4.2.7
	Spacer, End Cover Assy (Dwg. 9292122) Examination for defects	10		3.2	4.4.2.8
	Spacer End Bracket Assy (Dwg. 9292120) Examination for defects	10		3.2	4.4.2.9

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63394(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Metal Parts, Mine, Anti-Tank: HE, XM75				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cup, Slotted, Spacer (Dwg. 9292117) Examination for defects	10		3.2	4.4.2.10
	Bracket, Spacer Eng (Dwg. 9292119) Examination for defects	10		3.2	4.4.2.11
	Elect End Bracket Assy (Dwg. 9292121) Examination for defects	10		3.2	4.4.2.12
	Bracket, Elect Eng (Dwg. 9292118) Examination for defects	10		3.2	4.4.2.13
	Cup, Slotted, Elect (Dwg. 9292185) Examination for defects	10		3.2	4.4.2.14

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Cover, Electronics				9292106
					NEXT HIGHER ASSEMBLY
					9292227
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter, (O.D.)		0.40%	3.2	Gage
102	Inside diameter, (I.D.)		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Protective finish missing or improper	(a)	-	3.2	Visual
105	True position, OD TO ID		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES: (a) Sampling and rejection in accordance with QQ-P-35.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63394(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Ring, Pressure				9292112
					NEXT HIGHER ASSEMBLY
					9292227
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Middle diameter		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	Height		0.40%	3.2	Gage
105	Weld incorrect		0.40%	3.2	Visual
106	Protective finish missing or improper	(a)	-	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:
(a) Sampling and rejection in accordance with MIL-C-5541, Class 1A.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Case, Mine				9292142
					NEXT HIGHER ASSEMBLY
					9292227
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Outside height		0.40%	3.2	Gage
104	Inside height		0.40%	3.2	Gage
105	Edge thickness		0.40%	3.2	Gage
106	Protective finish missing or improper	(a)	-	3.2	Visual
107	True position, outside height to inside height		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.4	Visual
202	Angle incorrect		0.65%	3.2	Visual

NOTES: (a) Sampling and rejection in accordance with TT-C-490, type 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Cup, Outer, Electronics	1 OF 1	9292169
			NEXT HIGHER ASSEMBLY: 9292227

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside length		0.40%	3.2	Gage
102	Inside width		0.40%	3.2	Gage
103	Location of slot		0.40%	3.2	Gage
104	Width of slot		0.40%	3.2	Gage
105	Depth of slot		0.40%	3.2	Gage
106	Angle		0.40%	3.2	Gage
107	Outside width		0.40%	3.2	Gage
108	Outside length		0.40%	3.2	Gage
109	Burrs in MDF slot		0.40%	3.2	Visual
Minor					
201	Thickness		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63394(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Cup, Outer, Spacer				9292176
					NEXT HIGHER ASSEMBLY
					9292227
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside length		0.40%	3.2	Gage
102	Inside width		0.40%	3.2	Gage
103	Height of slot		0.40%	3.2	Gage
104	Outside length		0.40%	3.2	Gage
105	Outside width		0.40%	3.2	Gage
106	Radius inside edge of channel missing		0.40%	3.2	Visual
107	Angle		0.40%	3.2	Gage
108	Width of channel		0.40%	3.2	Gage
109	Burrs on inside edge of channel		0.40%	3.2	Visual
110	Location of slot		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.4	Visual
202	Thickness		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Cover, Spacer				9292113
					NEXT HIGHER ASSEMBLY
					9292122
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Protective finish missing or improper	(a)	-	3.2	Visual
Minor					
201	Thickness		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES: (a) Sampling and rejection in accordance with MIL-C-5541, Class 1A.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292193
4.4.2.7	Spacer, Lens				NEXT HIGHER ASSEMBLY 9292122
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Diameter of S&A cavity		0.40%	3.2	Gage
103	Depth of S&A cavity		0.40%	3.2	Gage
104	Length of propellant cavity		0.40%	3.2	Gage
105	Width of propellant cavity		0.40%	3.2	Gage
106	Depth of propellant cavity		0.40%	3.2	Gage
107	Overall height		0.40%	3.2	Gage
108	Spherical radius		0.40%	3.2	Gage
109	Width of space cup slot		0.40%	3.2	Gage
110	Depth of space cup slot		0.40%	3.2	Gage
111	Location of S&A flat		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Spacer, End Cover Assembly				9292122
					NEXT HIGHER ASSEMBLY
					9292227
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height, max		0.40%	3.2	Gage
102	Adhesive material missing or improperly applied (not 360°)		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Spacer, End Bracket Assembly				9292120
					NEXT HIGHER ASSEMBLY 9292227
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Welding incorrect		0.40%	3.2	Visual
102	Insulator does not cover bottom surface of slotted cup		0.40%	3.2	Visual
103	Tape extends into I.D. of bracket		0.40%	3.2	Visual
104	Length		0.40%	3.2	Gage
105	Width		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63394(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.10	Cup, Slotted, Spacer	1	1	9292117
				NEXT HIGHER ASSEMBLY: 9292120

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height		0.40%	3.2	Gage
102	Base angle		0.40%	3.2	Gage
103	Inside width		0.40%	3.2	Gage
104	Inside length		0.40%	3.2	Gage
105	Width of slot		0.40%	3.2	Gage
106	Location of slot		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Bracket, Spacer End				9292119
					NEXT HIGHER ASSEMBLY
					9292120
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Location of flat surface of S&A hole		0.40%	3.2	Gage
104	Depth of S&A MDF slot		0.40%	3.2	Gage
105	Distance between flat surfaces		0.40%	3.2	Gage
106	Thickness		0.40%	3.2	Gage
107	Angle		0.40%	3.2	Gage
108	Protective finish missing or improper	(a)	-	3.2	Visual
109	Width of MDF slot		0.40%	3.2	Gage
110	Burrs in MDF slot		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:
(a) Sampling and rejection in accordance with QQ-P-35.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Electronics End Bracket Assembly				9292121
					NEXT HIGHER ASSEMBLY
					9292227
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Welding missing or improper		0.40%	3.2	Visual
102	Insulator does not cover bottom surface of slotted cup		0.40%	3.2	Visual
103	Location of slot cup		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Bracket, Electronics End				9292118
					NEXT HIGHER ASSEMBLY 9292121
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Radius from center of S&A hole to inner surface of slot		0.40%	3.2	Gage
103	Length of slot		0.40%	3.2	Gage
104	Location of flat surface of S&A hole		0.40%	3.2	Gage
105	Distance from flat surface of S&A hole to surface of extension		0.40%	3.2	Gage
106	Width of guide		0.40%	3.2	Gage
107	Depth of guide		0.40%	3.2	Gage
108	Burrs in MDF slot		0.40%	3.2	Visual
Minor					
201	Thickness		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63394 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.14	Cup, Slotted, Electronics	1	1	9292185
				NEXT HIGHER ASSEMBLY: 9292121

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height		0.40%	3.2	Gage
102	Base angle		0.40%	3.2	Gage
103	Inside width		0.40%	3.2	Gage
104	Inside length		0.40%	3.2	Gage
105	Width of the slot		0.40%	3.2	Gage
106	Location of slot		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.00%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. There is no test applicable to this section.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

5. PACKAGING

5.1 Preservation and packaging. Each component shall be packaged in accordance with the commerical requirements of MIL-STD-1188. When packaging the case and covers, care must be exercised not to bend or crease the items. Each bracket assembly must be carefully packaged so as not to bend or deform any part.

5.2 Packing. Each component shall be packed in accordance with the commerical requirements of MIL-STD-1188.

5.3 Marking. The marking of the outer box shall be in accordance with the commerical requirements of MIL-STD-1188.

6. NOTES

6.1 Intended use. The metal parts covered by this specification are intended for use in the XM75 anti-tank mine.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of designs for approval. See MIL-A-48078. Submit equipment designs, as required, to Commander, U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAA-M, Dover, New Jersey 07801.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading" U.S ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)" may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data orginally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1345-A-113

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-M-63394 MINE, ANTI-TANK: HE, XM75 METAL PARTS FOR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.