MIL-S-48164A (AR)
28 October 1977
SUPERSEDING
MIL-S-48164 (PA)
21 February 1973

MILITARY SPECIFICATION

SHIPPING AND STORAGE CONTAINER FOR
WARHEAD SECTION: M544
PARTS AND ASSEMBLY FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the metal parts for one type of container, designated as Shipping and Storage Container for Warhead Section: M544.

2. APPLICABLE DOCUMENTS

2.1 Issues of Documents. - The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-5021	-	Test: Aircraft and Missile Welding Operator's Qualification.
MIL-W-13748	-	Welding, Metal Arc: Steel Constructional, Readily Weldable, For High Stressed Joints.
MIL-I-45607	-	Inspection Equipment, Acquisition, Maintenance and Disposition Of.
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.
MIL-M-50508	-	Mounts, Resilient (For use in ammunition shipping container).
* MIL-E-52798	-	Enamel, Alkyd, Camouflage.

FSC: 8140

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS (see 6.4)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

F-9211120 - Shipping and Storage Container for Warhead Section: M544.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with the applicable drawings and specifications.

* 3.1.1 Camouflage Paint. - The camouflage paint shall comply with all requirements specified in MIL-E-52798 (see 4.5.1).

3.2 First Article Testing. - This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

3.3 Parts. - The container parts shall comply with all requirements specified on Drawing (Dwg.) F-9211120, all associated drawings, and with all requirements specified in applicable specifications.

3.3.1 Resilient Mounts (dwg. 9211130). - The resilient mounts shall comply with all requirements specified in MIL-M-50508.

3.4 Welding. - The welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of fusion, penetration and soundness of weld deposits representative of good

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

welding practice. All welding fluxes, scale, and excessive weld spatter, acids or basic solutions shall be completely removed prior to application of any finish. All welding shall be in accordance with applicable specifications and shall be performed by operators who are currently certified as class B operators in accordance with MIL-T-5021.

3.5 Assembly and Disassembly. - The container shall accept the warhead section, or fixture, without evidence of excessive effort, in assembly or disassembly, or closing and securing the cover (see 4.5.2).

3.6 Functioning. - Base and cover assemblies shall adequately fit together as in stacking position, without misalignment of holes or component (indexing) parts, or creation of any unstable stacking conditions (see 4.5.3).

3.7 Performance Characteristics. - The container shall comply with all the requirements specified on drawing F-9211120, and with all requirements specified in this specification, when loaded with a Warhead Section, without evidence of puncture, loose parts or fasteners, broken or permanently set structual members, or distorted or cracked resilient mounts which render the container unusable or unserviceable. Minor dents or creases in non-structual members, bent rings or eyes, and cracks in wooden skids shall not be considered objectionable. The Warhead Section shall be operable after completion of the following tests. All tests shall be conducted at a temperature of plus (+) 80 degrees Fahrenheit (F) plus or minus (±) 20 degrees Fahrenheit.

3.7.1 Fork-Lifting. - The loaded container shall be capable of being lifted by a suitable fork-type lift truck and meet the requirements of 3.7 (see 4.5.4.1).

3.7.2 Stacking. - The loaded container shall be capable of supporting a simulated stacking load equal to four (4) times the weight of a loaded container and meet the requirements of 3.7 (see 4.5.4.2).

3.7.3 Hoisting. - The loaded container shall be capable of carrying an additional load equal to two (2) times the weight of a loaded container and meet the requirements of 3.7, when suspended by the lift provisions provided. (see 4.5.4.3).

3.7.4 Pushing. - The loaded container shall fulfill the requirements of 3.7 (see 4.5.4.4).

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

3.7.5 Towing . - The loaded container shall fulfill the requirements of 3.7 (see 4.5.4.5).

3.7.6 Edgewise Drop. - The loaded container shall fulfill the requirements of 3.7 (see 4.5.4.6).

3.7.7 Cornerwise Drop. - The loaded container shall fulfill the requirements of 3.7 (see 4.5.4.7).

3.7.8 End Impact. - The loaded container shall fulfill the requirements of 3.7 (see 4.5.4.8).

3.7.9 Roll-Over. - The loaded container shall fulfill the requirements of 3.7 (see 4.5.4.9).

3.7.10 Vibration. - The loaded container shall fulfill the requirements of 3.7 (see 4.5.4.10).

3.8 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made part of this detail specification.

4.2 Classification of Inspections. - The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First Article Inspection

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

Part Description	Drawings	Quantity
Shipping and Storage Container, Warhead Section: M544	9211120	1
Mounts, Resilient	9211130	4

4.3.1.1 The first article shall comply with the homogeneity criteria of MIL-A-48078 (PA), Paragraph 4.4.1.

4.3.2 Inspections to be Performed. - See MIL-A-48078 and Table I specified herein. All inspections listed in Table I shall be classified Major unless otherwise specified. Containers so tested shall not be considered as part of the production order and shall not be returned to the lot. In addition, the following test sequence shall be followed:

	Sequence	Test
*	1	Examination for Defects
*	2	Camouflage Paint Thickness
	3	Vibration
	Optional	Edgewise Drop
	"	Cornerwise Drop
	"	End Impact
	"	Roll-over
	"	Fork-lifting
	"	Stacking
	"	Hoisting
	"	Pushing
	"	Towing

4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-S-48164A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Shipping and Storage Container, Warhead Section: M544 and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Shipping and Storage Container, Warhead Section: M544 (Drawing 9211120)				
	Examination for Defects	1		3.3	4.4.2.1
	Vibration Test	1		3.7.10	4.5.4.10
	Edgewise Drop	1		3.7.6	4.5.4.6
	Cornerwise Drop	1		3.7.7	4.5.4.7
	End Impact	1		3.7.8	4.5.4.8
	Roll Over	1		3.7.9	4.5.4.9
	Fork Lifting	1		3.7.1	4.5.4.1
	Stacking	1		3.7.2	4.5.4.2
	Hoisting	1		3.7.3	4.5.4.3
	Pushing	1		3.7.4	4.5.4.4
	Towing	1		3.7.5	4.5.4.5

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Shipping and Storage Container, Warhead Section: M544 and Components	2 OF 2	See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Mount, Resilient (Dwg. 9211130)	4		3.3.1	4.5.4.11
	*Base Assembly (Dwg. 9211121)				
	Camouflage Paint Thickness	1		3.3	4.5.1/Gage
	*Cover Assembly (Dwg. 9211122)				
	Camouflage Paint Thickness	1		3.3	4.5.1/Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling Plans. - Unless otherwise specified in the Classification of Defects, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.1	Shipping and Storage Container, Warhead Assembly: M544				9211120
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Distance between parallel skids (2 places)		0.40%	3.3	Gage
102	Total distance between lower chamfered ends of skids (2 places)		0.40%	3.3	Gage
103	T-bolts missing, damaged or ends not staked		0.40%	3.3	Visual
104	Metal identification plate missing		0.40%	3.3	Visual
105	Any component missing or damaged		0.40%	3.3	Visual
106	Slot in suspension frame assembly missing		0.40%	3.3	Visual
*107	Assembly and dis-assembly		100%	3.5	4.5.2
*108	Functioning		100%	3.6	4.5.3
Minor					
201	Improper torque of bolts or nuts		0.65%	3.3	Gage
202	Alignment of holes for metallic (shipping) seals		0.65%	3.3	Visual
203	Marking misleading or unidentifiable		0.65%	3.3	Visual
204	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-S-46164A (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.1	Shipping and Storage Container, Warhead Assembly: M544				9211120
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
205	Bare spots covered		0.65%	3.3	Visual
206	Split in skid longer than maximum or split less than maximum not repaired properly		0.65%	3.3	Gage/Visual

NOTES:

10

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Base Assembly (Prior to Painting)		9211121
			NEXT HIGHER ASSEMBLY 9211120

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Surface not properly cleaned		0.40%	3.8	Visual
102	Crack in fork strap (2)		100%	3.1	Visual
103	Improper or incomplete welds		100%	3.4	Visual
104	Crack in bracket (4), Resilient Mount		100%	3.1	Visual
Minor	None Defined.				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9211121
4.4.2.3	Base Assembly				NEXT HIGHER ASSEMBLY 9211120
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
*101	Thickness of camouflage paint		100%	3.3	4.5.1/Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual
202	Any component missing or damaged		0.65%	3.3	Visual
203	Protective finish improper		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9211122
4.4.2.4	Cover Assembly (Prior to Painting)				NEXT HIGHER ASSEMBLY 9211120
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Surface not properly cleaned		0.40%	3.8	Visual
102	Improper or incomplete welds		100%	3.4	Visual
Minor	None Defined.				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Cover Assembly				9211122
					NEXT HIGHER ASSEMBLY 9211120
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Parallelism of roll over flange		0.40%	3.3	Gage
•102	Thickness of camouflage paint		100%	3.3	4.5.1/Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual
202	Any component missing or damaged		0.65%	3.3	Visual
203	Protective finish improper		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:15Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9211123
4.4.2.6	Suspension Frame Assembly (Prior to Painting)				NEXT HIGHER ASSEMBLY 9211120
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Surface not properly cleaned		0.40%	3.8	Visual
102	Improper or incomplete welds		100%	3.4	Visual
Minor	None Defined.				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Suspension Frame Assembly				9211123
					NEXT HIGHER ASSEMBLY 9211120
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Slot missing		0.40%	3.3	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual
202	Any damaged or missing component		0.65%	3.3	Visual
203	Protective finish improper		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:15Z
Check the source to verify that this is the currenversion before use.

DRDSC-OA Form 160 Jul 77 Replaces SARPA-OA Form 2567 Feb 74 which is Obsolete

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Aft Support Assembly (Prior to Painting)				9211124
					NEXT HIGHER ASSEMBLY 9211120
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Improper welds or incomplete welds		100%	3.4	Visual
102	Surface not properly cleaned		0.40%	3.8	Visual
Minor	None Defined.				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 20261O-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Aft Support Assembly				9211124
					NEXT HIGHER ASSEMBLY 9211120
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Thickness of finished surface of support		0.40%	3.3	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual
202	Any component missing or damaged		0.65%	3.3	Visual
203	Protective finish improper		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

DD Form 1660, Jul 77 Replaces SARPA-08 Form 2567 Feb 71 which is Obsolete

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9211127
4.4.2.10	Skid				NEXT HIGHER ASSEMBLY 9211120
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Height of skid		0.40%	3.3	Gage
Minor	None Defined.				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9211165
4.4.2.11	Rail				NEXT HIGHER ASSEMBLY 9211123
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Distance from end of rail to slot		0.40%	3.3	Gage
102	Slot missing		0.40%	3.3	Visual
103	Burrs, rough spots and sharp projections		0.40%	3.8	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260122T19:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48164A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9211167
4.4.2.12	Brace, Rail				NEXT HIGHER ASSEMBLY 9211123
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Square cuts missing (2 places)		0.40%	3.3	Visual
102	Length of cuts (2 places)		0.40%	3.3	Gage
103	Burrs, rough spots and sharp projections		0.40%	3.8	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Assembly and Dis-assembly. - Each container shall be subjected to this test. Any container that fails to comply with the requirements in 3.5 shall be classified defective and removed from the lot (see 4.5.2).

4.4.3.2 Functioning. - Each cover assembly and base assembly shall be subjected to this test. Any assembly that fails to comply with the requirements in 3.6 shall be classified defective and removed from the lot (see 4.5.3).

4.4.4 Inspection Equipment. - The inspection equipment required to perform the examinations and tests prescribed in this specification is identified either directly or by reference in the "Paragraph Reference/Inspection Method" column of the First Article Inspection and Quality Conformance Inspection Tables herein. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test Methods and Procedures

* 4.5.1 Camouflage Paint Thickness. - The camouflage paint thickness shall be tested using a dry film type meter. The primer thickness shall be measured prior to applying the camouflage paint. Camouflage paint shall be measured at a minimum of five (5) randomly selected points on the curved exterior of each assembly

4.5.2 Assembly and Dis-Assembly. - The warhead section or fixture shall be loaded and the container strap assemblies re-assembled the cover assembly shall be fitted to the base assembly and T-bolts locked in place. There shall be no excess effort required to assemble the item or cover and to re-assemble and lock the container strap assemblies and T-bolts. The fit-up of cover assembly and locking of T-bolts may be accomplished as part of the shipping requirements.

4.5.3 Functioning. - Each base shall be mounted to a simulated cover (or regular cover) and in turn, a simulated base (or regular base) mounted to each cover. Assemblies (simulated cover and base - simulated base and cover) shall have mounting bolts inserted through all mounting holes without excessive effort, with no mis-alignment of holes, mating (indexing) surfaces or creation of any unstable stacking condition.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

4.5.4 Performance Characteristics. - The warhead section shall be loaded into the container. The container shall then be subjected to the tests listed in paragraphs 4.5.4.1 through 4.5.4.10. All test procedures and equipment shall be approved by the Contracting Officer. (see 4.4.4)

4.5.4.1 Fork-Lifting. - The loaded container shall be lifted clear of another container (or equipment) when stacked, lowered to the floor by a fork-lift truck having forks forty (40) inches, minimum in length. The truck shall be cleared of the container, lifting position reassumed and restacked. This procedure shall be followed in lifting once from each side and three times from each end. The container shall be examined for punctures, broken or bent frame structures and cracked or seperated welds.

4.5.4.2 Stacking. - The required load shall be placed on top of the container. The container shall be examined for permanent set and breakage of structure members.

4.5.4.3 Hoisting. - The loaded container shall be lifted free of any support by means of the lifting eyes or rings.

4.5.4.4 Pushing. - The loaded container shall be pushed across at least fifty (50) feet of rough concrete in a direction parallel to the axis of the container with the ends of the fork truck blades in contact with the skids. The test shall be repeated in a direction normal to the axis of the container with the ends of the fork truck blades in contact with the skids.

4.5.4.5 Towing. - The loaded container shall be pulled across at least fifty (50) feet of rough concrete in a direction parallel to the axis of the container, using the towing provisions provided. The test shall be repeated in a direction normal to the axis of the container.

4.5.4.6 Edgewise Drop. - The loaded container shall be supported at one end of its base on a sill approximately five (5) inches in height and placed at right angles to the skids. The other end of the container shall be raised and allowed to fall freely from a thirty-six (36) inch height to a concrete or similarly hard surface. This test shall be applied to both ends of the container.

4.5.4.7 Cornerwise Drop. - The loaded container shall be supported at one corner of its base on a block approximately five (5) inches in height and with a block approximately twelve

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

(12) inches high placed under the other corner of the same end of the container. The opposite end of the container shall be raised and allowed to fall freely from a thirty-six (36) inch height, measured from the lower of the two (2) corners, to a concrete or similarly hard surface. This test shall be applied to one (1) corner of each end of the container.

4.5.4.8 End Impact. - The loaded container shall be suspended as a pendulum at the end of four (4) cables. The container shall be permitted to swing, with a velocity of 10 ± 1.5 feet per second into a hard, flat, vertical surface. The impact shall be applied to both ends of the container, parallel to the longitudinal axis. Observation shall be made for external damage. Damage to wooden skids shall be disregarded.

4.5.4.9 Roll-Over. - The loaded container, erect on its skids on a hard, level floor, shall be tipped slowly sideways until it falls freely by its own weight to the floor. This process shall be repeated for one (1) revolution with falls from side to top, top to opposite side and from that side to base.

4.5.4.10 Vibration. - The loaded container shall be assembled to a suitable fixture with cover closed and latches fastened in a normal manner. The container assembly shall then be subjected to the vibrations specified in Table II below. The vibrations shall be applied in the vertical axis at 80°F ± 20F°. Adequate safety precautions shall be observed to preclude endangering personnel and equipment.

TABLE II

Test	Frequency Interval Of Forcing Function Hertz (Note 1)	Input	Total Cycle Time Minutes	Bi-Direction Sweep Time Minutes	Number of Sweeps
Cycling	5-9-5	.3DA	5.6	1.4	4
	9-26-9	±1.3 G	14.4	3.6	4
	26-52-26	.036 DA	9.6	2.4	4

NOTE 1: Frequency variation within each interval is 0.8 octave per minute ± 10% (logarethmic sweep rate).

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:15Z
Check the source to verify that this is the current version before use.

4.5.4.11 Resilient Mount. - The first article samples shall be tested in accordance with the MIL-M-50508 First Article Test Plan.

5. PACKAGING

5.1 Marking. - Marking shall be in accordance with MIL-STD-129 and Dwg. 9211120.

5.2 Shipping. - When components from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended Use. - The container covered by this specification is intended for use with the M251 and M201 Warheads.

6.2 Ordering Data. - See MIL-A-48078.

6.3 Submission of Designs for Approval. - See MIL-A-48078. Submit equipment designs, as required, to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Drawings. - Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

* 6.5 Changes from previous issue. - The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 8140-A414

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAA
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE. This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE MIL-S-48164A(AR) SHIPPING AND STORAGE CONTAINER FOR WARHEAD SECTION: M544 PARTS AND ASSEMBLY FOR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.