MIL-T-48643A (AR)
06 August 1987
SUPERSEDING
MIL-T-48643 (AR)
12 December 1985

MILITARY SPECIFICATION

TILE, ARMOR: XM1 AND XM2, PARTS FOR

This specification is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1. Scope. This specification covers requirements and quality assurance provisions for parts for the Tile, Armor XM1 and XM2 Assemblies.

2. APPLICABLE DOCUMENTS.

2.1 Government documents

2.1.1. Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-STD-6866 - Inspection, Penetrant Method of

MIL-W-8611 - Welding, Metal Arc and Gas, Steels and Corrosion and Heat Resistant

MIL-A-48078 - Ammunition Standard Quality Assurance General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 2350
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for - Inspection by Attributes
MIL-STD-171	- Finishing of Metal and Wood Surfaces
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the data of the solicitation.

DRAWINGS

US ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

XM1 PARTS

9392228	- Fastener
9392229	- Foam, Sheet
9392230	- Plate,
9392233	- Cover, Top
9392235	- Spacer
9392236-1	- Attenuator
9392237	- Cover, Bottom
9392241	- Washer, Seal
9392242-1	- U-Seal
9392244	- Grommet

XM2 PARTS

9392228	- Fastener
9392235	- Spacer
9392236-1	- Attenuator
9392236-2	- Attenuator
9392241	- Washer, Seal
9392242-2	- U-Seal
9392244	- Grommet
9392248	- Foam, Sheet, Large
9392249	- Plate, Large
9392254	- Cover, Top, Large
9392258	- Cover, Bottom, Large

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting officer).

2.1.3 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues in effect of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of solicitation.

AMERICAN SOCIETY FOR TESTING MATERIALS (ASTM)

ASTM A 519 Standard Specification for Seamless Carbon and Alloy Steel Mechanical Tubing

(American Society for Testing and Material (ASTM) Standards for test methods are generally available in reference libraries. They are also distritibuted among technical groups and certain federal agencies. Application for copies should be addressed to the American Society Testing Materials, 1916 Race Street, Philadelphia, Pennsylvania 19102).

2.1.4 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on drawings 9392228, 9392229, 9392230, 9392233, 9392235, 9392236-1,9392236-2, 9392237, 9392241, 9392242-1, 9392242-2, 9392244, 9392248, 9392249, 9392254, 9392258, all associated drawings and with all requirements specified in applicable specifications.

3.3 Welds. Welds shall be performed in accordance with MIL-W-8611 by qualified operators and operations.

3.3.1 Weld inspection. Welds shall be visually inspected for discontinuities porosity, and cracks in accordance with MIL-STD-6866.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

3.4 Protective finish. Unless otherwise specified, the exterior and interior of parts that require finishing shall be prepared and finished in accordance with applicable drawings and MIL-STD-171.

3.5 Data requirement. The contractor shall generate data in accordance with requirements of data item description cited in 6.4.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. All parts shall be fabricated in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign material. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspections. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspection shall be conducted on the item:

a. First article inspection

b. Quality conformance inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities indicated.

XM1 PARTS

Part Description	Drawings	Quantity
Fastener	9392228	6
Foam, Sheet	9392229	3
Plate	9392230	6
Cover, Top	9392233	6
Spacer	9392235	3
Attenuator	9392236-1	6
Cover, Bottom	9392237	6
Washer, Seal	9392241	3
U-Seal	9392242-1	6
Grommet	9392244	3

XM2 Parts

Fastener	9392228	6
Spacer	9392235	3
Attenuator	9392236-1	6
Attenuator	9392236-2	6
Washer, Seal	9392241	3
U-Seal	9392242-2	6
Grommet	9392244	3
Foam, Sheet, Large	9392248	3
Plate, Large	9392249	6
Cover, Top, Large	9392254	6
Cover, Bottom, Large	9392258	6

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejections. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

TABLE 1. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Tile, Armor: XM1 or XM2 (as applicable)		SHEET 1 OF 2		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fastener (Dwg. 9392228) Examination for Defects	6		3.2	4.4.2.1
	Foam, Sheet or Foam, Sheet, Large (Dwg. 9392229) or (Dwg. 9392248 as applicable Examination for Defects	3		3.2	4.4.2.2
	Plate, or Plate, Large (Dwg. 9392230) or (Dwg. 9392254) as applicable Examination for Defects	6		3.2	4.4.2.3
	Cover, Top, or Cover, Top,Large (Dwg. 9392233) or (Dwg. 9392254) as applicable (Examination for Defects)	6		3.2	4.4.2.4
	Examination of Welds	6		3.3.1	4.5.2
	Spacer (Dwg. 9392235) Examination for Defects	3		3.2	4.4.2.5
NOTES:					

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

TABLE 1. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-48643A (AR)

PARAGRAPH	TITLE: Tile, Armor: XM1 or XM2 (as applicable)		SHEET 2 OF 2		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Attenuator (Dwg. 9392236-1) or (Dwg. 9392236-2) as applicable Examination for Defects	3		3.2	4.4.2.6
	Cover, Bottom, or Cover, Bottom, Large (Dwg. 9392237) or (Dwg. 9392258) as applicable Examination of Defects	6		3.2	4.4.2.7
	Washer, Seal (Dwg. 9392241) Examination for Defects	3		3.2	4.4.2.8
	U-Seal (Dwg. 9392242-1) or (Dwg. 9392242-2) as applicable Examination for Defects	6		3.2	4.4.2.9
	Grommet Dwg. 9392244 Examination for defects	3		3.2	4.4.2.10

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection Lot Formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specifed in the classification of defects and test tables, sampling plans and major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Fastener				9392228
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Body length		0.40%	3.2	Gage
102	Small outside diameter		0.40%	3.2	Gage
103	Inside diameter (after painting)		0.40%	3.2	Gage
104	Distance to slots		0.40%	3.2	Gage
105	Straightness of body		0.40%	3.2	Gage
106	Material and heat treatment		0.40%	3.2	Certification of Conformance per ASTM 519 and 9392228
Minor					
201	Large outside diameter		0.65%	3.2	Gage
202	Flange thickness, min.		0.65%	3.2	Gage
203	Width of slots (8 places)		0.65%	3.2	Gage
204	Radius at flange		0.65%	3.2	Gage
205	Protective finish not as specified, missing, damaged, incomplete in indicated area or improper color		0.65%	3.4	Visual
206	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:
Defects apply prior to painting except as noted.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9392229 or 9392248 as applicable
4.4.2.2	Foam, Sheet or Foam, Sheet, Large (as applicable)				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Width		0.65%	3.2	Gage
203	Diameter of holes		0.65%	3.2	Gage
204	Thickness		0.65%	3.2	Gage
205	True position of holes		0.65%	3.2	Gage
206	Sides concave		0.65%	3.2	Visual
207	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.3	Plate, or Plate Large (as applicable)	1	1	9392230 or 9392249 as applicable
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Perpendicularity of edge to datum B (2 places)		0.40%	3.2	Gage
102	Flatness		0.40%	3.2	Gage
103	Diameter of hole (4 places)		0.40%	3.2	Gage
104	True position of holes		0.40%	3.2	Gage
105	Thickness		0.40%	3.2	Gage
Minor					
201	Width		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Radius (4 corners)		0.65%	3.2	Gage
204	Protective finish not as specified, missing, or damaged, incomplete or color improper.		0.65%	3.4	Visual
205	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH 4.4.2.4	TITLE Cover, Top, or Cover, Top, Large (as applicable)		SHEET 1 OF 1		DRAWING NUMBER 9392233 or 9392254 as applicable NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Perpendicularity of side to datum B (2 places)		0.40%	3.2	Gage
102	Flatness of outside top surface		0.40%	3.2	Gage
103	Perpendicularity of side to datum A (4 places)		0.40%	3.2	Gage
104	Inside dimension (2 places)		0.40%	3.2	Gage
105	Location of holes		0.40%	3.2	Gage
106	Weld beads not free of voids		0.40%	3.2	Visual
107	Diameter of hole (4 places)		0.40%	3.2	Gage
108	True position of holes		0.40%	3.2	Gage
109	Inward angle of sides not allowed (4 places)		0.40%	3.2	Gage
110	Stock thickness		0.40%	3.2	Gage
111	Nonslip deck covering missing on top exterior surface and not applied to areas as specified on applicable dwg.		100%	3.2	Visual/Gage
Minor					
201	Radius of inside corner (4 places)		0.65%	3.2	Gage
202	Outside length of sidewall (2 places)		0.65%	3.2	Gage
203	Protective finish not as specified, missing, damaged, incomplete or improper color.		0.65%	3.4	Visual
204	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9392235
4.4.2.5	Spacer				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width		100%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
Minor					
201	Protective finish not as specified, missing, damaged, incomplete or improper color		0.65%	3.4	Visual
202	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTIONS

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Attenuator	1 OF 1	9392236-1 or 9392236-2 as applicable
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material			3.1	Certificate of Conformance
Minor					
201	Length		0.65%	3.2	Gage
202	Width (2 sides)		0.65%	3.2	Gage
203	Radius		0.65%	3.2	Gage
204	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9392237 or 9392258 as applicable
4.4.2.7	Cover, Bottom, Sealed or Cover, Bottom, Large (as applicable)				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Perpendicularity of side to datum B		0.40%	3.2	Gage
102	Flatness of outside top surface		0.40%	3.2	Gage
103	Perpendicularity of side to datum A		0.40%	3.2	Gage
104	Outside dimension (2 places)		0.40%	3.2	Gage
105	Diameter of hole (4 places)		0.40%	3.2	Gage
106	True position of holes		0.40%	3.2	Gage
Minor					
201	Stock thickness		0.65%	3.2	Gage
202	Radius of inside corner (4 places)		0.65%	3.2	Gage
203	Outside length of sidewall (4 places)		0.65%	3.2	Gage
204	Protective finish, not as specified, missing, damaged, incomplete in indicated area or improper color		0.65%	3.4	Visual
205	Joint sealant not applied to inside and outside surfaces		0.65%	3.4	Visual
206	Marking not located properly, missing, incomplete or illegible		0.65%	3.2	Visual
207	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Washer, Seal				9392241
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	Material			3.1	Cerificate of conformance
Minor					
201	Thickness		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Inside diameter		0.65%	3.2	Gage
204	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	U-Seal				9392242-1 or 9392242-2 as applicable
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material			3.1	Certificate of Conformation
Minor					
201	Thickness (2 places)		0.65%	3.2	Gage
202	Width of channel opening		0.65%	3.2	Gage
203	Overall width		0.65%	3.2	Gage
204	Height		0.65%	3.2	Gage
205	Length (to be determined at assembly)		0.65%	3.2	Gage
206	Hardness		0.65%	3.2	Gage
207	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9392244
4.4.2.10	Grommet				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material			3.1	Certificate of Conformance
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Width		0.65%	3.2	Gage
204	Groove diameter		0.65%	3.2	Gage
205	Groove width		0.65%	3.2	Gage
206	Groove position		0.65%	3.2	Gage
207	Groove radius		0.65%	3.2	Gage
208	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection

4.5.1 Materials, components and processess. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspection. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Section 3 and 5 of this specification in accordance with 4.4.2 herein and Table 1.

4.5.2 Weld inspection. The welds shall be examined visually. Any unit which fails to meet the requirements of 3.3.1 shall be rejected and removed from the lot.

5. PACKAGING

5.1 Packaging and packing. The parts shall be packaged and packed in accordance with the requirements of level B of MIL-STD-1169.

5.2 Marking. Marking shall be in accordance with the requirements of level B of MIL-STD-1169.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use in the Tile, Armor; XMI and XM2 Assemblies.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection designs for approval See para. 6.2.3 of MIL-A-48078. Submit equipment designs as required to Commander, US Army Armament Research, Development and Engineering Center (ARDEC), ATTN: AMSMC-QAT-I, Picatinny, NJ 07806-5000. The address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

6.4 Data requirements. Deliverable data required by the specification cited as follows:

Data requirement	Applicable Data Item
Ammunition Data Card	DI-MISC-80043

6.5 Contractor. Unless otherwise specified, the word "Contractor", as used throughout this specification, shall mean any supplier or producer or items or material to the Government. This shall include commercial contractors, sub-contractors, Government-Owned, Contractor-Operated (GOCO) and Government-Owned, Government-Operated (GOCO) plants.

6.6 Drawings. Drawings listed in section 2 of this specification under the heading US Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as ARDC, ARRADCOM, Picatinny Arsenal or Rock Island drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.7 Changes from previous issue. The margins of this specification are marked with asterisks (or vertical lines) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.8 Subject term (keyword) listing.

Contractor
Documents
Drawing Numbers
Requirements
Responsibility
Tile, Armor: XM1 and XM2, Parts for

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 2350-A372)

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:35Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-48643A	TILE, ARMOR: XM1 AND XM2, PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* — Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* — Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* — Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-02-10T19:35Z
Check the source to verify that this is the current version before use.