MIL-F-17548B(SHIPS)
AMENDMENT-2
23 October 1978
SUPERSEDING
AMENDMENT-1
17 August 1964

MILITARY SPECIFICATION

FLAME ARRESTER, VENTILATION-EXHAUST

(NAVAL SHIPBOARD USE)

This amendment forms a part of Military Specification MIL-F-17548B(SHIPS), dated 23 January 1962 and is approved for use by the Naval Sea Systems Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under SPECIFICATIONS: Delete "MIL-S-901" and substitute:

"MIL-S-901 - Shock Tests, H.I. (High-Impact); Shipboard Machinery, Equipment and Systems, Requirements For."

3.1 and 3.2: Delete and substitute:

"3.1 Sample for first article inspection. Prior to beginning production, a sample shall be examined and tested as specified in 4.2 (see 6.2)."

PAGE 2

3.4.1: Delete and substitute:

"3.4.1 Shock. The design of the complete flame arrester assembly shall be such that it is capable of passing the high impact shock tests specified in MIL-S-901 for grade A, class I equipment."

PAGES 3 THROUGH 5

4.1 through 4.6.1: Delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

"4.2 First article inspection. Unless otherwise specified (see 6.1), one sample of each size flame arrester covered in the contract or order shall be submitted for first article inspection. First article inspection shall consist of the examination specified in 4.6 and the tests specified in 4.7.1 through 4.7.4.

"4.2.1 Where an identical size flame arrester has successfully passed the first article inspection within a period of not more than 3 years of the date of the contract or order, the first article inspection may be extended by the command or agency concerned.

"4.3 Quality conformance inspection.

"4.3.1 Lot. All flame arresters of the same size offered for delivery at one time shall be considered a lot.

"4.3.2 Sampling for examination. A random sample of flame arresters shall be selected from each lot in accordance with table II for the examination specified in 4.6.

FSC 2040

Source: https://assist.dla.mil -- Downloaded: 202610-18T10:16Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling for examination.

Number of arresters in lot	Number of arresters to be examined	Acceptance number (defectives)	Rejection number (defectives)
Up to 8	All	----	----
9 to 15	7	0	1
16 to 25	10	0	1
26 to 65	15	0	1
66 to 110	20	1	2
111 to 180	25	1	2
181 to 300	35	2	3

"4.3.3 Sampling for tests. A sample flame arrester shall be selected from each lot for the test specified in 4.7.3.

"4.3.4 Inspection. Quality conformance inspection shall consist of the examination specified in 4.6 and the test specified in 4.7.3.

"4.4 Periodic tests. Periodic tests are required to assure continuing satisfactory operation of identical flame arresters. The tests are required under any contract or order for flame arresters of existing design when the contract or order is dated 3 years or more subsequent to the date of the last previous first article examination and tests of an identical flame arrester. Periodic tests shall be conducted on each size flame arrester covered in the contract or order, and shall consist of the examination and tests specified in 4.2.

"4.5 Routine tests.

"4.5.1 Flame arrester assembly. Each flame arrester assembly shall be subjected to the tests specified in 4.7.2 and 4.7.4.

"4.6 Examination. Flame arresters shall be examined and measured to verify compliance with the requirements of this specification not involving tests. Examination shall be conducted as specified in table III. Any flame arrester in the sample containing one or more defects shall not be offered for delivery, and if the number of defective units in any sample exceeds the acceptance number for the sample, the lot represented by the sample shall not be offered for delivery.

TABLE III. Classification of defects.

Categories	Defects
Critical	None defined.
Major	
101	Size not as specified.
102	Incomplete, component parts missing.
103	Evidence of unauthorized material used.
104	Casing or enclosure material thickness; inside and outside dimensions nonconforming.
105	Welding (as applicable) incomplete, not free of cracks, nonfusion, heavy porosity, heavy undercut, slag inclusions or not smooth as specified.
106	Casing or enclosure drilled or punched holes nonconforming; holes missing, location and size not as required.
107	Provisions not provided to hold filter assembly springs in place; springs nonconforming, not located as required.
108	Casing or enclosure hardware (for example, wingnuts, lockwashers, bolts and nuts) not provided, size and length nonconforming.
109	Casing surface not free of cracks, splits, tears, burrs, and sharp edges, or not clean prior to galvanizing or electroplating with zinc as specified.
110	Casing and arresting media coating incomplete, uncoated areas (bare spots), not free of sharp projections.
111	Air filter missing, defective, or not as specified.
112	Access cover and gasket missing, defective, or not as specified.
113	Painting (as applicable) nonconforming.
114	Marking, manufacturer's name or trademark, direction of airflow arrows missing, not permanent, incorrect or illegible.

"

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:16Z
Check the source to verify that this is the current version before use.

4.7: Delete and substitute:

"4.7 Tests."

4.7.1: Delete and substitute:

"4.7.1 Shock test. The flame arrester assembly shall be shock tested on the lightweight machine and the test shall be as specified for type A of MIL-S-901. The shock test shall be conducted prior to tests specified in 4.7.3 and 4.7.4. Evidence of fragmentation or missile effect of parts, or deformation of parts that will permit passage of a flame or destroy the watertight integrity of the casing shall be cause for rejection."

4.7.2: Add, "The pressure drop of the flame arrester with the air filters removed shall not exceed that specified in 3.4.7."

Add as paragraph 4.7.3.5:

"4.7.3.5 Cause for rejection. Failure to prevent the passage of flame from one side of the arrester to the other shall be cause for rejection."

4.7.4: Add, "A drop in hydrostatic gage pressure in excess of 0.125 lb/in^2 in the 10 minute period shall be cause for rejection."

4.7.5: Delete.

PAGE 6

6.1: Add as item (e):

"(e) First article inspection, if other than as specified (see 4.2)."

6.2 and 6.3: Delete and substitute:

"6.2 First article inspection. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection as to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract."

Notice: Delete.

NOTE: The margins of this amendment are marked "#" to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 2040-N143)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:16Z
Check the source to verify that this is the current version before use.