METRIC

DOD-M-24672(SH)
SUPPLEMENT 1
27 October 1986

MILITARY SPECIFICATION

MOLDS, AND MOLD HEATING PLATEN FOR MOLDING ELECTRICAL CONNECTORS AND CABLES (METRIC)

This supplement forms a part of DOD-M-24672(SH), dated 27 October 1986.

SPECIFICATION SHEETS

DOD-M-24672/1(SH) - Molds, Split-Cavity For Molding Plugs (Symbols 713, 713.1, 713.2, 713.3, 713.4, 713.6, 713.7, 713.9, and 713.10).
DOD-M-24672/2(SH) - Mold, Split-Cavity For Molding 90 Degree Plugs Symbols 713.5, and 713.8.
DOD-M-24672/3(SH) - Mold Heating Platen, For Split-Cavity Molds For Plugs Symbols 713 Through 713.10.
DOD-M-24672/4(SH) - Molds - Split Cavity - For Molding Limit Switch Plug, Symbol 1223 For 5-Pin Connectors Using 1SWF-2 (Symbol 1245.1) and FSS-2 Cable (Symbol 1245.2).
DOD-M-24672/5(SH) - Molds - Split Cavity - For Molding Plugs of Three, Five, Nine, Fourteen and Twenty-Four Number Sixteen Contacts - Electrical, Watertight, Submarine.
DOD-M-24672/6(SH) - Molds - Split Cavity - For Molding Plugs Symbols 1170.1, 1171.1, 1173.1, 1174.1, 1175.1, 1176.1, 1177, 1177.1, 1177.2, 1178, 1229, 1230, Type FHOF-9 and RG-130/U Cable.
DOD-M-24672/7(SH) - Mold - Split Cavity - For Ungrounded RG-17A/U Hull Fitting Plug - Symbol 1225.
DOD-M-24672/8(SH) - Mold - Split Cavity For Molding 90-Degree Plugs - Symbol 1224.1 Having Eight Number 16 Contacts.
DOD-M-24672/9(SH) - Molds - Split Cavity for Molding 90 Degree Plugs.
DOD-M-24672/10(SH) - Mold - Split Cavity for Molding 90-Degree Plugs Symbol 1224 Used with Resistance Temperature Detectors.
DOD-M-24672/11(SH) - Mold - For Cable Splices (0.50 Inch Diameter Cable).

Preparing activity:
Navy - SH

AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A Approved for public release, distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:53Z
Check the source to verify that this is the current version before use.