MIL-C-50534A (PA)
AMENDMENT 2
29 January 1975
SUPERSEDING
AMENDMENT 1
14 February 1974

MILITARY SPECIFICATION

CASE, CARTRIDGE, M205,
152MM, PARTS FOR

This Amendment forms a part of Military Specification MIL-C-50534A (MU) dated 15 January 1971 and is approved for use by all Departments and Agencies of the Department of Defense.

Change "XM205E2" to read "M205" wherever it appears at the following locations of the specification:

"Pg 1, Title.

Pg 1, Para 1.1

Pg 2, Para 2.1 Drawings.

Pg 7, Para 4.3.2.1.

Pg 8, Para 4.3.2.2"

Page 1, Para 2.1; Delete the following:

"MIL-P-81705-Film, Transparent, Flexible, Electrostatic-free, Heavy Duty.

MIL-B-131 - Barrier Material, Water-Vaporproof, Flexible.

MIL-F-50533 - Fiber, Acrylic, Fibrillated."

Page 1, Para 2.1; Add the following:

"MIL-F-50809 - Fiber, Acrylic, Fibrillatable."

Page 1, Para 2.1; Add the following specification:

"FEDERAL

PPP-B-26-Bag, Plastic, Polyethylene"

FSC: 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

Page 2, Para. 2.2, Add the following:

"Technical Association of the Pulp and Paper Industry

TAPPI Method T1002 - Drainage time of Pulp for Insulating Board

(Application for copies should be addressed to the Secretary, TAPPI, 360 Lexington Avenue, New York, N.Y.)"

Page 4, Add the following:

"3.9 Drainage rate - fibrillated acrylic fiber shall have a drainage rate of 14.0 ± 2.5 seconds when tested as specified in 4.3.3.8."

Page 10, Add the following:

"4.3.3.8 Drainage Rate (see 3.9), Major defect, Code No. 05001. A random sample shall be selected from each batch and the drainage rate determined in accordance with TAPPI Method T1002. If the sample fails the applicable requirement, the affected batch shall be rejected."

Page 15, Para 4.4.4; Add the following:

"Artificial lighting at the proper intensity and location shall be utilized to provide the best resolution of residue in the gun. A fan shall be utilized at the proper speed and location such that smoke is removed from the gun tube without removing residue. A minimum film time of 15 seconds after breech opening at a minimum camera speed of 40 fps on the tube and 16 fps at the breech is required for each round to allow smoke to clear and to study any residue that does occur. All information concerning residue type, size, location and duration shall be reported for each round. When any residue is observed visually following each firing sequence, the residue shall be removed from the gun, placed in an envelope and identified as to lot number, round number, approximate size and location in weapon and forwarded to Picatinny

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z
Check the source to verify that this is the current version before use.

Arsenal, ATTN: SARPA-QA-A-P for analysis. All residue from one round shall be placed in an envelope together. Residue from different rounds shall be placed in separate envelopes. The Proof Director shall review all films and shall coordinate film observations and visual observations at the gun site. All observations shall be recorded in the Firing Record."

Page 16, Para 4.4.4.1; Add the following:

"If films of more than two rounds are lost from the gun breech or tube for any reason, replacement rounds shall be conditioned as applicable and fired in accordance with 4.4.4."

Page 16, Para 5.1.1; Delete in its entirety and substitute the following:

"5.1.1 Level C - Each case body shall be sealed and shipped in accordance with Dwg C8889489. Each case base shall be sealed and shipped in accordance with Dwg C9242503."

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1320-A256

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:28Z -
Check the source to verify that this is the current version before use.