INCH-POUND

MIL-C-60537(AR)
AMENDMENT 5
30 April 1991
SUPERSEDING
AMENDMENT 4
15 May 1990

MILITARY SPECIFICATION

CARTRIDGE; GRENADE: 5.56MM, M195

This Amendment forms a part of Military Specification MIL-C-60537(MU), dated 23 August 1966, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title, Delete "XM195" and substitute "M195". Make similar model change wherever "XM195" appears in the specification.

PAGE 2

* 3.4, Delete in its entirety and substitute the following:

"3.4 Waterproof. Cartridges shall have a minimum velocity of 140 fps after being submerged under twelve inches (12") of water for 24 hours."

3.5, Line 1, Delete the words "The sample cartridges fired in a horizontal position and" and substitute "The sample cartridges conditioned for a minimum of 4 hours and fired in a horizontal position."

3.8, Delete in its entirety.

4.2.1, Delete in its entirety and substitute the following:

"4.2.1 Initial production sample. At the beginning of regular production, a sample shall be submitted in accordance with the contract requirements and shall consist of 550 cartridges. The sample shall be manufactured using the same material, equipment, processes and procedures as will be used for regular production and shall be obtained from the same source of supply."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:42Z
Check the source to verify that this is the current version before use.

4.3.3.1, Table II - Under Test: After Function and Casualty delete "5/" and substitute "4".

Delete "Primer Sensitivity 6/, 3.8"

4.3.3.1, Delete footnote "5/" in its entirety.

* 4.4.2, Delete in its entirety and substitute the following:

"4.4.2 Waterproof. The water in the tank shall be between 65°F and 75°F for the duration of the test. The cartridges shall be submerged upright to a depth of 12" from the top of the cartridge for 24 hours. After 24 hours, the cartridges shall be removed from the water bath and towel dried. The cartridges shall then be fired for velocity in accordance with appendix A."

4.4.6 Delete in its entirety.

4.4.7 Change paragraph number to 4.4.6.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1330-A363)

Source: https://assist.dla.mil - Downloaded: 2026-10-23T00:42Z
Check the source to verify that this is the current version before use.