MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, RELAY SENSE RESISTORS

1. SCOPE

1.1 This specification covers the detail requirements for one type of circuit card assembly. The requirements of this specification together with the general requirements of MIL-C-60898 comprise the complete requirements for the Relay Sense Resistors Circuit Card Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-C-60898	Circuit Card Assemblies, General Specification for

DRAWINGS

U. S. Army, Frankford Arsenal

D10554184	Electronic Component Assembly, Relay Sense Resistors

PACKAGING DATA SHEET

10554184	Packaging of Circuit Card Assembly, Relay Sense Resistors

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

3, REQUIREMENTS

3.1 Fabrication. The assembly shall be manufactured in accordance with Drawing D10554184 and drawings pertaining thereto.

3.2 General specification. The assembly shall meet the requirements of MIL-C-60898.

3.3 Environmental service conditions. See MIL-C-60898.

3.3.1 Output voltage at temperature extremes. For the conditions of 3.3.2 of MIL-C-60898, the voltage at the Output pins specified in 3.4.1 shall be +3.27 ± 0.47 vdc.

3.4 Electrical performance .

3.4.1 Output voltage. With +22.0 ± 0.1 vdc (10 milliamperes) source appilied between pin 1 (Return) and the pins listed in column 1' of Table I (only one pin receiving voltage at any one time), there shall be a voltage of +3.27 ± 0.175 vdc between the output pins specified in column 2 of Table I and pin 1.

Table I

Input (+22.0 ± 0.1 vdc)	Output (+3.27 ± 0.175 vdc)
Pin 2	Pin 5
3	6
7	9
8	10
11	12
13	15
17	16
19	18
23	22
27	26

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 General. The quality assurance provisions of MIL-C-60898 shall apply to the assembly covered by this detail specification.

4.2 First article inspection. As specified in MIL-C-60898.

4.3 Control test sample. As specified in MIL-C-60898.

4.4 Functional tests. The following characteristics shall be 100 percent tested in accordance with the applicable test method,

	Characteristic	Requirement	Procedure
100	Output voltage	3.4.1	4.5,2.1

4.4.1 Inspection equipment. As specified in MIL-C-60898 and below in 4.4.1.1,

4.4,1.1 Test equipment. In conjunction with 4.4.1, the following test equipment shall be utilized in the performance of the applicable tests as specified in 4.5.

Item		Description
1.	POWER SUPPLY	Nominal value of plus 22 ± 0.1 vdc, current rating of at least 500 ma; ± 1 percent regulating; 0.1 percent maximum ripple.
2,	DIGITAL VOLTMETER	A range of at least 0.0010 to 999.9 vdc; four significant figures; accuracy of at least ± 0.2 percent. Input impedance of at least 10 megohms on all ranges.

4.5 Test methods and procedures

4.5.1 Environmental. As specified in MIL-C-60898 except the requirements of 3.3.1 herein shall be verified during temperature extremes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

4.5.2 Electrical tests.

4.5.2.1 Output voltage. Set the plus 22 vdc POWER SUPPLY, item, 1 of 4$4.1.1, for current limiting to 10 milliamperes. Connect the negative terminals of the POWER SUPPLY and of the DVM, item 2 of 4.4.1.1, to pin 1. Connect the plus lead of the POWER SUPPLY to the input pins, listed in the following table, one at a time. Connect the DVM plus lead to the corresponding output pins listed in the table. The DVM shall indicate a voltage of +3.270 ± 0.175 vdc in each case.

Input	output
Pin 2	Pin 5
3	6
7	9
8	10
11	12
13	15
17	16
19	18
23	22
27	26

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with Packaging Data Sheet 10554184.

6. NOTES

6.1 The notes specified in MIL-C-60898 are applicable to this specification.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 4931-A041

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Frankford Arsenal
ATTN: SARFA-MDM
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.