MILITARY SPECIFICATION

CARRIER, ELECTRONIC WARFARE SYSTEM,
FULL-TRACKED: M1015A1

This amendment forms a part of Military Specification MIL-C-62500(AT), dated 11 September 1985, and is approved for use by US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

3.4.7.1, delete paragraph title and substitute: "Generating system voltage (alternator)."

3.4.7.1.1, delete in its entirety and substitute:

"3.4.7.1.1 Alternator governor frequency variation. The alternator governor system, at any constant load between no-load and full-load, shall maintain the alternator unit frequency constant within ± 1 hertz (Hz). There shall be no sustained periodic frequency oscillations, even within the ± 1 Hz variation at constant (see 4.8.3.7.1)."

3.4.7.1.2, delete in its entirety and substitute:

"3.4.7.1.2 Alternator governor frequency drift. The alternator governor system shall not permit the alternator unit frequency to change more than 3 Hz for an ambient temperature change of 60°F, within the specified temperature range, at any constant load condition from no-load to full-load. The alternator system shall not permit the frequency to change more than 3 Hz during warm-up and stabilization for any load condition from no-load to full-load for any environmental condition specified herein (see 4.8.3.7.1).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:44Z
Check the source to verify that this is the current version before use.

PAGE 8

3.4.11.1, second line, delete "engine-drive" and substitute "engine-driven."

3.4.11.2, line six, add "transient" between "voltage" and "change."

3.4.11.3, line five, add "transient" between "frequency" and "change."

3.4.11.4.1d, delete and substitute: "3.4.11.4.1d. Low speed increaser oil pressure."

3.4.11.4.1e, delete and substitute: "3.4.11.4.1e. Speed increaser temperature high."

3.4.11.4.2c, delete "800" and substitute "50."

PAGE 9

3.4.11.4.3a, add to end of line: "or lower than 380 Hz."

3.4.11.4.3b, delete and substitute: "3.4.11.4.3b. Generator temperature high."

3.4.11.5.3, second line, insert "EW system" between "the" and "load."

3.4.11.5.4, second line, insert "EW system" between "the" and "load."

PAGE 11

3.4.12.3, delete in its entirety and substitute:

"3.4.12.3 Ground rod driver brake. The ground rod driver hoist shall be capable of being locked to prevent accidental dropping of the hammer carriage when the hoist is left unattended (see 4.8.3.11.5)."

3.4.13c, delete "block" and substitute "blocks."

3.4.13e, delete "bracket" and substitute "blocks."

PAGE 12

3.5.5, delete paragraph in its entirety and substitute:

"3.5.5 Acceleration. With the vehicle at a standstill, transmission in the 1-3 range and engine at idle speed, the vehicle shall accelerate from 0 to 20 mph in not more than 18 seconds with rated payload or 11 seconds without load on a smooth, level, hard-surfaced road (see 4.8.4.5)."

PAGE 15

3.9, line 4, delete "rod" and substitute "road".

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:44Z
Check the source to verify that this is the current version before use.

PAGE 17

4.3.1.2.1, delete in its entirety and substitute:

"4.3.1.2.1 Contractor inspection. The contractor shall subject the vehicle to a road test and the FPVI specified in table III to determine conformance to contract and specifications. The road test will be as specified in 4.5. After inspection, the contractor shall submit the acceptable vehicle (and all inspection records and certifications) to the responsible Government inspection element at contractor's plant for preliminary examination."

PAGE 18

Table III, two places for requirements 3.4.7.1 and 3.4.7.1.1, delete "EW generator" and substitute: "Alternator" in both places.

PAGE 19

Table III, six places, delete "EW generator" and substitute "Alternator" in each place.

PAGE 20

Table III, delete "3.4.12.5" and substitute "3.4.12.3."

PAGE 28

4.8.3.7.1, delete in its entirety and substitute:

"4.8.3.7.1 Generating system voltage (alternator) test. To determine conformance to 3.4.7.1 with the alternator operating at specified voltage, measurement shall be made with a voltmeter after the described load is removed. Conformance to 3.4.7.1 shall be determined immediately after the road test."

PAGE 32

6.3.3, first line, in title after "voltage" add "and high current." On second line at end of sentence after "voltage" add "and high current."

Add paragraph:

"6.10 Subject term (key word) listing.

Electronic Warfare System Carrier: M1015A.
Full Tracked Carrier, Electronic Warfare System.
M1015A1, Carrier, Electronic Warfare System.

Custodian:
Army - AT

Preparing activity:
Army - AT

(Project 2350-A360)

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:44Z
Check the source to verify that this is the current version before use.