INCH-POUND

MIL-C-71150 (AR)
AMENDMENT 5
11 February 2000
SUPERSEDING
AMENDMENT 4
9 September 1998

MILITARY SPECIFICATION

CARTRIDGE, 60MM PRACTICE, SHORT RANGE, M766
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-C-71150 (AR), dated 1 November 1993, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

DRAWINGS, Delete: "6.5", and substitute: "6.4".

Delete: "QUALITY ASSURANCE PROVISIONS ... QAP C12961001 - Dud Plug".

PAGE 4

3.3.7.2 Delete in its entirety.

3.4.4: Delete in its entirety and substitute:

"3.4.4 Range and deflection precision. The cartridge shall have a horizontal range probable error (PEr) less than 15 meters for all zones when calculated to the nearest one tenth (0.1) meter. The deflection probable error (PEd) shall be less than 15 meters for all zones when calculated to the nearest one tenth (0.1) meter)."

AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

PAGE 5

3.4.9.1: Delete in its entirety and substitute:

"3.4.9.1 Functioned round. All dud plug heads (regardless of stems) shall blow out of the projectile body upon fuze function."

3.4.9.2: Delete in its entirety and substitute:

"3.4.9.2 Inert round. No dud plug head (regardless of stems) shall exit the projectile body during ballistic flight or upon impact."

PAGE 6

4.3.3, delete requirement "b." in its entirety and substitute:
"b. Three or more duds occur."

Delete "g." and "h." in their entirety and substitute:

"g. If the weapon is damaged by abnormal wear of the interior or of the firing pin, or caused by excessive pressure.

h. Two or more improper impact signatures occur."

Add the following:

"i. All three dud plug heads (regardless of stems) are missing from the projectile body in the inert fuze ballistic test.

j. More than one dud plug head (regardless or stems) remains in a single projectile body upon fuze function except in the case of a particular round that was an actual dud. In this case, paragraph "i." Above applies."

PAGE 7

Table I, Delete under Dud Plug and subsitute the following:

"Dud Plug ...(dwg. 12988971)

Examination for defects ...10(a) ... 3.1 ... 4.4.2.9

Add Note: "(a) Ten (10) samples are required from each mold cavity."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

* Table I, Delete: "Plug, Increment" and substitute: "Increment Plug"

Delete: "(Dwg. 12944200)" and substitute: "(Dwg. 12991840)"

PAGE 10

4.4.2.1, Major 105: Delete:

"Length of large outside diameter section",

and substitute:

"Length between large outside diameter aft face to firing pin point".

PAGE 13

4.4.2.3, Major 102: Delete the word "excessive" and substitute the word "inadequate".

PAGE 14

* 4.4.2.4, Delete Title: "Plug, Increment" and substitute: "Increment Plug"

Delete Dwg. Number: "12944200" and substitute: "12991840"

Add Major Defect 107

Under Examination or Test: "Increment plug pull test"

Under Conformance Criteria: "V"

Under Requirement Paragraph: "3.3.5"

Under Inspection Method Reference: "Test"

Add Major Defect 108

Under Examination or Test: "Longitudinal length of slit"

Under Conformance Criteria: "a"

Under Requirement Paragraph: "3.1"

Under Inspection Method Reference: "Gage"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

Add Minor Defect 204

Under Examination or Test: "Width of slit"

Under Conformance Criteria: "a"

Under Requirement Paragraph: "3.1"

Under Inspection Method Reference: "Gage"

PAGE 15

4.4.2.5: Delete Specials A, B, C, D, E, F and G in their entirety and add the following:

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
"1	Fuze striker in armed position	100%	3.3.4	Gage
2	Breech plug assembly firing pin not below flush after assembly to round	100%	3.3.3	Gage
3	Powder from energetic cartridges found on outside of round	100%	3.1	Visual
Major				
108	Obturator ring missing	100%	3.3.2	Visual
109	Fin tail cracked, damaged or distorted	100%	3.1	Visual
110	Fuze packing clip missing or improperly assembled	100%	3.1	Visual
111	Cartridge assembly fails to fully enter complete round alignment gage	100%	3.3.1	Gage (b)
112	Any dud plugs missing	100%	3.3.7	Visual"

Under Notes: Delete "(a)" and substitute "(b)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

4.4.2.6: Delete Special A in its entirety.

Add the following:

“Major 101 Packing clip missing from fuze ... 100% ... 3.2 ... Visual”

4.4.2.9 Delete in its entirety and substitute:

PARAGRAPH "4.4.2.9	TITLE Dud Plug	SHEET 1 of 1		DRAWING NUMBER 12988971 NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined			
MAJOR				
101	Outside diameter of plug head	(a)	3.1	Gage
102	Thickness of plug head	(a)	3.1	Gage
103	Outside diameter of plug stem	(a)	3.1	Gage
104	Inside diameter of plug stem	(a)	3.1	Gage
105	Length from head flat to end of stem	(a)	3.1	Gage
MINOR				
201	Poor workmanship	30	3.6	Visual
202	Stem slit missing	(a)	3.1	Visual

NOTES: (a) 20 samples from each mold cavity shall be examined for this feature or dimension. The sample of 20 shall incude the first two parts from the beginning of each production run and the last two parts from the end of the run. The remaining samples of (at least sixteen) shall be randomly selected during the production run. Any defects found in any of the 20 samples from each die cavity shall be cause for rejection of all dud plugs produced from that particular die cavity."

4.4.3.1.1: Delete “c.” in its entirety and substitute:

"c. Short rounds, Major defect (see 3.4.2).".

Delete “c.” in its entirety and substitute:

"e. Metal parts separation, Major defect (see 3.4.3).".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

Delete “i.” in its entirety and substitute:

"i. All dud plug heads out of any one projectile in the inert fuze ballistic test, Critical defect (see 3.4.9.2).".

Add the following:

"j. More than one dud plug head (regardless of stems) remains in a single projectile body after fuze function in the live fuze ballistic test, Major defect (see 3.4.9.1)."

4.4.3.1.2: delete requirement "b." in its entirety and substitute: "b. Three or more duds occur."

Delete "i." And "j." in their entirety and substitute:

"i. All three dud plug heads (regardless of stems) are missing from the projectile body in the inert fuze ballistic test.

j. More than one dud plug head (regardless of stems) remains in a single projectile body upon fuze function except in the case of a particular round that was an actual dud. In this case, paragraph "i." above applies.

PAGE 22

4.5.1.1, first paragraph, after second sentence: Add the following: “All rounds shall be fired onto a flat, nongrassy earthen surface that is not marshy or frozen.”

PAGE 23

Add the following:

"4.5.1.3: Accuracy. The individual defelctions and ranges shall be recorded to an accurancy of both to 0.01 meter. Range probable error shall be calculated to the nearest 0.1 meter."

4.5.5, Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

PAGE 24

5.3.1: Delete: “12944136”, and substitute: “12953578”.

PAGE 25

6.9 Add the following:

“6.9 Inspection lot definition. A homogeneous collection of units of product or one shipment of component parts or assemblies from a subcontractor, bearing identification and treated as a unique entity from which a sample is to be drawn and inspected (and tested) to determine conformance with the acceptability criteria.”

6.10 Delete in its entirety.

* 6.11 Delete in its entirety.

6.12 Add the following:

“6.12 Marshy ground. Marshy ground is defined as an earthen surface that contains standing water or free flowing (fluid) mud or a combination of both.”

6.13 Add the following:

“6.13 Frozen ground. Frozen ground is defined as earthen ground within which water has frozen creating a hard surface.”

The margins of this amendment are marked with an asterisk, or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-0242)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.