INCH-POUND

MIL-C-48683A (AR)
AMENDMENT 3
09 June 1993
SUPERSEDING
Amendment 2
25 January 1991

MILITARY SPECIFICATION

CARTRIDGE, 40MM, M918 TP; PROJECTILE ASSEMBLY

This amendment forms a part of MIL-C-48683A (AR), dated 20 October 1987, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Add to 3.4:

"For 1,000 meter test, sound and smoke or sound and flash are also acceptable."

PAGE 5

4.3.1 Change:

From:	"Body Assembly	9399402	50"
To:	"Body Assembly (prior to painting)	9399402	25
	Body Assembly (after painting)	9399402	25"

PAGE 8

Add to Projectile Assembly (Dwg. 9399374) under functioning:

"Petalling (missing petals), 200 5/, 1-2 6/, 3.4, 4.5.6, 4.5.6.2, 4.5.6.3
Petalling (blown case), 200 5/, 0-1, 3.4, 4.5.6, 4.5.6.2, 4.5.6.3".

Add Note 5/:

"5/ Projectiles fired in 135 to 200 feet and rapid fire tests shall be recovered and inspected for missing petals and blown bases."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

Add Note 6/:

"6/ One defect consists of one or more missing petals per projectile."

Table I Change,

From: "Body Assembly (Dwg. 9399402)

Examination for defects	50	3.2	4.4.2.12, 4.4.2.13
Salt Spray	4	3.2	4.5.2.2
Push test of rotating band	50	3.2	4.5.9"

To: "Body Assembly (prior to painting)(Dwg. 9399402)

Examination for defects	25	3.2	4.4.2.12
Body Assembly (after painting) (Dwg. 9399402)	25	3.2	4.4.2.13
Salt Spray	4	3.2	4.5.2.2
Push test of rotating band	50	3.2	4.5.9"

Add to Note 1:

"For 1,000 meter test, sound and smoke or sound and flash are also acceptable."

PAGE 13

Add Major 110

"110. Missing or improperly placed groove, .40, 3.2, Visual".

* Minor 206: Delete in its entirety and substitute the following:

"206	Poor workmanship	.65	2/	3.5	Visual"

* Add Note 2 as follows under Notes:

"2/ Total surface imperfections for nicks, dents, scratches and voids in color shall not exceed 2.5% of the total surface of the part with any individual indentation not to exceed 0.010 in. in depth provided the items pass the salt spray requirements per paragraph 4.5.2.1."

PAGE 15

Add new paragraph 4.4.2.6.1 as included Page 15a.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4.4.2.6.1	Spring, Anti-Creep (alternate)		9399408
			NEXT HIGHER ASSEMBLY 9399390

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined				
MAJOR					
101.	Load Test	125	Acc-1 Rej-2		4.5.3
102.	Length		.40		Gage
103.	Outer diameter		.40		Gage
MINOR					
201.	Poor workmanship		.65		Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 17

* 4.4.2.8, Delete Major 101:

"101. Wall Thickness, Min, .40 1/, 3.2, Gage"

* Add Minor 205:

"205. Wall Thickness, Min, .65 1/, 3.2, Gage"

Change from "201" to "201"
202 202
202 203
201 204

PAGE 18

* 4.4.2.9, Delete Major 101:

"101. Wall Thickness, Min, .40 1/, 3.2, Gage"

* Add Minor 205:

"205. Wall Thickness, Min, .65 1/, 3.2, Gage"

PAGE 20

4.4.2.11, Major 104 and Major 106, Delete in their entirety.

4.4.2.11, Minor 205, Delete in its entirety.

4.4.2.11, Delete Major 107 in its entirety.

4.4.2.11, Major 108, Delete "Total"

4.4.2.11, Change From: "Thickness of groove (6) in base"
To: "Thickness below groove (6) in base"

PAGE 21

Add to 4.4.2.12:

"105. Runout of indicated point of taper with outside large diameter .40, 3.2, Gage/9399396

106. Location, large diameter on taper, .40, 3.2, Gage/9399396".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

Add Major 104:

"104. Missing or improperly placed markings, .40, 3.2, Visual"

* 4.4.2.14, Delete Major 106:

"106. "135-200 Feet test, 50 0-1"

* Add Major 106:

"106. 135-200 Feet test, 50 0-2, 100 1-2"

Delete Major 102:

"102. Gap between body and ogive, rein, .40, 3.2, Gage"

Renumber Majors as follows:

"102. True position, rotating band to ogive diameter, .40, 3.2, Gage"

"103. Assembly torque, prior to sealant cure, 3/ 3/, 3.2, 4.5.4"

"104. Pressure test, 125 3-4, 3.2, 4.5.5"

"105. Functioning,
1000 meter, min, test, 144 6-7 4/, 3.4, 4.5.6, 4.5.6.1
135 to 200 feet, test, 50 0-1 4/, 3.4, 4.5.6, 4.5.6.1".

"106. Airburst, 194 2/ 0-1, 3.4, 4.5.6 4.5.6.1 4.5.6.2"

"107. Petalling (Missing petals), 50 5/, 1-2 6/, 3.4, 4.5.6, 4.5.6.2"

"108. Petalling (Blown base), 50 5/, 0-1, 3.4, 4.5.6, 4.5.6.2"

Add Note 5/

"5/ projectiles fired in 135 to 200 feet and rapid fire tests shall be recovered and inspected for missing petals and blown bases.".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

Add Note 6/

"6/ One defect consists of one or more missing petals per projectile."

4.4.2.14,
Major 106, delete "Rapid fire test, 150 to 656.2 feet (200 meters) 50 0-1 4/ 3.4 . . , 4-5.6.3"

Critical 6, change,
From: "244"
To: "194"

Critical 6, Delete "4.5.6.3"

Major 107, Change,
From: "244"
To: "194"

Major 107, Delete "4.5.6.3"

PAGE 24

4.4.2.14:

Note 2/ Delete "and rapid fire tests."

Add:

"202. Marking missing, improper or illegible, .65 3.2 Visual

4.4.2.14

Add to note 4: "For 1,000 meter test, sound and smoke or sound and flash are also acceptable. "

In note 5, delete: "and rapid fire test"

PAGE 31

4.4.2.2, Delete in its entirety.

PAGE 32

4.5.3 Delete: "Dwg 9399390" and substitute " Dwg. 9399395".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.5.6, change
From: "MK 19 MOD III Grenade Machine Gun"
To: "weapon"
4.5.6.1, Delete "linked" from paragraph. (3 times)
Add to end of paragraph: "All tests performed shall be observed from the gun position."
4.5.6.1, Delete "linked" from paragraph.
Change
From: "Machine gun"
To: "weapon"
4.5.6.2, Delete "linked" from paragraph.
Change
From: "Machine gun"
To: "weapon"
4.5.6.3, Change
From: "Machine gun"
To: "MK 19 MOD III Grenade Machine Gun"
Add to end of paragraph: "This test shall be performed at an approved government installation."

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1310-A463)

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:36Z
Check the source to verify that this is the currentversion before use.