MIL-V-51195B(EA)
14 June 1979
SUPERSEDING
MIL-V-51195A(MU)
13 April 1967

MILITARY SPECIFICATION

VALVE, OUTLET, C19

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers an outlet valve which has a plastic valve seat, cover and a rubber disk.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

FEDERAL

FED-STD-123 Marking for Shipment (Civil Agencies).

MILITARY

MIL-STD-l05 Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

CHEMICAL SYSTEMS LABORATORY

C5-9-159 - Valve, Outlet, C19.

FSC 4240

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn: DRDAR.TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:52Z
Check the source to verify that this is the current version before use.

standard fittings. Removal of the plated portion after inspection

B136-44-1-9 - Indicator, Inet and Outlet Valve Resistance, Q212,
B136-202-12 - Indicator, Outlet Valve Leakage, M4A1.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer,)

3. REQUIREMENTS.

3.1 Materials and components.

3.1.1 Materials. All materials cited On Drawing C5-9-159 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the outlet valve shall conform to the specifications and drawings listed-on Drawing C5-9-179 and subsidiary drawings.

3.2 Manufacture and assembly. The outlet valve shall be manufactured and assembled as specified on Drawing C5-9-159.

3.3 Resistance to airflow. The assembled outlet valve shall have a resistance not exceeding a pressure differential of 22 millimeters (mm) of water, (215 Pascals (Pa)) at an airflow rate of 85 liters per minute, when tested as specified in 4.2.4.1.

3.4 Leakage. Leakage through the assembled valve shall not exceed 15 milliliters of air per minute, at a pressure differential of 25 mm of water, (245 Pa), when tested as specified in 4.2.4.2.

3.5 Workmanship. The outlet valve assembly shall be free from damage, such as dents, distortion, roughened valve seat, and torn disc that would impair its function, and foreign matter such as dirt, oil or viscous material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection:

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:52Z
Check the source to verify that this is the current version before use.

unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection

4.2.1 Lotting. A lot shall consist of the outlet valves produced by one manufacturer, from the same materials, under essentially the same manufacturing conditions.

4.2.2 Sampling for examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedure. .

4.2.3.1 Examination and nondestructive tests. Outlet valves shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

4.2.3.2 Classification of defects.

(a) Valve, outlet, C19 (DwF C5-9-159).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 0.10 percent defective	
101	Resistance to airflow	4.2.4.1
102	Leakage	4.2.4,2
	AQL 1.0 percent defective	
103	Component missing, incorrect or incorrectly assembled	
104	Marking illegible or incorrect	
105	Workmanship (3.5)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:52Z
Check the source to verify that this is the current version before use.

4.2.4 Tests.

4.2.4.1 Resistance to airflow. The resistance to airflow shall be determined with the Q212 Inlet and Outlet Valve Resistance Indicator in accordance with B136-44-1-9.

4.2.4.2 Leakage. The leakage shall be determined with the M4A1 Outlet Valve Leakage Indicator in accordance with B136-45-203-12.

5. PACKAGING

5.1 Interplant shipment (see 6.4). The outlet valve shall be packaged end packed to provide adequate protection from physical damage from the supply source to the first receiving activity for immediate use of further processing. Shipping containers shall be in compliance with the rules and regulations applicable to the mode of transportation. Marking shall be in conformance with FED-STD-123,

5.2 Repair part, When this item is procured for storage and issue as a repair part, preservation, , packaging, packing and marking shall be as specified on the repair part packaging data sheet which is identified by the National Stock Number for the repair part.

6. NOTES

6.1. Intended use. This outlet 'valve is intended for use on the M22 protective mask, the M13Al hospital protector headpiece, the M13 and M13Al filter units, and M4 protective suit.

6.2 Ordering data. Procurement documents should specify title, number and date of this specification.

6.3 International interest. Certain provisions of this specification are the subject of international standardization agreement ABCA-AMY-STD-154. When amendment, revision or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization officer, if required.

6.4 Iterplant shipment. Packaging for supplies and materials which will not enter the military supply system, Typical interplant shipments are shipments from the vendor 'to a subcontractor or a prime contractor, or from a subcontractor to a prime contractor, or from a vendor or contractor to a military arsenal or plant.

Source: https://assist.dla.mil -- Downloaded: 2026t0-22T20:52Z
Check the source to verify that this is the currentversion before use.

Custodian :

Army-EA

International interest (see 6.3)

Preparing activity:

Army - EA

Project No. 4240-A549

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:52Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:52Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DOD-314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament Research & Development Command
ATTN: DRDAR-TSC-S
Aberdeen Proving Ground, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-L-51195D

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:52Z
Check the source to verify that this is the current version before use.