INCH-POUND

MIL-F-71149 (AR)
AMENDMENT 3
31 July 1996
SUPERSEDING
AMENDMENT 2
09 May 1995

MILITARY SPECIFICATION

FUZE, POINT DETONATING, PRACTICE, M779
WITH PYROTECHNIC SIGNATURE CARTRIDGE

This amendment forms a part of MIL-F-71149 (AR), dated 01 November 1993, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.10: Delete in its entirety and substitute:

"3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive when applied to the forward joint and the rear section joint after it is properly assembled to an M779 fuze body."

PAGE 7

4.3.1, under Part Description: Delete: "Packing Preformed AMS 3303 O-Ring ... 12929048 ... 10".

Delete: "Body, Fuze ... 12944162".

and substitute: "Body, Fuze ... 9343991".

* Delete part description "Metal Parts Assembly, Fuze M779".

and substitute: "Metal Parts Assembly".

AMSC N/A **FSC 1390**

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

PAGE 8

Table I, under Examination or test: Delete: "Body, Fuze ... (Dwg. 12944162)"

and substitute: "Body, Fuze ... (Dwg. 9343991)".

PAGE 13

Table I, Section pertaining to the Packing Preformed AMS 3303 O-Ring: Delete in its entirety.

* Table I, Delete under Examination or Test "Metal Parts Assembly, Fuze M779" and substitute "Metal Parts Assembly".

PAGE 14

Table I, Under Loading Assy, Fuze M779: Delete: "Fuze chamber operation test:,

and substitute: "Fuze sleeve and chamber operation test".

Under Conformance Criteria: Delete: "25",

and substitute: "50".

Under Fuze, PD, Practice, M779: Delete: "Fuze sleeve and chamber operation test ... 50 ea ... 3.9 ... Test/4.5.16".

PAGE 19

4.4.2.1, Major 111: Delete: "True position of minor striker hole to rear cavity",

and substitute: "Location of minor striker hole".

4.4.2.1, Sheet 1 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

PAGE 20

4.4.2.1, Sheet 2 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

PAGE 21

4.4.2.1, Sheet 3 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

PAGE 22

4.4.2.2, Minor 203: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

PAGE 42

4.4.2.21: Delete in its entirety.

PAGE 43

* 4.4.2.22, Delete "Fuze M779" from the title block.

PAGE 44

4.4.2.22, Major 102: Delete in its entirety.

* 4.4.2.22, Delete "Fuze M779" from the title block.

PAGE 50

* 4.5.5, Line 2, after the word “fuzes” add the following: "(For lot acceptance testing, primed hulls with inert filler may be substituted for the full-up spotting cartridge. Primed hulls shall not be dropped more than one time before being discarded.)".

The margins of this amendment are marked with an asterisk, or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-0847)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.