INCH-POUND

MIL-F-71149 (AR)
AMENDMENT 6
03 February 1999
SUPERSEDING
AMENDMENT 5
12 November 1997

MILITARY SPECIFICATION

FUZE, POINT DETONATING, PRACTICE, M779
WITH PYROTECHNIC SIGNATURE CARTRIDGE

This amendment forms a part of MIL-F-71149 (AR), dated 01 November 1993, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.10: Delete in its entirety and substitute:

"3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive when applied to the forward joint and the rear section joint after it is properly assembled to an M779 fuze body."

PAGE 7

4.3.1, under Part Description: Delete: "Packing Preformed AMS 3303 O-Ring ... 12929048 ... 10".

Delete: "Body, Fuze ... 12944162".

and substitute: "Body, Fuze ... 9343991".

Delete part description "Metal Parts Assembly, Fuze M779".

And substitute: "Metal Parts Assembly".

AMSC N/A **FSC 1390**

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

* Add the following:

Under Part Description: "Ball, Setback"

Under Drawing: "12988976"

Under Quantity (EA): "10"

PAGE 8

Table I, under Examination or test: Delete: "Body, Fuze ... (Dwg. 12944162)"

and substitute: "Body, Fuze ... (Dwg. 9343991)".

PAGE 13

Table I, Section pertaining to the Packing Preformed AMS 3303 O-Ring: Delete in its entirety.

PAGE 14

Table I, Under Loading Assy, Fuze M779: Delete: "Fuze chamber operation test:,

and substitute: "Fuze sleeve and chamber operation test".

Under Conformance Criteria: Delete: "25",

and substitute: "50".

Under Fuze, PD, Practice, M779: Delete: "Fuze sleeve and chamber operation test ... 50 ea ... 3.9 ... Test/4.5.16".

* Table I:

Under Examination or Test: "Ball, Setback
(Dwg. 12988976)
Examination for defects"

Under Conformance Criteria: "10"

Under Requirement Paragraph: "3.2"

Under Inspection Method Reference: "4.4.2.26"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

PAGE 19

4.4.2.1, Major 111: Delete: "True position of minor striker hole to rear cavity",

and substitute: "Location of minor striker hole".

4.4.2.1, Sheet 1 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

PAGE 20

4.4.2.1, Sheet 2 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

Delete Major 120 in its entirety.

PAGE 21

4.4.2.1, Sheet 3 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

PAGE 22

4.4.2.2, Minor 203: Delete in its entirety.

PAGE 42

4.4.2.21, Delete in its entirety.

PAGE 43

4.4.2.22, Delete "Fuze M779" from the title block.

PAGE 44

4.4.2.22, Major 102: Delete in its entirety.

Add Minor 203 as follows: "203 ... Setback pin hole seal missing or not adhering ... V ... 3.2 ... Visual"

4.4.2.22, Delete "Fuze M779" from the title block.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

PAGE 48

* Add Paragraph 4.4.2.26 as follows:

PARAGRAPH 4.4.2.26	TITLE Ball, Setback	SHEET 1 OF 1		DRAWING NUMBER 12988976 NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Diameter of ball (Two places. See Note 1.)	III	3.2	Gage
Minor 201	Poor workmanship	V	3.16	Visual

NOTES:
1. The second diameter of ball measurement shall be taken 90° (normal) to the axis of the first diameter of ball measurement."

PAGE 50

4.5.5, Line 2, after the word "fuzes" add the following: "(For lot acceptance testing, primed hulls with inert filler may be substituted for the full-up spotting cartridge. Primed hulls shall not be dropped more than one time before being discarded.)".

PAGE 52

4.5.9, Line 3, delete: "of 10 +/- 2 pounds" and substitute: "in accordance with drawing 9344005".

The margins of this amendment are marked with an asterisk, or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-0872)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.