INCH-POUND

MIL-K-71151 (AR)
AMENDMENT 5
12 August 1999
SUPERSEDING
AMENDMENT 4
9 September 1997

MILITARY SPECIFICATION

KIT, REFURBISHMENT, FOR CARTRIDGE, 60MM, PRACTICE,
SHORT RANGE, M766
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-K-71151 (AR), dated 1 November 1993, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

DRAWINGS, Delete: "6.5", and substitute: "6.4".

PAGE 3

3.3: Delete: "propelling charge", and substitute: "ignition cartridge".

Line 2: Delete the first two words: "flush to".

3.6.1 Delete in its entirety and substitute:

"3.6.1 Misfires. The cartridges shall not fail to fire from the weapon when they are initially dropped into it."

AMSC N/A FSC 1315
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

3.6.4: Delete in its entirety and substitute:

"3.6.4 Range and deflection precision. The cartridge shall have a horizontal range probable error (PEr) less than 15 meters, for all zones when calculated to the nearest one tenth (0.1) meter. The deflection probable error (PEd) shall be less than 15 meters for all zones when calculated to the nearest one tenth (0.1) meter."

3.6.6: Add: "unobstructed", before the word "flight".

3.6.9.1: Delete in its entirety and substitute:

"3.6.9.1 Functioned round. All dud plug heads (regardless of stems) shall blow out of the projectile body upon fuze function."

3.6.9.2 Delete in its entirety and substitute:

"3.6.9.2 Inert round. No dud plug head (regardless of stems) shall exit the projectile body during ballistic flight or upon impact."

3.9.2: Delete in its entirety.

4.3.3: Delete requirement "b." in its entirety and substitute: "b. Three or more duds occur."

Delete "g." and "h." in their entirety and substitute:

"g. If the weapon is damaged by abnormal wear of the interior or of the firing pin, or caused by excessive pressure.

h. Two or more improper impact signatures occur."

Add the following:

"i. All three dud plug heads (regardless of stems) are missing from the projectile body in the inert fuze ballistic test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

j. More than one dud plug head (regardless of stems) remains in a single projectile body upon fuze function except in the case of a particular round that was an actual dud. In this case, paragraph "i." above applies."

* 4.3.3: Delete “j” in its entirety and substitute:

“j. More than one dud plug head (regardless of stems) remains in a single projectile body upon fuze function except in the case of a particular round that was an actual dud. In this case, paragraph "i." above applies."

PAGE 7

Table I: Delete under Dud Plug and add the following:

"Dud Plug ...(dwg. 12988971)

Examination for defects ...10(a) ... 3.1 ... 4.4.2.11

Add note:

"(a) Ten (10) samples are required from each mold cavity."

PAGE 11

4.4.2.1, Major 105: Delete:

"Length of large outside diameter section",

and substitute:

"Length between large outside diameter aft face to firing pin point".

PAGE 13

4.4.2.3, Major 102: Delete the word "excessive" and substitute the word "inadequate".

PAGE 15

4.4.2.5: Delete Special A in its entirety.

Critical: Add the following:

"1 Fuze striker in armed position ... 100% ... 3.1 ... Visual".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

PAGE 16

4.4.2.6: Delete Major 103 in its entirety.

PAGE 20

4.4.2.10: Delete Specials A, B, C, D, E, F and G in their entirety and add the following:

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
“1	Fuze striker in armed position	(a)	3.1	Gage
2	Breech plug assembly firing pin not below flush after assembly to round	(a)	3.3	Gage
3	Powder from energetic cartridges found on outside of round	(a)	3.1	Visual
Major				
105	Red marking visible on fuze striker	(a)	3.4	Visual
106	Fuze packing clip missing or improperly assembled	(a)	3.1	Visual
107	Obturator ring missing	(a)	3.1	Visual
108	Any dud plugs missing	(a)	3.9.1	Visual”

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

4.4.2.11, Delete in its entirety and substitute:

PARAGRAPH	TITLE			DRAWING NUMBER
"4.4.2.11	Dud Plug	SHEET 1 of 1		12988971
				NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined			
MAJOR				
101	Outside diameter of plug head	(a)	3.1	Gage
102	Thickness of plug head	(a)	3.1	Gage
103	Outside diameter of plug stem	(a)	3.1	Gage
104	Inside diameter of plug stem	(a)	3.1	Gage
105	Length from head flat to end of stem	(a)	3.1	Gage
MINOR				
201	Poor workmanship	30	3.6	Visual
202	Stem slit missing	(a)	3.1	Visual

NOTES: (a) 20 samples from each mold cavity shall be examined for this feature or dimension. The sample of 20 shall incude the first two parts from the beginning of each production run and the last two parts from the end of the run. The remaining samples of (at least sixteen) shall be randomly selected during the production run. Any defects found in any of the 20 samples from each die cavity shall be cause for rejection of all dud plugs produced from that particular die cavity."

4.3.3.1.1: Delete "c." and "e." in their entirety and substitute:

"c. Short rounds, major defect (see 3.6.2).

e. Metal parts separation, major defect (see 3.6.3).

Delete "h." and "i." in their entirety and substitute:

"h. Improper impact signature, major defect (see 3.6.8).

i. All dud plug heads out of any one projectile in the inert fuze ballistic test, critical defect (see 3.6.9.2)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

PAGE 21 (cont'd)

Add the following:

"j. More than one dud plug head (regardless of stems) remains in a single projectile body after fuze function in the live fuze ballistic test, Major defect (see 3.4.9.1)."

4.3.3.1.2: Delete requirement "b." in its entirety and substitute: "b. Three or more duds occur."

Delete "i." and "j." in their entirety and substitute:

"i. All three dud plug heads (regardless of stems) are missing from the projectile body in the inert fuze ballistic test.

j. More than one dud plug head (regardless of stems) remains in a single projectile body upon fuze function except in the case of a particular round that was an actual dud. In this case, paragraph "i." above applies.

* 4.4.3.1.1: Delete "j." in its entirety and substitute:

"j. More than one dud plug head (regardless of stems) remains in a single projectile body after fuze function in the live fuze ballistic test, Major defect (see 3.4.9.1)."

* 4.4.3.1.2: Delete "j." in its entirety and substitute:

"j. More than one dud plug head (regardless of stems) remains in a single projectile body upon fuze function except in the case of a particular round that was an actual dud. In this case, paragraph "i." above applies."

PAGE 22

4.5.1.1, First paragraph, after third sentence: Add the following: "All rounds shall be fired onto a flat, nongrassy earthen surface that is not marshy or frozen."

4.5.1.1, d.: Delete "4.4.3.2.1", and substitute: "4.4.3.1.2".

PAGE 23

Add the following:

"4.5.1.3: Accuracy. The individual deflections and ranges shall be recorded to an accuracy of both to 0.01 meter. Range probable error shall be calculated to the nearest 0.1 meter."

4.5.4, Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

6.9 Add the following:

"6.9 Inspection lot definition. A homogeneous collection of units of product or one shipment of component parts or assemblies from a subcontractor, bearing identification and treated as a unique entity from which a sample is to be drawn and inspected (and tested) to determine conformance with the acceptability criteria."

6.10 Delete in its entirety.

6.11 Add the following:

"6.11 Outlier test. When the accept criteria is not met and if it is suspected that a statistical outlier may be present in the sample of 30 observations. Arrange the observed values in order of increasing magnitude (X1, X2 .. Xn-1, Xn). Using the statistics calculated for the sample, calculate Tn where:

$$Tn = \frac{Xn - \bar{X}}{s}$$

If X1, the smallest value, rather than Xn, is the doubtful value the test criterion is:

$$T1 = \frac{\bar{X} - X1}{s}$$

Where:

$\bar{X}$ = arithmetic average of all n values
s = estimate of the population standard deviation based on the sample data calculated as follows:

$$s = \left[\frac{\sum\left(x_i - \bar{x}\right)^{1/2}}{n-1}\right] = \left[\frac{n\sum x_i^2 - \left(\sum x_i\right)^2}{n(n-1)}\right]^{1/2}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.

If Tn is less than or equal to 2.745, the highest value may not be eliminated. The lot is rejected. If Tn is greater than or equal to 2.745, the largest value obtained in the sample shall be eliminated and the sample statistics X and s shall be recalculated using the twenty-nine remaining values. This shall be compared to the accept criteria. If the criteria is met, accept the lot. If not, the same procedure shall be followed for the Xn-1 observation. Calculate Tn-1 based on the new statistics of the remaining sample of 29. If Tn-1 is less than or equal to 2.730, the lot is rejected. If Tn-1 is greater than or equal to 2.730, then this observation shall be eliminated and the sample statistics calculated based on the remaining 28 observations. If these values meet the accept criteria, accept the lot. If the accept criteria is still not met, reject the lot."

6.12 Add the following:

"6.12 Marshy ground. Marshy ground is defined as an earthen surface that contains standing water or free flowing (fluid) mud or a combination of both."

6.13 Add the following:

"6.13 Frozen ground. Frozen ground is defined as earthen ground within which water has frozen creating a hard surface."

The margins of this amendment are marked with an asterisk, or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-0237)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:24Z
Check the source to verify that this is the current version before use.