INCH-POUND

MIL-P-50944B (AR)
AMENDMENT 3
9 December 1992
SUPERSEDING
AMENDMENT 2
20 April 1984

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE: M483A1
NON-METALLIC HARDWARE FOR

This Amendment forms a part of Military Specification MIL-P-50944B (AR), dated 26 May 1982, and is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* 4.3.1 Add:

"Spacers (Alternate) 12597947-1 25
Spacers (Alternate) 12597947-2 25"

PAGE 4

* TABLE I Add:

"Spacers, Alternate (12597947-1)				
Examination for defects	25	-	3.2	4.4.2.5
Spacers, Alternate (12597947-2)				
Examination for defects	25	-	3.2	4.4.2.5"

PAGE 6

4.4.2.1 Delete Major Defect 101.

DISTIRBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

PAGE 8

4.4.2.2 Add Major Defect 115 and Note (a) as follows:

"115 Improper color Note (a) 3.2 Visual

Note (a) One (1) sample from each mold representing the batch of raw material used."

PAGE 9

4.4.2.3 Add Major Defect 110 and Note (a) as follows:

"110 Improper color Note (a) 3.2 Visual
Note (a) One (1) sample from each mold representing the batch of raw material used."

PAGE 10

* 4.4.2 Add the attached new table paragraph 4.4.2.5.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:44Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Spacer (Alternate)				12597947
					NEXT HIGHER ASSEMBLY 9241400
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Profile outside of tolerance zone		.40%	3.2	Gage
102	Dimension "A" improper		.40%	3.2	Gage
103	Thickness of rib improper		.40%	3.2	Gage
104	Width of rib improper		.40%	3.2	Gage
105	Improper color		(a)	3.2	Visual
106	Overall height		.40%	3.2	Gage
Minor					
201	Surface variations outside permitted zone		.65%	3.2	Visual
202	Blends at ends of ribs not present		.65%	3.2	Visual
203	Excess gating		.65%	3.2	Visual (b)
204	Distance from center of rib to cavity		.65%	3.2	Gage
205	Distance from outside of rib to cavity		.65%	3.2	Gage
206	Width of cavity		.65%	3.2	Gage
207	Overall width of spacer		.65%	3.2	Gage
208	Major radius of spacer		.65%	3.2	Gage
209	Distance from top of part to cavity		.65%	3.2	Gage
210	Wall thickness		.65%	3.2	Gage
211	Thickness of cross members (3 places)		.65%	3.2	Gage
212	Dimension "B" improper		.65%	3.2	Gage
213	Radii's and bevels improper		.65%	3.2	Gage
214	Evidence of poor workmanship		.65%	3.3	Visual

NOTES:
(a) One (1) sample from each mold representing the batch of raw materials used.
(b) When this characteristic is in doubt, gaging may be used to determine acceptability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:44Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-AC48)

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:44Z
Check the source to verify that this is the current version before use.