MIL-T-63264 (AR)
AMENDMENT 2
16 JUN 1989
SUPERSEDING
AMENDMENT 1
11 October 1979

MILITARY SPECIFICATION

TEST, SET, ELECTRONICS SYSTEMS: M92

This amendment forms a part of Military Specification MIL-T-63264 (AR), dated 3 May 1978, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Under "Military Standards":

Delete the following:

"MIL-STD-331 -Fuze and Fuze Components, Environmental and Performance Tests For".

* Add:

"MIL-STD-202 -Test Methods For Electronic and Electrical Component Parts".

PAGE 3

3.4, Delete: "except for temperature humidity which is contained in MIL-STD-331".

3.4.1, Add to end of paragraph: "using curve AW of Figure 514.2-7".

3.4.2: Delete "Test 105.1 of MIL-STD-331 ..." and substitute "Method 507.1, Procedure I".

* 3.5: Delete "MIL-STD-1460, except that para. 4.1.3 does not apply" and add "MIL-S-45743 and MIL-S-46844".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

PAGE 5

* TABLE I, line 2, Transportation Vibration: Add "(a)" in examination or test column.

Add to Notes: "(a) Order of tested as listed".

PAGE 7

4.4.2.1: Delete Minor Defect 201.

PAGE 10

4.4.2.4, under Examination or Test column: Specify Major Defects 102 and 103 and Minor Defect 201 are to be performed prior to assembly.

PAGE 14

* 4.4.2.8 Change the title from: "Electronic Flash Assembly" to "Printed Wiring Board Assembly".

Change Drawing Number from: "926713" to "12624794".

Add Major 103: "Any part missing, damaged or improperly assembled to the x-y orientation, ..., 0.40%, 3.2, Visual".

PAGE 35

* Add: "Figure 10" to Schematic.

PAGE 41

4.5.1, Test #5, Step 2: Delete "16-20" and substitute "16-30".

4.5.2: Delete in its entirety.

PAGE 43

4.5.3, Add after "Procedure X": "using curve AW of Figure 514.2-7".

4.5.4: Delete in its entirety and substitute:

"4.5.4 Temperature humidity. Using equipment in accordance with 4.4.4, subject each first article unit to Test Method 507.1, Procedure I of MIL-STD-810. Replace Step 6 and 7 of test method with the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.

Step 6 - At the end of the tenth cycle, remove and inspect the test item and condition the test item at 25 ± 5° (ambient) for at least one (1) hour, operate the test item and obtain results in accordance with General Requirements, 3.2.

Any item which fails to meet the applicable requirements shall cause the first article sample to be rejected."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project: 4925-A048)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:30Z
Check the source to verify that this is the current version before use.