MIL-B-48343(AR)
AMENDMENT 1
8 February 1982

MILITARY SPECIFICATION

BATTERY, PRIMARY, RESERVE, AMMONIA,
5 MILLIAMPERE HOUR CAPACITY

This amendment forms a part of Military Specification MIL-B-48343(AR), dated 17 May 1978, and is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.8: Delete "twenty-five degrees centigrade plus five degrees centigrade" and substitute "twenty-five degrees centigrade plus or minus five degrees centigrade".

PAGE 7

Table I: Delete "Sheet 1 of 4" and substitute "Sheet 1 of 5".

PAGE 8

Table I: Delete "Sheet 2 of 4" and substitute "Sheet 2 of 5".

PAGE 9

Table I: Delete "Sheet 3 of 4" and substitute "Sheet 3 of 5" as attached.

PAGE 10

Delete in its entirety and substitute new Page 10, as attached.

PAGE 10A

Add new specification Page 10A as attached.

PAGE 23

4.4.2.12, Major 106, change "4.5.9.5" to "4.5.9.5/4.4.3.7.2".
Major 107, change "4.4.3.7.2" to "4.4.3.7.3".

FSC 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

PAGE 28

4.4.3.7.3: Change paragraph 4 from "Test temperature and the numbering samples per temperature group shall be in accordance with 4.4.3.7.4." to "Test temperature and the number of samples per temperature group shall be in accordance with the requirements of 4.4.3.7.4."

PAGE 29

4.4.3.7.4, Table III: Change "For sample size of 200 batteries" to "For sample size of 175 batteries".

PAGE 30

4.4.4: Delete in its entirety and substitute "4.4.4 Inspection equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit inspection equipment designs for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078."

PAGE 34

4.5.9.2, Last subparagraph: Change "5 1/4C" to "5°C".

PAGE 35

4.5.9.5: Change "During first artible acceptance testing the contractor shall continuously monitor the battery voltage until it drops below 2.7 volts." to "During first article acceptance testing, the contractor shall monitor the battery voltage a minimum of once an hour until it drops below two and seven tenths (2.7) volts".

4.5.10.3: Change "Test Method 104 of MIL-STD-331." to "Test Method 119 of MIL-STD-331 shall be used except test vehicle shall be randomly located in standard shipping pack."

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1345-A172)

[redacted]

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

MIL-B-48343(AR)
AMENDMENT 1

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Battery, Primary Reserve, Ammonia, 5 Milliampere Hour Capacity	4 OF 5	See below
			NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Rise time	261(b) (c)		3.5.3	4.5.9.3
	Long time capacity	261(b) (c)		3.5.5	4.5.9.5
	Short time capacity	75(d)		3.5.4	4.5.9.4
	Support, Ampule (Dwg. 9298650)				
	Examination for defects	25		3.2	4.4.2.13
	Hardness test	Note e		3.2	4.5.4

NOTES a/ Delete Note "(a)" and substitute "(a)".

b/ The Batteries shall be subjected to the five (5) environmental tests in the sequence shown. After environmental testing, the Batteries shall be subjected to the electrical test denoted by (b)., however, the Batteries do not require rotation during activation, in the sequence shown. Twelve (12) each Batteries shall be tested at the temperature listed in Table II of 4.4.3.7.4. If the test sample contains one (1) reject for activation, rise time or Section I of the long time discharge requirement of 4.4.3.7.4, a second sample of thirty-six (36) Batteries shall be tested. The first article sample shall have passed the above criteria if there are zero (0) rejects in the second sample. The low temperature rise time and first seven (7) minutes of Section I discharge requirements shall be for information purpose only. The average end of life requirement to three and three tenths (3.3)

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Battery, Primary Reserve, Ammonia, 5 Milliampere Hour Capacity	5 OF 5	See below
			NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	volts for both the twelve (12) low temperature samples without spin (batteries molded in wedges) and the seventy-five (75) low temperature sample with spin (batteries out of wedges) shall have an average end of life requirement (X) so the X minus three (3) sigma shall equal or exceed 38 hours. However, the average life requirement shall not be less than sixty (60) hours. Failures allowed by the sampling plan below shall not be included in calculation. The first article shall be rejected if the first sample or the combined samples contains two (2) or more rejects for activation and rise time where specified or for Section I discharge requirements of 4.4.3.7.2. The test vehicle for the above test shall be a Wedge as described by a figure in the specification complying with Honeywell Drawing 28115374. (b) If the test sample contains two (2) rejects for the requirement of 4.4.3.7.3, a second sample shall be tested. The sample shall have passed if there is one (1) or less rejects in the first sample or three (3) or lessrejects for both samples. The first article shall be rejected if the first sample contains three (3) or more rejects or if the combined total exceeds three (3) rejects.				
c/	The Batteries shall be subjected to the electrical test denoted by (c). and in the sequence shown. Seventy-five (75) each Batteries shall be tested at the temperatures listed in Table II of 4.4.3.7.4. Three (3) rejects shall be allowed for the activation and rise time requirements; three (3) rejects shall be allowed through the Section I discharge requirements of 4.4.3.7.2 and eight (8) rejects shall be allowed through Section II discharge requirement of 4.4.3.7.3.				
d/	Twenty-five (25) each Batteries shall be tested at the temperatures listed in Table II of 4.4.3.7.4. One (1) reject shall be allowed for the requirement of 4.4.3.7.1 and one (1) when tested as specified in 4.5.9.4.				
e/	A Coupon from the support ampule batch shall be used as the sample.				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.