MILITARY SPECIFICATION

BRAKE MACHINE, SHEET METAL, POWER OPERATED (STANDARD TYPE AND BOX-PAN TYPE)

1. SCOPE

* 1.1 Scope. This specification covers floor mounted bending brakes used for bending sheet metal and light plate. All machines covered herein are equipped with a power operated bending leaf (apron)

* 1.2 Classification. This specification covers bending brakes of the following types and classes, and of the sizes shown in tables I and II. The type, class and size supplied shall be as specified (see 6.2.1). In the following classification, the "clamping" method denotes the method by which the workpiece is clamped in position during the bending operation, and the "top leaf adjustment" denotes the method by which the top leaf is adjusted to compensate for the workpiece thickness-.

Type I - Standard Brakes

Class 1 - Manual clamping with manual top leaf adjustment
Class 2 - Air clamping with manual top leaf adjustment
Class 3 - Air clamping with powered top leaf adjustment

Type 11 - Box and Pan Brakes

Class 2 - Air clamping with manual top leaf adjustment
Class 3 - Air clamping with powered top leaf adjustment

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, Memphis, Tennessee 38114, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3441

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services

MILITARY

MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated the issue in effect on date of invitation for bids or request for proposal shall apply.

U. S. DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1970)

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

B11.3 Construction, Care and Use of Power Press Brakes, Safety Requirements for the

(Application for copies should be addressed to the Amercian National Standards Institite, 1430 Broadway, New York, NY 10018.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

NFPA-79 NATIONAL FIRE PROTECTION ASSN (NFPA)

ELECTRICAL STANDARDS FOR MACHINE TOOLS

NATIONAL FIRE PROTECTION ASSN
470 Atlantic Ave., Boston, Mass 02210

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2.1), the contractor shall furnish one complete bending machine for first article inspection and approval (see 4.2 and 6.3).

3.2 Design. The machine shall be new and one of the manufacturer's current models, capable of bending sheet metal or plate metal in accordance with the requirements herein. Bending shall be accomplished by firmly gripping the workpiece between the upper surface of the base and the ton leaf, and rotating the bending leaf (apron) to the desired position by an electric motor driven mechanism. The machine shall include all components, parts and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, repair or replacement.

* 3.2.1 Controls. All operating controls shall be located convenient to the operator, and identified to facilitate selection and use.

* 3.2.2 Safety and health requirements. Covers, guards, or other safety devices shall be provided for all parts of the bending machine that present safety hazards, The safety devices shall not interfere with operation of the machine. The safety devices shall prevent unintentional contact with the guarded part, and shall be removable to facilitate inspection, maintenance and repair of the parts. All machine parts, components, machanisms, and assembl ies furnished on the machine, whether or not specifically required herein, shall comply with all of the requirements of OSHA 2206 that are applicable to the machine itself. In addition, the machine shall comply with all the requirements of ANSI B11.3 that are designated therein as the responsibility of the machine manufacturer. In the-event of conflict between the requirements of OSHA and ANSI Standards, the requirements of OSHA shall apply. Additional safety and health requirements shall be as specified (see 6.2.1 and 6.4).

*3.2.3 Lubrication. Means shall be provided to insure adequate lubrication for all moving parts (except sealed for life bearings) that require continuous lubrication. Recirculating systems, when provided, shall include filters which are cleanable or replaceable. Each lubricant reservoir shall have means for determining fluid level. All oil holes, grease fittings, and filler caps shall be easily accessible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

3.2.4 Interchangeabi lity. To provide for replacement of worn parts, all parts shall be manufactured to definite dimensions and tolerances which will permit installation of replacement parts without modification of part or machine.

3.3 Construction. The machine shall be constructed of parts which are new, without defects, and free of repair. The structure shall be capable of withstanding all forces encountered during the operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free of scale and mismatching. No process such as welding, peening, plugging, or filling with solder or paste shall be used for reclaiming any defective part.

3.3,2 Welding, brazing, or soldering Welding, brazing, or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Those subject to removal or adjustment shall not be swaged, peened, staked or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be cleaned and free of sand, dirt, fins, sprues, flash, scale, flux and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer’s standard commercial practice.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the machine shall he painted in accordance with the manufacturer's standard commercial practice.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable “Detailed Standard” section referenced therein.

3.3.7 Plates. All words on instruction and indicating plates shall be in the English language. Characters shall be engraved, etched, embossed or stamped in boldface on a contrasting background.

3.3.8 Gears. All gears shall be constructed from a material suitable for the intended purpose, All gears shall transmit full rated torque of the drive motor without gear damage, failure, or premature wear.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

3.3.9 Reclaimed materials. The machine shall contain reclaimed materials to the maximum extent possible without jeopardizing its intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which restores them to the same chemical composition and physical properties as the materials originally selected for use on the machine. Reclaimed materials shall include iron, steel, copper, brass, aluminum, fiber products, plastics, and elastomers that have been collected from discarded solid, liquid, semi-solid, or gaseous waste such as garbage, refuse or sludge,

3.4 Components: The machine shall consist essentially of a base, a top leaf, a bending leaf (apron), a clamping mechanism, and a drive mechanism. Any additional component necessary to the operation of the machine shall be furnished to the manufacturer's standard design and specification.

3.4.1 Base. The base of the machine shall support the top leaf, the leaf, their operating mechanisms, and other related equipment. The base shall have adequate strength and rigidity to maintain al? operating parts in alignment when bending plates of full capacity length and thickness specified in tables I and II. The upper surface of the base shall be a flat surface for supporting the workpiece, and shall have a replaceable bottom bar extending across the entire length of the base. The bottom bar shall serve as the lower clamping surface for clamping the workpiece in position, and shall be constructed of a wear resistant material suitable for the purpose. The base shall have pivots that support the bending leaf, and allow the bending leaf to pivot during bending operations. The back side of the base shall either be of open construction or shall have openings to allow access to the components located within the base structure. Means shall be provided for securely fastening the machine to the floor or a foundation,

3.4.2 Bending leaf (apron). The machine shall have a bending leaf with maximum strength and rigidity. The bending leaf shall be mounted on, and shall pivot on, pivot bosses attached to the base structure. Means shall be provided for aligning the top edge of the bending leaf with the bottom bar mounted on the base surface. The too edge of the bending leaf shall have a replaceable angle bar extending across the entire width of the bending leaf. The angle bar shall strengthen the bending leaf and shall be the member which actually contacts the workpiece during the bending operation. The bending leaf shall be powered by means of a drive mechanism conforming to 3.4.6. The bending leaf drive mechanism shall be controlled form a conveniently located control which will allow the operator to start, stop, hold, and reverse the motion of the bending leaf. Adjustable limit switches shall be Drovided for stopping the bending leaf at any predetermined position for repetitive bending operations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

3.4.3 Top leaf. All machines covered herein shall have a top leaf that clamps the workpiece to the bottom bar mounted on the machine base. The top leaf shall be constructed to insure maximum strength, rigidity, and alignment. The top leaf shall be supported on sturdy pivots attached to the machine base. The pivots shall allow the top leaf to pivot during the clamping operation, and shall also be adjustable to allow the nose of the top leaf to be adjusted toward or away from the bending leaf pivot to adjust for workpiece thickness and bend radius. The top leaf clamping mechanism shall conform to the requirements of 3.4.4 and the top leaf, fore and aft, adjustment shall conform to 3.4.5. The nose of the top leaf shall accommodate interchangeable nose bars capable of forming sharp bends or radiused bends. The nose bar to be furnished shall conform to the requirements of 3.4.3.2.

3.4.3.1 Top leaf (type II machines) In addition to meeting the requirements of 3.4.3, the top leaf of type II (Box and Pan) brakes, shall be designed to accommodate removable and rearrangeable finqers of various widths entending across the entire width of the top leaf. It shall be possible to select various width fingers and install them in various combinations to form boxes and pans having lengths and widths varying, in 1/4 inch increments, within a range of 2 inches to the capacity of the machine. A complete set of random width fingers that will extend across the entire length of the top leaf shall be furnished with each machine. To assist in selection of the proper fingers to form a box of the desired dimensions, each finger shall be permanently marked to indicate its width in inches and fractions of an inch. The fingers shall fit into a groove, and shall be supported by a ledge on the top leaf structure. The fingers shall be securely held in position during the bending operation. The fingers shall accommodate various types of interchangeable nose bars for making various types of bends. The type of nose bars to be furnished shall conform to the requirements of 3*4.3.2. The finger extension (dimension from tip of nose bar to front edge of top leaf) shall be one of the dimensions selected from table II and as specified (see 6.2.1).

3.4.3.2 Nose bar. Unless otherwise specified (see 6.2.1) type I brakes shall have a nose bar extending across the entire width of the top leaf, and of the type suitable for forming sharp bends. Unless otherwise specified (see 6.2.1), each finger of type 11 brakes shall have a nose bar extending across the entire width of each finger, and of the type suitable for forming sharp bends. When special nose bars are required they shall be as specified, and as fully described (see 6.2.1). Al? nose bars shall be constructed of a wear resistant material suitable for the purpose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

3.4.4 Top leaf clamping mechanism. The machine shall have a mechanism that actuates the top leaf, and securely clamps the workpiece between the top leaf nose bar and the bottom bar mounted on the base. On type I, Class 1 machines, workpiece clamping shall be accomplished by manually operated hand levers located on each end of the machine. On type I, Classes 2 and 3 and type II machines, workpiece clamping shall be accomplished by pneumatic cylinders utilizing compressed air from a 90 to 125 PSI air supply Machines utilizing pneumatic clamping shall be complete with pressure regulating valve, pressure gauge, control valves, air filter-separator, lubricator and all necessary hoses, piping, and fittings. Power clamping machines shall have provisions for varying the clamping pressure so that the workpiece may be lightly clamped and positioned to a scribed line ne then tightly clamped during the bending operation.

3.4.5 Top leaf adjusting mechanism. Each machine shall have a mechanism that adjusts the top leaf toward and away from the bending leaf pivot. Classes 1 and 2 shall have a manually operated adjusting mechanism. Class 3 machines shall have a powered adjustment mechanism. Push button controls shall provide forward and reverse leaf adjustment. A scale graduated in increments not larger than 1/32 inch shall indicate the top leaf adjusted position.

3.4.6 Bending leaf drive mechanism. The machine shall have a drive mechanism for raising and lowering the bending leaf. The drive mechanism shall consist of an electric motor, conforming to the requirements of 3.4.7.1, transmitting power through gear to the bending leaf.

3.4.7 Electrical system, Unless otherwise specified (see 6.2.1), electrical system shall conform to all requirements in this paragraph. The system shall conform to the requirements of NFPA-79. Each machine shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz circuit having a fused safety disconnect switch. The bending machine shall be initially wired for operation on 230 volts. An identified terminal for grounding the machine when installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in Table 240-A of NFPA-79 for the disconnect, fuse rating.

* 3.4.7.1 Motors. Motors shall have ball or roller bearings. Unless otherwise specified (see 6.2.1), each motor shall meet the requirements of a dripproof enclosure.

3.5 Machine characteristics. The machine shall meet the applicable requirements of tables I and II, by type, class and size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

TABLE I

Type I - STANDARD BRAKES

SIZE	CAPACITY*		Narrowest Flange On Capacity Material, Inches (Not More Than)**
	Workpiece Length, Feet Feet (Not Less Than)	Workpiece Thickness (Not Less Than)	
		CLASS 1- MANUAL CLAMPING, MANUAL TOP LEAF ADJUSTING	
1	6	10 ga.	1
2	6	3/16"	1-1/4
3	6	1/4"	1-1/2
4	6	3/8	2
5	8	10 ga.	1
6	8	3/16"	1-1/4
7	8	1/4"	1-1/2
		CLASS 2 - AIR CLAMPING, MANUAL TOP LEAF ADJUSTMENT	
1	10	10 ga.	1
2	10	3/16"	1-1/4
3	12	10 ga.	1
		CLASS 3 - AIR CLAMPING, POWERED TOP LEAF ADJUSTMENT	
1	6	1/2"	4
2	8	3/8"	2
3	8	1/2"	4
4	10	1/4"	1-1/2
5	10	3/8"	2
6	10	1/2"	4
7	12	3/16"	1-1/4
8	12	1/4"	1-1/2
9	12	3/8"	2
10	12	1/2"	4

* Capacity is based on hot rolled, open hearth steel having a carbon content of .20 to .30 percent.

** Shall form flanges to this dimension on capacity material. Will form narrower flanges on material of less than capacity in size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

TABLE II

TYPE II - BOX AND PAN BRAKES

SIZE	CAPACITY*		Narrowest Flange On Capacity Material, Inches (Not Greater Than) **	Finger Extension, Inches (Not Less Than) ***
	Workpiece Length, Feet (Not Less Than)	Workpiece Thickness (Not Less Than)		
	CLASS - AIR CLAMPING, MANUAL TOP LEAF ADJUSTMENT			
1	6	10 ga.	1	6, 8 or 12
2	8	10 ga.	1	6, 8 or 12
3	10	10 ga.	1	6, 8 or 12
4	6	3/16"	1-1/4	6, 8 or 12
5	8	3/16"	1-1/4	6, 8 or 12
6	10	3/16"	1-1/4	6, 8 or 12
7	6	1/4"	1-1/2	6, 8 or 12
8	8	1/4"	1-1/2	6, 8 or 12
	CLASS 3 - AIR CLAMPING, POWERED TOP LEAF ADJUSTMENT			
1	10	1/4"	1-1/2	6, 8 or 12

* Capacity is based on h t rolled, open hearth steel having a carbon content of .20 to .30 percent.

** Shall form flanges to this dimension on capacity material. Will form narrower flanges on material of less than capacity in size.

*** As specified, see 3.4.3.1 and 6.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

3.6 Performance. All brakes shall be capable of bending metal sheet and plate of the composition, widths and thickness specified in tables I and II under "Capacity" to the following accuracies and requirements:

(a) Angle of bend - The machine shall be capable of forming bends with the range of 0 degrees to 135 degrees, measured from the horizontal plane (180 degrees to 45 degrees included angle) .

(b) Bend radius . The machine shall be capable of making sharp bends having an inside radius not more than twice the thickness OF the metal being bent. The machine shall also be capable of making larger radius bends by adjusting the top leaf away from the bending leaf pivot and making "freehand" multiple partial bends, or by using special nose bars.

(c) Bending accuracy - The machine shall be capable of forming 90 degrees bends to an accuracy of ± 2 degrees.

(d) Repeatability - Using the bending leaf stops, the machine shall be capable of making repetitive bends to a repeatable accuracy of ± 2 degrees.

(e) Narrow flanges - The machine shall be capable of forming narrow flanges having a width conforming to the requirements of tables I and II. The flanges shall be uniform in heights within + 0.015 inch,

(f) Bends described above shall show no evidence of "slip" or "creep".

(g) In addition to the above, type 11 brakes shall be capable of forming multiple bends in material having previously formed side flanges, as encountered during box and pan forming Box and pan brakes shall also be capable of makinq bends forming rectangular tubes, when using special nose bars that extend between fingers.

3.7 Standard equipment. Unless otherwise specified (see 6.2.?), the machine shall be furnished with all standard equipment including one set of hand tools normally furnished by the manufacturers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

3.8 Optional equipment. Optional equipment shall be furnished as specified (see 6.2.1).

* 3.9 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The following information shall be furnished on the chart or plate:

Points of application
Service interval
Type of lubricant
Viscosity

* 3.10 Nameplate. Unless otherwise specified (see 6,2.1), a corrosion resistant metal nameplate identifying the machine shall be securely attached to each machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each such caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's serial number
Power input (volts, total amps, phase(s), frequency)
Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture
u s

3.11 Technical data. Data shall be furnished as specified (see 6,2.2.).

3.12 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein" Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specification when such action is deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection, When first article approval is required under 3.1, first article inspection shall be performed. Unless otherwise specified (see 6.2.1), first article inspection shall comprise the examination in 4.4 and all tests in 4.5. Failure of the item to pass any examination or test shall be cause for disapproval of the first article.

* 4.3 Quality conformance inspection. Each machine shall be subjected to quality conformance inspection prior to being offered for acceptance. Unless otherwise specified (see 6,2.1), quality conformance inspection shall consist of the examination in 4.4, the tests in 4.5,1 through 4.5,2.2 and the inspection in 4.6. Failure to pass the examination or any test shall be cause for rejection.

4.4 Examination. The machine and equipment shall be examined to determine compliance with the requirements in 3.2 through 3.5 and 3.7 through 3.12.

4.5 Tests.

4.5.1 Operation test. The machine shall be operated at no load for not less than 30 minutes. Proper operation of all controls, motors, adjusting mechanisms, and accessories shall be verified during the trial period.

4.5.2 Performance test. The machine shall satisfactorily perform the following test on two workplaces of the size specified as "Capacity" in table I or table 11 as applicable. The test shall be performed on workplaces of hot rolled, open hearth steel having a carbon content of .20 to .30 percent. The bending leaf shall be fitted with an angle bar support, the top leaf shall be properly adjusted, and a 90 degree flange of the height shown as “narrowest flange on capacity material” in tables I and table II, as applicable, shall be formed on each workpiece. The finished flanges shall conform to the requirements of 3,6 (b), (c), (d), (e), and (f).

4.5.2.1 Optional box and pan tests (type II machines only). When specified (see 6.2.1), type II (box and pan) brakes shall be required to perform the following test in addition to the test required in 4.5.2. A shallow pan, hanving a length of 15-1/4 inches, a width of 12-1/2 inches, and a height of 2-1/4 inches shall be formed out of metal plate of the compostion and thickness specified under “Capacity” in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

The finished pan shall be measured for accuracy of the length, width, and height dimensions, and for squareness of all corners. All of the dimensions of the pan shall be accurate within + 1/16 inch of the above stated dimensions, and all formed corners shall be square within an accuracy of ± 2 degrees. The bends shall show no evidence of "slip" or "creep."

* 4,6 Packaging inspection. Preservation, packing and marking shall be inspected to determine compliance with the requirements of Section 5.

5. PACKAGING

5.1 preservation, packing and marking. Unless otherwise specified (see 6.2.1) preservation, packing and marking shall conform to the requirements of MI[-STD-1188.

6. NOTES.

6.1 Intended use. Brakes covered by this specification are intended for use in fabricating shops for bending sheet and plate metal.

6.2 Ordering data.

6.2.1 Procurement requirements, Purchasers should specify their requirements in procurement documents, including whether each choice is required or not required, by entering an appropriate statement identified to each of the following:

a. Title, number, and date of this specification.

b. Type, class, and size machine required (see 1.2 and tables I and 11).

c* First Article approval, if required (see 3.1 and 6.3).

d. Specify additional safety and health requirements (see 3.2.2 and 6,4).

e. Painting, if different (see 3.3.5).

f. On type II machines only, specify one of the finger extension dimensions shown in table II (see 3.4.3.1 and table II).

g" Nose bar, if different: specify and fully describe nose bar(s) required (see 3.4,3.2).

h. Electrical system, if different (see 3,4.7).

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:41Z
Check the source to verify that this is the current version before use.

i. Motor enclosure, if different (see 3.4.7.1).

j. Standard equipment, if different (see3.7).

k. Optional equipment, if required; fully describe (see3.8).

1. Lubrication chart, if different (see 3.9),

m. Nameplate, if different (see 3.10).

n. Specify if optional test in 4.5.2.1 shall be performed on Type 11 machines as a part of First Article inspection (see 4.3).

00 Quality conformance inspection, if different: specify if optional test in 4.5.2.1 shall be performed on Type II machines as a part of quality conformance inspection (see 4.3).

p. Required preservation, packing and marking, if different (see 5.1).

6.2.2 Contract data requirements. Required technical data, such as operators manuals, parts lists, foundation and anchor bolt plans, wiring diagrams and other instructions for operation and maintenance as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract (see 3.13).

6.3 First article, When first article approval is required under 3.1, the solicitation should include complete information concerning examination, testing and approval.

6.4 Safety and health requirements. Paragraph 3.2.2 requires compliance only with those OSHA requirements that concern the machine itself. It does not require compliance with those OSHA requirements that concern "the machine in its operating environment" such as noise levels, radiation levels, electromagnetic emissions, noxious vapors, air contaminants, heat, etc. Since OSHA limits the total hazard level of these hazards in the environment (and does not limit the hazard level of individual machines in the environment) the procuring agency is advised to analyze the existing hazard levels in the proposed operating environment, and specify additional machine requirements that will integrate the new machine into its future operating environment. If specific point-of-operation guarding is required, the procuring agency should specify the exact configuration of the guard required, as in most cases, the guard configuration is dependent on the size and configuration of the workplaces. The above, and any other additional safety and health requirements should be specified in detail under 6.2.1 (d).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review Activities:
Army - AV
DLA - GS
Navy - SH

User Activities:
Navy - MC
Army - AR

Preparing Activity:
DLA - IP

Project Number:
3441-0097

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-B-80153B

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO
	DATE

DD FORM 1426 1 OCT 76 Replaces edition of 1 Jan 72 which may be used. S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:41Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY
DoD-[redacted] 304

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Defense Industrial Plant Equipment
Center, Attn: DIPEC-PA
2163 Airways Blvd.
Memphis, TN 38114

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:41Z
Check the source to verify that this is the current version before use.