MIL-C-48022 (MU)
6 August 1973
SUPERSEDING
(See 6.6)

MILITARY SPECIFICATION

CARTRIDGE, 107MM, HE: M453

BODY ASSEMBLY FOR

1. SCOPE

1.1 This specification covers the metal parts for the body assembly for one type of cartridge designated as Cartridge, 107MM, HE: M453.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A-2550	- Ammunition, General Specification for

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	- Quality Assurance Terms and Definitions

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

MIL-STD-1168 - Lot Numbering of Ammunition

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. Army Munitions Command

D-9211936 - Body Assembly
F-8848553 - Pallet for 4.2 inch mortar Projectile Bodies

C-9202029 - Gage, Snap
B-9202031 - Gage, Template
C-9202032 - Gage, Plug Special
C-9202033 - Gage, Snap
B-9202035 - Gage, Snap, Adj, Special
A-9202036 - Gage, Plug, Special
D-9202038 - Gage, Flush Pin
D-9202039 - Gage, Flush Pin
D-9202040 - Gage, Snap, Progressive
C-9202087 - Gage, Plug Special
D-9202209 - Gage, Flush Pin
C-9202210 - Gage, Plug Special
D-9202211 - Gage, Concentricity
D-9202216 - Adapter
D-9202230 - Air Test Fixture

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM E 8-69 - Tension Testing of Metallic Materials

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawing (Dwg.) D-9211936, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Mechanical properties.-Cold-working or heat-treating (including quenching-and-tempering, normalizing, normalizing-and-tempering, annealing, and stress-relieving) operations, shall be performed in such a manner as to produce the specified properties uniformly throughout the entire lot. The contractor shall determine the detailed procedures to produce parts meeting the required mechanical properties. These procedures shall be documented and submitted with the first article sample to the procurement Contracting Officer. Changes in procedures shall also be documented and submitted to the Procurement Contracting Officer.

3.4 Workmanship.-All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

3.4.1 Heat treatment.-All heat treatment procedures shall be controlled so as to produce in each lot of components the mechanical properties specified on the applicable component drawings and in applicable specifications.

3.5 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (see 6.5)

3.6 First article testing.-This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contractor or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements when such material is purchased by the contractor or commercial specifications referenced in any of the contractural documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.
f. Number of units of product inspected.
g. Results obtained by defect code, for all inspection performed.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection.(See 3.3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4.2.1 Submission.-The contractor shall submit a first article quantity as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2 (See 6.1) The first article sample shall consist of the following:

a. Twenty (20) of each body, unpainted.
b. Twenty (20) of each shell nose, unpainted.
c. Twenty (20) body assemblies, unpainted.
d. Five (5) body assemblies, painted.

All parts and completed assemblies submitted shall have been produced by the Contractor (or furnished by a supplier) using the same production processes, procedures and equipment as will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of conformance. A first article quantity, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process (including heat treatment procedures and equipment), material used, drawing specification or source of supply as to significantly affect product uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer.

4.2.2 Inspection to be performed.-All parts and assemblies shall be subjected by the Government to any or all the examinations or tests specified in this specification and any or all requirements of the applicable drawings. In addition, the following tests shall be performed:

4.2.2.1 Tension Tests of Body.-One (1) test specimen shall be taken from each of the twenty (20) unpainted bodies.

4.2.2.2 Tension Tests of Shell Nose.-One (1) test specimen shall be taken from each of the twenty (20) shell noses.

4.2.3 Rejection.-If any part or assembly fails to comply with any of the applicable requirements, the first article quantity shall be rejected. The Government reserves the right

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

to terminate its inspection upon any failure of any part or assembly in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions.-

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process in accordance with the same drawing, same drawing revision, same specification and same specification revision, and complies with the provisions for submission of product as specified in MIL-STD-105. Change to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.3.1.1 Heat treatment lot.

4.3.1.1.1 Heat treatment or stress-relief lot.-A heat treatment or stress-relief lot shall consist of bodies from one mill-heat of steel that have been heat-treated or stress-relieved in the same furnace at the same temperature and for the same length of time. Test samples shall be selected after completion of all heat treatment operations. Where heat-treatment or stress-relief is done in a continuously operated, conveyor-type furance, the identification maintained shall be that code number assigned the particular mill-heat of steel. Where heat treatment or stress-relief is performed in batch-type furnaces,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

additonal identification control must be maintained that directly relates to that portion of the mill-heat processed as a batch. The method of control must meet with the approval of the Procurement Contracting Officer. Components in heat treatment or stress-relief lots shall remain grouped together for identifying purposes until mechanical properties tests have been completed. Components from heat-treatment or stress-relief lots which comply with the applicable requirements may be subsequently regrouped into body assembly lots. A letter or number system shall be used for coding heat treatment lots. Coding by color shall not be used.

4.3.1.1.2 Shell Nose.-A heat treatment lot shall consist of shell noses (aluminum forgings or bar-stock) of one lot of the specified aluminum alloy that has been heat treated by the same process, in the same furnace, at the same temperature, and for the same length of time.

4.3.1.1.2.1 A heat treatment lot of shell noses (aluminum forgings) shall not exceed 25,000 pieces.

4.3.1.1.2.2 A heat treatment lot of bar-stock (for shell noses) shall not exceed 11,000 pounds of bar stock.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plan for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Individual defects shall have an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Nose, shell (See Dwg. D-9211938 covering a detail of Dwg. D-9211936).

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical:	None defined		
Major			
101.	Depth to smaller basic diameter at bottom of cavity	Gage	01001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

	102. Distance between bottom of large cavity and bottom of tapered cavity	D9202039	01002
	103. Pitch diameter of external thread	Gage	01003
	104. Major diameter of external thread	Gage	01004
	105. Pitch diameter of internal thread	Gage	01005
	106. Minor diameter of internal thread	Gage	01006
	107. Outside diameter of body seat shoulder	Gage	01007
	108. Diameter of thread relief, minimum (min)	B9202035	01008
	109. Width of thread relief, maximum (max)	A9202036	01009
	110. Depth of large cavity from body seat shoulder	D9202038	01010
	111. Diameter of large cavity	Gage	01011
	112. Length to body seat	Gage	01012
	113. Length to external basic diameter from face	Gage	01013
	114. Outside diameter at nose end	Gage	01014
Minor			
	201. Total length, min	D9202040	01015
	202. Evidence of poor workmanship (See 3.4)	Visual	01016

4.3.2.2 Body (See Dwg. D-9211937 covering a detail of Dwg. D-9211936).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
	101. Diameter of counterbore at rear end	C9202032	02001
	102. Larger inside diameter	C9202087	02002
	103. Smaller inside diameter	C9202210	02003
	104. Diameter of both bourrelets, min	Gage	02004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

105.	Diameter between bourrelets	Gage	02005
106.	Pitch diameter of thread	Gage	02006
107.	Outside diameter at rear end	Gage	02007
108.	Minor diameter of thread, max	Gage	02008
109.	Length of thread, min	Gage	02009
110.	Concentricity of smaller inside diameter with both bourrelets	D9202211 D9202216	02010
111.	Concentricity of larger inside diameter with both bourrelets	D9202211 D9202216	02011
112.	Concentricity of counterbore at rear end with both bourrelets	D9202211 D9202216	02012
113.	Concentricity of pitch diameter of thread with both bourrelets	D9202211 D9202216	02013
114.	Total length	C9202029	02014
115.	Width of forward bourrelet, min	B9202031	02015
116.	Perpendicularity of rear face with both bourrelets	D9202211 D9202216	02016
117.	Perpendicularity of forward face with bourrelets	D9202211 D9202216	02017
118.	Depth to shell nose seat below thread cavity, max	Gage	02018
119.	Length to internal basic diameter from forward face	D9202209	02019
120.	Finish of cavity wall improper in end counterbore	Visual	02020
Minor			
201.	Distance between forward face and beginning of bourrelet near middle	B9202031	02021
202.	Depth of counterbore at rear end, min	C9202032	02022
203.	Evidence of poor workmanship (See 3.4)	Visual	02023
204.	Chamfer missing or incorrect	Visual	02024

4.3.2.3 Body Assembly (See Dwg. D-9211936)

Categories	Defects	Method of Inspection	Code No.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

Critical: None defined

Major			
101.	Diameter of both bourrelets, max (after painting)	Gage	03001
102.	Total length, max	C9202033	03002
103.	Concentricity of pitch diameter of thread with both bourrelets	Gage	03003
104.	Concentricity of inside diameter of nose with inside diameter of body	Gage	03004
105.	Gap between body and nose, max (prior to blend machining)	Gage	03005
106.	Thread damaged	Visual	03006
107.	Air test stamp missing	Visual	03007
Minor			
201.	Protective coating with bare spot (other than slight scratches)	Visual	03008
202.	Evidence of poor workmanship (See 3.4)	Visual	03009
203.	Staking notches missing or inadequate	Visual	03010
204.	Marking misleading or unidentifiable	Visual	03011

4.3.2.4 Pallet, prior to assembling of cover (See Dwg. F 8848553).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major			
101.	Incorrect number of assemblies	Visual	04001
102.	Assemblies incorrectly positioned	Visual	04002
Minor:	None defined		

4.3.2.5 Pallet (See Dwg. F-8848553)

Categories	Defects	Method of Inspection	Code No.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

Critical:	None defined		
Major			
101.	Hardware missing, broken or loose	Visual/Manual	05001
102.	Strapping missing, broken or loose	Visual/Manual	05002
103.	Board broken or split	Visual	05003
104.	Liner missing	Visual	05004
Minor			
201.	Hardware improperly engaged	Visual/Manual	05005
202.	Strapping improperly assembled	Visual	05006
203.	Marking misleading or unidentifiable (including incorrect color code)	Visual	05007
204.	Car seal missing, unsealed or improperly positioned	Visual	05008

4.3.3 Testing .

4.3.3.1 Air test of body-nose joint (See Dwg. D-9211936) Major defect(Code No. 06001).-The sampling plan for this test shall be in accordance with MIL-STD-105 using code letter L and an AQL of 0.25 percent. The test shall be performed as specified in 4.4.1 using air test equipment D9202230. Any body assembly which fails to comply with the specified requirement shall be classed defective.

4.3.3.2 Tension tests of body, prior to machining, (See Dwg. D9211937) Major Defect (Code No. 07001).

4.3.3.2.1 Sample coupons of the body shall be taken from each mill-heat of steel in accordance with Table I and tested as specified in 4.4.2.

TABLE I

No. of Bodies in Heat Lot	Sample
50-200	2
201-300	3
301-400	4
401-500	5
501-600	6
601-700	7
701-800	8
801-900	9
over 900	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

If more than one heat treatment or stress-relief batch is included in the mill-heat of steel, or when the heat of steel is processed in two (2) or more batch-type furnaces, the sample bodies shall be selected in such a manner as to be representative of the greatest number of batches possible within the mill-heat. When heat treatment or stress relief is performed in a continuously operated, conveyor-type furnace, the samples shall be selected in a sequence that will be representative to the maximum extent, of the entire mill heat-lot in process.

4.3.3.2.2 Rejection.-If any test coupon fails to comply with the applicable physical requirements, that quantity of bodies represented by the failing coupon shall be rejected.

4.3.3.3 Tension tests of shell nose, prior to machining. (See Dwg. D-9211037) Major Defect.

4.3.3.3.1 Heat treatment lot (aluminum forgings) Code No. 08001.-Three (3) shell noses shall be randomly selected from each heat treatment lot after completion of the heat treatment process. The three (3) specimens prepared therefrom shall be subjected to these tests. The tests shall be performed as specified in 4.4.3.

4.3.3.3.2 Continuous heat treatment lot (aluminum forgings) Code No. 08002.-Three noses shall be randomly selected from each eight (8) hour's production, or portion thereof, after completion of the heat treatment process. The three (3) specimens prepared therefrom shall be subjected to these tests. The tests shall be performed as specified in 4.4.3.

4.3.3.3.3 Heat treatment lot (bar-stock) Code No. 08003.-Two (2) specimens shall be selected from each of three (3) bars, randomly selected from each heat treatment lot. The specimens shall be taken from one end and center of each of the selected bars. The tests shall be performed as specified in 4.4.3.

4.3.3.3.4 Rejection.-If any specimen fails to comply with the mechanical requirements specified on the applicable drawing, the heat treatment quantity represented by the failing specimen shall be rejected.

4.3.4 Inspection equipment.-The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Method of Inspection" headings in 4.3.2 and in 4.3.3 (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4.4 Test methods and procedures.

4.4.1 Air test of body-nose thread joint.-The body assembly shall be assembled to fixture D9202230 and a measured quantity of air applied to produce the air pressure as specified on the applicable drawing.

All equipment used in this test shall be capable of performing the test accurately and consistently. Equipment shall be calibrated at the start of each shift and, thereafter, at intervals of not more than four (4) hours of continuous operation. It shall also be calibrated prior to restarting the operation after a layoff of three (3) hours or more. If it is found that the gage is out of calibration in such a direction that the test pressure was actually lower than that specified on the drawing, body assemblies tested since the last satisfactory calibration shall be retested after the gage error has been corrected. All test and calibration instructions, equipment and procedures shall be approved in accordance with 4.3.4.

The test fixture shall be constructed in such a manner that the pressure specified on the applicable drawing will be applied to the inside of the body assembly. The body assembly shall then be isolated from the pressure supply. A leaking assembly shall be evidenced by a decrease in pressure as the assembly remains isolated for the testing time specified on the applicable drawing. NOTE.-Use of water in making this test, such as an immersion test, will not be allowed.

4.4.2 Tension test of body.-The body shall be subjected to the tension test in accordance with ASTM E 8-69, to determine its mechanical properties (yield strength, tensile strength, and percentage of elongation). The tension specimen shall be taken from the mid-section. Dimensions of specimen shall conform to ASTM E 8-69. Yield strength shall be determined by either the offset method or extension-under-load method. The limiting set shall be 0.2 percent (0.002 inch per inch of gage length). In addition, the elongation shall be determined by the divider method. Identity of each heat-treated lot shall be maintained until minimum mechanical properties have been verified by the inspector.

4.4.3 Tension Tests of Shell Nose.

4.4.3.1 Aluminum Forging.-The shell nose shall be subjected to the tension test in accordance with ASTM E 8-69 to determine

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

its mechanical properties (yield strength, tensile strength, and percentage of elongation). The tension specimen shall be taken from the shell nose. Dimensions of the specimen shall conform to ASTM E 8-69. Yield strength shall be determined by either the offset method or extension-under-load method. The limiting set shall be 0.1 percent (0.001 inch per inch of gage length). In addition, the elongation shall be determined by the divider method. Identity of each heat-treated lot shall be maintained until minimum mechanical properties have been verified by the inspector.

4.4.3.2 Bar-Stock.-The test shall be performed as specified in 4.4.3.1. Identity of each heat-treated lot shall be maintained until minimum mechanical properties have been verified by the inspector.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging .

5.1.1 Level C.-The body assemblies shall be preserved and packaged in accordance with Dwg. F-8848553.

5.2 Packing.

5.2.1 Level C.-The body assemblies, preserved and packaged as specified in 5.1.1, shall be packed for shipment in accordance with Dwg. F-8848553.

5.3 Marking.-Marking shall comply with Dwg. F-8848553.

5.4 Shipping.-When components from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

c. Provisions for submission of first article samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types: Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.
b. A source control drawing or a specification control drawing as defined in MIL-STD-100.
c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is catalogued and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the categroy and form (per MIL-D-1000) specified in the Contract Data Requirement Lists (DD Form 1423).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five-digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design.

6.3.3 Submission of designs for approval.-Contractor designs shall be approved by the Government prior to fabrication or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423). Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Submission of test data.-In addition to the normal distribution of records, when the body assembly is procured by the U.S. Army Munitions Command, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commanding Officer, Picatinny Arsenal, Attn: SARPA-QA-A-S.

6.5 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, Attn: SARPA-QA-A-S.

6.6 Supersession data.-This specification includes the requirements of, and supersedes, Purchase Specification AEI-385, dated 26 September 1966.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1315-A004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.