INCH-POUND

MIL-C-50701A(AR)
AMENDMENT 2
17 December 1990
SUPERSEDING
AMENDMENT 1
24 July 1984

MILITARY SPECIFICATION

CARTRIDGE, 7.62X39MM, BALL

This Amendment forms a part of Military Specification MIL-C-50701A(MU), dated 20 August 1971, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

Delete "AMCR 715-505 Volume 3" wherever it appears in the specification and substitute "SCATP-7.62."

PAGE 1

* 2.1 Under Drawings, add: "11738714 Cartons"

PAGE 2

* 3.8 Delete paragraph 3.8 in its entirety and substitute:

"3.8 Velocity - The average velocity of the sample cartridges, conditioned at 68° to 72°F, shall be 2275 feet per second (ft/sec) plus or minus 30 ft/sec at 78 feet from the muzzle of the weapon or 2350 ft/sec plus or minus 50 ft/sec at 15 feet from the muzzle of the weapon. The standard deviation of the velocities shall not exceed 32 feet per second."

3.10 Delete the word "ambient" and substitute "room."

4.3.3.1 - Table II: Delete the heading "Ambient Temp" and substitute "70 ± 2°F."

PAGE 8

4.3.3.2 - Table III: Change defect numbers from "3, 4, 5 and 6" to "4, 5, 6 and 7" respectively. Then insert new defect number 3 as follows:

"3. Hangfire 7/ 0 -"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:34Z
Check the source to verify that this is the current version before use.

PAGE 9

4.3.3.2 - Table III: Add footnote 7/ to Table III as follows:

"7/ For definition of hangfire, see SCATP-7.62 paragraph 10.6.2."

PAGE 10

* Add a new paragraph 4.4.8.1 as follows:

"4.4.8.1 Alternate velocity/pressure barrel - For the velocity and pressure tests an alternate barrel used by SAAMI with the following dimensions may be used:

Overall barrel length - 20 inches
Piston diameter - .206 inches
Piston diameter location is to remain the same as current government drawing 8648664."

4.4.9.2 Delete the phrase "for not less than 4 hours" and substitute "for 4 to 5 hours."

Add a new paragraph 4.4.9.3 as follows:

"4.4.9.3 Room temperature tests. The sample shall be conditioned for not less than 2 hours at 68°F to 72°F (room temperature) and fired at that temperature."

4.4.10 - Delete the word "ambient" and substitute the word "room".

PAGE 11

* 5.0 Delete paragraph 5 and sub-paragraphs 5.1 and 5.2 in their entireties and substitute the following:

"5. PREPARATION FOR DELIVERY

5.1 Packaging: The cartridges shall be packaged in accordance with drawing 11738714.

5.2 Packing: The cartridges shall be packed in accordance with Drawing 11738715.

5.3 Marking: The packed cartridges shall be marked in accordance with drawings 11738714 and 11738715."

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:34Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1305-AD53)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:34Z
Check the source to verify that this is the current version before use.