INCH-POUND

MIL-C-70998 (AR)
AMENDMENT 3
08 October 1997
SUPERSEDING
AMENDMENT 2
29 July 1996

MILITARY SPECIFICATION

CONTAINER, SHIPPING AND STORAGE, CARTRIDGE, 25MM, PA125
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-C-70998 (AR), dated 18 February 1992, and is approved for use by the US Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.4.1, add the following to end of paragraph:

"The filler pad shall be centrally located to and adhere to cover assembly. The filler pad shall not interfere with operation of gasket 3.5, 3.8. Adhesive material shall not come in contact with gasket materials."

3.4.1, delete from paragraph:

"The filler pad shall be centrally located to and adhere to cover assembly. The filler pad shall not interfere with operation of gasket 3.5, 3.8. Adhesive material shall not come in contact with gasket materials."

PAGE 4

Add new paragraph 3.4.4 as follows:

"3.4.4 Body assembly. Filler pad shall be centrally located to and adhere to body assembly. The filler pad shall not be folded or creased so as to take up more volume at the container bottom than intended for use."

Delete paragraph 3.4.4 in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:17Z
Check the source to verify that this is the current version before use.

* Table II - Delete in its entirety and substitute:

"TABLE II. Attribute sampling inspection

	Inspection Levels		
Lot Size	V	VI	VII
2 to 8	*	*	*
9 to 15	*	*	13
16 to 25	*	20	13
26 to 50	32	20	13
51 to 90	32	20	13
91 to 150	32	20	13
151 to 280	32	20	20
281 to 500	48	47	29
501 to 1200	73	47	34
1201 to 3200	73	53	42
3201 to 10000	86	68	50
10001 to 35000	108	77	60"

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

PAGE 10

* Para. 4.4.2.1 - delete in its entirety and substitute.

PAGE 11

Para 4.4..2 Add new major characteristic 107 as follows:

"107.	Filler pad missing, creased, incomplete adhesion, or adhesive visible"	Level II	3.4.4	Visual

4.4.2.2, delete major characteristic 107 in its entirety.

* Para 4.4.2.2, delete in its entirety and substitute new para 4.4.2.2 included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	PA125 Ammunition Container Assembly	1 OF 1	12576143
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Performance (before temp) 2/	20 0-1	3.4	4.6.2
102	Performance (after temp) 2/ 3/	20 0-1	3.4	4.6.1 & 4.6.2
103	Airtightness 2/	Level V	3.5	4.6.3
104	Pretreatment 2/	Note 1/	3.7.1	4.6.4
105	Paint adhesion 2/	3	3.7.2	4.6.5
106	Gasket compression 2/	Level V	3.8	SMTE
107	Corrosion 2/	3	3.7.3	4.6.6
Minor				
201	Evidence of poor workmanship	Level VII	3.12	Visual

NOTES:
1/ 3 standard panels per TT-C-490
2/ Accept on zero defects, reject on one defect.
3/ Samples for this test shall be taken from Major 101.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Body Assembly	1 OF 1	12576144
			NEXT HIGHER ASSEMBLY: 12576143

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside width, body assembly, min	Level V	3.2	SMTE
102	Inside length, body assembly, min	Level V	3.2	SMTE
103	Inside depth, body assembly, min	Level V	3.2	SMTE
104	Convexity or concavity top edges of body	Level V	3.10.2	SMTE
105	Interior or exterior paint missing or nonconforming	Level V	3.7.1 & 3.7.2	Visual /1
106	Hasp assembly weld	20 0-1	3.9.1	4.6.8.1
107	Handle assembly weld	20 0-1	3.9.2	4.6.8.2
Minor				
201	Poor workmanship	Level VII	3.12	Visual

NOTES:

1/ MIL-STD-406 shall be used as a guide to classify paint defects. Missing, damaged or incomplete paint shall be classified as a defect. In the standard, defects classified as incidental shall be considered permissible; defects classified as minor shall be considered major and shall be cause for rejection. Bare spots on any subassembly which do not accumulate to exceed 1/2 square inch in area or scratches which do not penetrate to the phosphate coating shall be disregarded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:17Z
Check the source to verify that this is the current version before use.

PAGE 12

Para 4.4.2.3, characteristic 104:

Delete: "Missing, inverted, loose, misaligned or defective gasket."

Substitute: "Gasket, missing, inverted, loose, misaligned, exterior spotted from adhesive or defective. Filler pad: Missing, loose, misaligned, adhesive visible or defective."

4.4.2.3, characteristic 104:

Delete : "Gasket, missing, inverted, loose, misaligned, exterior spotted from adhesive or defective. Filler pad: Missing, loose, misaligned, adhesive visible or defective."

Substitute: "Missing, inverted, loose, misaligned or defective gasket."

* Para 4.4.2.3 delete in its entirety and substitute new para 4.4.2.3 included.

PAGE 13

Para 4.4.2.4 note 2/: Delete "ferrule" and substitute "handle".

Para 4.4.2.4 delete in its entirety and substitute new para 4.4.2.4 included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE CHARACTERISTICS

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70998(AR)
AMENDMENT 3

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Cover Assembly		12576152
			NEXT HIGHER ASSEMBLY
			12576143

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critcal	None defined			
Major				
101	Width, inside cover (2 places)	Level V	3.2	SMTE
102	Interior or exterior paint missing or nonconforming	Level V	3.7.1 & 3.7.2	Visual 1/
103	Flatness	Level V	3.10.1	SMTE
104	Weld security of latch	Level V	3.9.3	4.6.8.3
105	Missing, inverted, misaligned, loose or defective gasket	Level V	3.4.1	Visual-Manual 2/
Minor				
201	Poor workmanship	Level VII	3.12	Visual

NOTES:

1/ MIL-STD-406 shall be used as a guide to classify paint defects. Missing, damaged or incomplete paint shall be classified as a defect. In the standard, defects classified as as incidental shall be considered permissible; defects classified as minor shall be considered major and shall be cause for rejection. Bare spots on any subassembly which do not accumulate to exceed 1/2 sq in. or scratches which do not penetrate to the coating shall be disregarded.

2/ If the gasket is missing, inverted, broken, split or torn, contains a gross defect in texture, or can be shifted horizontally with the retainer by finger pressure or manual shake of the cover assembly, the sample shall be classified defective.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T04:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70998 (AR)
AMENDMENT 3

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Container Assembly	1 OF 1	12576143

NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Cracked or split component	Level V	3.12	Visual
102	Missing, incomplete, improper assembly of component	Level V	3.12	Visual
103	Missing, incomplete or improper welds	Level V	3.12	Visual
104	Mutilated metal component	Level V	3.12	Visual 1/
105	Steel sliver, burr or sharp edge	Level V	3.12	Visual-Manual 2/
106	Outside height	Level V	3.2	SMTE
107	Outside length	Level V	3.2	SMTE
108	outside width	Level V	3.2	SMTE
Minor				
201	Marking incorrect, incomplete, illegible or missing	Level VI	3.2	Visual
202	Foreign matter, except corrosion	Level VI	3.12	Visual
203	Poor workmanship	Level VII	3.12	Visual

NOTES:

1/ If the body or cover is severly dented or malformed, or the closing or locking hardware is bent or otherwise distorted to cause functional failure or become a personnel hazard, the sample unit shall be classed defective.

2/ If a steel sliver, burr or sharp edge which could injure unprotected hands is found on a handle, the bottom edge of a latch or cover skirt, or on the top or bottom edges of the body, the sample unit shall be classified defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:17Z
Check the source to verify that this is the current version before use.

PAGE 14

* Para 4.4.3.1 Delete in its entirety and substitute:

"4.4.3.1 Performance. Failure of one or more units of sample to comply with the specified requirements shall be cause for rejection of the lot."

* Para 4.4.3.2 Delete in its entirety and substitute:

"Air tightness. Failure of one or more units of the sample to comply with the specified requirements shall be cause for rejection of the lot. A stream or recurring succession of bubbles from any surface, seam, or gasket junction shall be evidence of a defective container."

PAGE 16

Para 4.6.2c: Delete in its entirety and substitute the following:

"c. Remove all cover assemblies. Inspect the gasket for fit, security, adhesive, cuts and splits. Filler pad shall not interfere with removal and/or replacement of gasket."

* Para 4.6.2c: Delete and substitute:

"c. Remove all cover assemblies. Inspect the gasket for fit, security, cuts and splits."

PAGE 17

* Para 4.6.7: Delete "(see 6.8)" and substitute "(see 6.7)".

PAGE 20

6.7: Delete "car" and substitute "care".

The margins of this amendment are marked with an asterisk of vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-0178)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:17Z
Check the source to verify that this is the current version before use.