MIL-F-48126 (MU)
1 November 1972
(See 6.9)
SUPERSEDING

MILITARY SPECIFICATION

FUZE, PD, M720, LOADING ASSEMBLY AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of fuze designated as Fuze, PD, M720.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons; General Specification for
MIL-D-46256	-	Detonator, Stab, M24, Loading, Assembling and Packing
MIL-I-45607	-	Inspection Equipment, Supply and Maintenance of
MIL-P-60412	-	Packaging, Packing and Marking of Artillery Type and Rocket Fuzes

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-331	-	Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-1168	-	Lot Numbering of Ammunition
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

8861213 - Box, Wire bound, Packing, Ammunition, for Artillery or Rocket Type Fuzes
8864492 - Box, Ammunition, Metal for Artillery and Rocket Type Fuzes
9229636 - Fuze, Point Detonating, M720 Assembly
9228935 - Fuze, Point Detonating, Sub-Assembly

PUBLICATIONS

ARMY

ET-9229636 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Fuze assembly. - The PD, M720 Fuze assemblies shall comply with all the requirements specified on the applicable drawings and with all the requirements specified in the applicable specifications.

3.3 Jolt and Jumble. - The fuze assembly shall comply with the requirements of MIL-STD-331, Tests 101 and 102.

3.4 Proving Ground. - The fuzes shall comply with the following requirements when tested in the S.Q. mode.

3.4.1 Arming Safety. - The fuze shall not detonate the supplemental charge of the inert round when fired against a vertical 1 inch plywood target placed at a distance of 25 feet from the muzzle of the weapon.

3.4.2 Arming. - The fuze shall detonate the supplemental charge of the inert loaded round, high order, when fired against a vertical 1 inch plywood target placed at a distance of 160 feet from the muzzle of the weapon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

3.4.3 Ground graze functioning. - The fuze, when fired against a gravel pad, 1000 meters from the muzzle of the weapon, shall detonate the round high order upon initial impact.

3.4.4 Premature bursts. - There shall be no premature bursts in the gun bore or in flight before impact.

3.5 Transportation vibration. - The loaded fuze assembly shall comply with the requirements of MIL-STD-331, Test No. 104.

3.6 Workmanship. - All parts shall be fabricated and finished in a thorough workmanlike manner. They shall be free of burrs, sharp edges, cracks, unblended radii; and chips, dirt, grease, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

3.7 First article inspection. - This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product. - At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Drawing, specification number and date, together with an identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 First article inspection

4.1.2.1 Submission. - The contractor shall submit a first article sample as designated by the contracting officer (see 6.8) for evaluation in accordance with the provisions of 4.1.2.2. The first article sample shall consist of 25 complete sets of parts (i.e., 25 each of every component and every subassembly) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures, and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as directed by the contracing officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.1.2.2 Inspections to be performed. - Assemblies and components will be subjected by the Government to any or all the examinations or tests specified in 4.2.2 and 4.3 of this specification and any or all requirements of the applicable drawings.

4.1.2.3 Rejection. - If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component to comply with any of the stated requirements.

4.2 Inspection provisions

4.2.1 Lot formation. - The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of loaded fuzes shall contain:

a. Parts and parts assemblies of one lot interfix number from one manufacturer.

b. Plunger assemblies of one lot number in an interfix from one manufacturer.

c. Safety adapter assemblies of one lot number in an interfix from one manufacturer.

4.2.2 Examination. - The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspection list shall be in accordance with 4.3.4.

4.2.2.1 Head assembly (see dwg. 8798232, covering a detail of dwg. 9228935).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL .65 percent		
101.	Detonator missing or inverted	Visual	01001
102.	Detonator cushion missing	Visual	01003
103.	Detonator retaining screw not fully seated	Visual	01004
104.	Detonator retaining screw not staked	Visual	01005

4.2.2.2 Fuze Sub-Assembly, prior to assembling head assembly, bottom closing screw assembly, flash tube and ogive (see dwg. 9228935).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Foreign matter in flash hole	Visual	02004
102.	Foreign matter in flash tube cavity	Visual	03003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	02006

4.2.2.3 Fuze Sub-Assembly, prior to assembling head assembly, bottom closing screw assembly and ogive (see dwg. 9228935)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Delay, non-delay plunger assembly armed	Visual	03001
2.	Interrupter does not completely obstruct the flash hole	Visual	02003
Major:	100 Percent Inspection		
105.	Setting sleeve not set perpendicular to base of body	Visual	03004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.65 percent		
101.	Flash tube stake missing	Visual	03002
102.	Delay, non-delay plunger assembly missing	Visual	02005
103.	Foreign matter in delay, non-delay plunger assembly	Visual	02007
104.	Excessive protrusion of setting sleeve above setting sleeve retainer	Gage	03007
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	03006

4.2.2.3.1 Ogive (see dwg. P-9232810)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Wall thickness	Gage	07001
102.	Inside diameter of head end	Gage	07002
103.	Through crack	Visual	07003
Minor:	AQL 4.0 percent		
201.	Inside diameter at body end	Gage	07004
202.	Total length	Gage	07005
203.	Outside diameter of head end	Gage	07006
204.	Outside diameter of body end	Gage	07007
205.	Evidence of poor workmanship, cracks or dents (see 3.6)	Visual	07008
206.	Protective finish missing, damaged, or contains bare spot	Visual	07009
207.	Location of internal projections ...	Gage	07010
208.	Distance between inside projections	Gage	07011

4.2.2.4 Assembly, prior to assembling safety adapter (see dwg. 9228935).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Major:	100 percent inspection		
101.	Ogive improperly positioned	Visual	04001
Major:	AQL 1.0 percent		
102.	Delay, non-delay plunger assembly inverted	Magnet	02001
103.	Bottom closing screw assembly crimp not below flush, min.	Gage	04004
104.	Total length, above max	Gage	04002
105.	Body thread damaged	Visual	04005
106.	Crack or puncture at ogive head stake or dimples	Visual	04006
107.	Ogive head stake missing or inadequate	Visual/ Manual	04007
108.	Bottom closing screw assembly stake missing or inadequate	Visual/ Manual	02002
109.	Distance from base to widest shoulder above threads, (max)	Gage	04003
Minor:	AQL 1.0 percent		
201.	Wrench slots damaged	Visual	04009
202.	Evidence of poor workmanship (see 3.6)	Visual	04010

4.2.2.5 Safety Adapter, prior to final fuze assembly (see dwg. 9229638).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Safety Adapter in an armed or partially armed condition	Visual	06001

Major: None defined

Minor: None defined

4.2.2.6 Assembly (see dwg. 9229636)

Categories	Defects	Method of Inspection	Code No.

Critical: None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

Major:	AQL 1.0 percent		
101.	Torque test failure (safety adapter to fuze) (see 4.4.3)	Test	05002
102.	Stake missing or improper	Visual	05003
103.	Thread damaged	Visual	05004
104.	Booster thread, pitch diam., above	Gage	05007
105.	Separation between booster and fuze above max.	Gage	05008
106.	Length from base of booster to flange, above max.	Gage	05009
107.	Total length, (max.)	Gage	05001
Minor:	AQL 1.5 percent		
201.	Marking missing, incorrect, misleading, or unidentifiable	Visual	05005
202.	Protective coating missing from marking	Visual	05010
203.	Firing pin closing disc missing or damaged	Visual	05018
204.	Evidence of poor workmanship (see 3.6)	Visual	05006

4.3 Testing

4.3.1 Jolt and Jumble - (see 3.3) - Critical defect - Code No. 05019.

4.3.1.1 First three lots. - Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements when tested as specified in 4.4.1, a sample of thirty (30) assemblies shall be randomly selected from each lot for these tests. If any assembly fails to comply with the test requirements, the lot shall be rejected.

4.3.1.2 Subsequent Lots. - After three consecutive lots have met the criteria specified in 4.3.1.1, a sample of twelve (12) assemblies shall be randomly selected from each lot for these tests. If any assembly fails to comply with the test requirements, the lot shall be rejected.

4.3.2 Transportation vibration (see 3.5). - Safe, (Critical defect) Code No. 05014 Operable (Major defect) - Code No. 05013.

4.3.2.1 First three lots. - Beginning with the first lot produced and continuing until three consectuve lots have complied with the applicable requirements, when tested as specified in 4.4.4, a sample of ten (10) loaded assemblies shall be randomly selected from each lot for these tests. If any assembly fails to comply with the requirements, the lot shall be rejected. The fuze shall be safe and operable following the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

4.3.2.2 Subsequent lots. - After three consecutive lots have met the criteria as specified in 4.3.2.1, a sample of five (5) assemblies shall be randomly selected from each lot for these tests. If any assembly fails to comply with the requirements, the lot shall be rejected. The fuze shall be safe and operable following the test.

4.3.3 Proving ground.

4.3.3.1 Premature burst (see 3.4.4) - Critical defect - Code No. 05015. - Any premature burst shall be cause for rejection of the lot.

4.3.3.2 Arming safety (see 3.4.1) - Critical defect - Code No. 05016. - A sample of twenty (20) assemblies shall be randomly selected from each lot for this test. If one or more samples fail to meet the twenty five foot (25) non-arming requirement, the lot shall be rejected. Testing shall be conducted in accordance with 4.4.2.1.

4.3.3.3 Arming (see 3.4.2) - Major defect - Code No. 05017. A sample of thirty two (32) assemblies shall be randomly selected from each lot for this test. If two or more samples fail to meet the one hundred sixty foot (160) arming requirement, the lot shall be rejected. Testing shall be in accordance with 4.4.2.2.

4.3.3.4 Ground and water graze functioning (see 3.4.3) Major defect - Code No. 05011, A sample of twenty (20) assemblies shall be randomly selected from each lot for this test. If four or more samples fail to function upon initial impact, the lot shall be rejected due to graze functioning failures. If two or more of these graze functioning failures are duds the lot shall be rejected. Testing shall be conducted in accordance with 4.4.2.3.

4.3.3.5 Retest. - If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional samples as required.

4.3.3.6 Check test for deterioration of detonator, Stab M24, Major defect. Code No. 09001. - If the total elapsed time between the acceptance of any detonator lot and assembly of that lot into fuze lots exceeds two (2) years, or if the detonators have been subject to adverse conditions, however brief, at any time since previous tests, the detonator lot shall be check-tested as specified in MIL-D-46256 immediately prior to detonator assembly into fuzes. This test shall be performed by the contractor on detonators selected by the Government inspector at the facility assembling

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

the detonators into the fuze. The test shall be conducted at Government expense without cost to the supplier who loaded the detonator or the supplier assembling the detonator into the fuze, and shall not constitute a basis for rejection against either supplier except where deterioration has occurred as a direct result of carelessness in handling, storage, etc. while the detonator lot is under the jurisdiction of either contractor (see 6.4).

4.3.4 Inspection Equipment. - The inspection equipment required to perform the examinations and tests prescribed in this section is identified by Equipment Tabulation ET-9229636 (see 6.3).

4.3.4.1 Government rights to documentation. - Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage or replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.4 Test methods and procedures

4.4.1 Jolt and Jumble (see 4.3.1). - The fuze assemblies shall be tested in accordance with the procedures specified in MIL-STD-331, Test No.'s 101 and 102, except that after completion of the jolt test the assemblies shall not be disassembled but shall be subject to the jumble test. The assemblies shall then be disassembled to determine compliance with the test requirements.

4.4.2 Proving ground (see 3.4 and 4.3.3). - These tests shall be conducted at a Government proving ground in accordance with the Acceptance Test Procedure. The sample fuzes shall be assembled to complete M657 Cartridges loaded as per Table I below, and fired from a 152mm gun cannon. Camera coverage of the target area shall be provided for the first three (3) lots, minimum, for the graze impact functioning test only.

TABLE I

Test	Cartridge Treatment
Arming safety (see 4.4.2.1)	Inert loaded with T2 Supplementary charge
Arming (see 4.4.2.2)	Inert loaded with T2 Supplementary charge
Ground and water graze functioning (see 4.4.2.3)	HE loaded

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

4.4.2.1 Arming safety. - The test samples shall be fired against a suitable supported one inch plywood target, of adequate size, placed twenty-five (25) feet from the muzzle of the weapon. The fuze shall not detonate the round prior to or upon impact with this target. Observation for impact element functioning is required.

4.4.2.2 Arming. - The test samples shall be fired against a suitably supported one inch plywood target, of adequate size, placed one hundred sixty (160) feet from the muzzle of the weapon. The fuze shall detonate the supplemental charge of the inert round, high order with superquick functioning, upon impact with this target. Observation for impact element functioning is required.

4.4.2.3 Ground graze functioning. - The test samples shall be fired against a gravel pad 1000 meters from the muzzle of the weapon. The fuze shall detonate the round high order with superquick functioning, upon initial impact with the target. Observation for impact element functioning is required.

4.4.3 Torque testing. - The disassembly torque shall be applied in a loosening direction while holding the parts immediately adjacent to the joints being tested so as to avoid possible loosening of any other joints. The joint under test shall be marked to provide a means for detection of any movement between the adjacent parts. Any discernable movement between adjacent parts shall be regarded as a torque test failure.

4.4.4 Transportation vibration. - The loaded fuze assemblies shall be tested in accordance with the procedures specified in MIL-STD-331, Test No. 104.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking

5.1.1 The fuze shall be packaged, packed and marked as specified on the applicable drawing in accordance with MIL-P-60412.

6. NOTES

6.1 Ordering data. - Procurement documents shall specify the following:

a. Title, number and date of this specification
b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

6.2 Inspection code numbers. - The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. They should also be cited as references on drawings of equipment designs submitted by the contractor (see 6.3.5)

6.3 Inspection Equipment Designs. - Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers on the Equipment Lists referenced on the Equipment Tabulation. Design responsibility for all other inspection equipment is assigned to the contractor. Equipment to be designed by the contractor is designated "CD". The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE Designs. - SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.
b. A source control drawing or a specification control drawing as defined in MIL-STD-100.
c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor Designs. - Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public.) Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment or with SIE designs if not otherwise covered thereby (see 6.3.1.c). Designs shall be of the category and form (per MIL-D-1000 specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five-digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design, together with the component or assembly drawing number and revision letter to which the specific design applies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

6.3.3 Submission of Designs for Approval. - Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Picatinny Arsenal, ATTN: SMUPA-QA-A-F, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Cost of check test. - The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in performance of the check test. The test shall be conducted at Government expense without cost to the contractor who loaded the detonator or to the contractor assembling this element into the fuze assembly and shall not constitute a basis of rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the element lots were under the jurisdiction of either contractor.

6.5 Visual examination. - When compliance with the applicable requirements is in doubt as a result of visual examination, the characteristic may be measured or gaged to determine acceptability.

6.6 Submission of test data. - In addition to the normal distribution of records, when the cartridge is procured by the Department of the Army, one copy of all test data shall be forwarded to each of the following:

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-QA-A-F
Dover, New Jersey 07801

6.7 It is noted that the size of inspection lots of components, assemblies or items or delivery may differ from the actual quantities contractually scheduled for delivery. However, in order to facilitate scheduling of tests or deliveries, inspection lots of items of delivery may be equivalent to such contract quantities provided all of the lot formation criteria and sampling provisions of this specification are maintained.

6.8 Sumission of first article samples. - Instructions as to the location for evaluation of the first article shall be obtained from the contracting officer. Upon receipt of such request, the contracting officer shall advise

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

Picatinny Arsenal and instructions will be issued accordinly. All inquiries should be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-F, Dover, New Jersey 07801.

6.9 This specification includes the requirements of PA-PD-3093 Rev. A dated 12 January 1969.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1390-A-003

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.