MIL-I-81007(AS)
Amendment 1
28 September 1967

MILITARY SPECIFICATION

Integrated Electronic Centrals
AN/ASQ-56A and AN/ASQ-56B

This amendment forms a part of Military Specification MIL-I-81007(WEP) dated 15 April 1964 and has been approved by Naval Air Systems Command, Department of the Navy.

By this amendment basic MIL-I-81007(WEP) is changed to MIL-I-81007(AS) and throughout the specification, Bureau of Naval Weapons shall be changed to Naval Air Systems Command.

Page 1, Specification Title: Add "and AN/ASQ-56B".

Page 1, Paragraph 1.2: Delete and substitute

"1.2 Classification - The Integrated Electronic Centrals shall be of two types which together shall include the following equipments:

Item	Name	Type Designation	MTBF	MIL-STD-781 Test Plan
1	Receiver-Transmitter, Radio	RT-542/ASQ	170	III
2	Receiver-Transmitter, Radio	RT-542A/ASQ	170	III
3	Receiver-Transmitter, Radio	RT-384/ARN-52(V)	250	III
4	Coder-Receiver-Transmitter	KY-533/ASQ	450	IV
5	Coder-Receiver-Transmitter	KY-533A/ASQ	450	IV
6	Amplifier-Power Supply-Receiver	AM-2310/ASQ	400	IV
7	Antenna	AS-909/ARA-48	2500	VI
8	Control, Radio Set	C-4684/ASQ-56A	5000	VI
9	Mounting-Plenum	MT-2243/ASQ-56	----	--
10	Mounting-Plenum	MT-3946/ASQ-56B	----	--
11	Adapter, Mounting	MX-4773/ASQ-56A	----	--
12	Control, Radio Set	C-2790/ARC		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.

Item	Name	Type Designation	MTBF	MIL-STD-781 Test Plan
13	Switching Unit	SA-629/ARC		
14	Mounting	MT-2141/ARC	560	V
15	Indicator, Frequency Channel	ID-758/ARC		
16	Control, Radio Set	C-8057/ARC	----	--
17	Equipment	Juliet-28	----	--
18	Control Radar Set	C-1159/APX-68	----	--
19	Control, Transponder Set	C-6280(P)/APX	----	--
20	Control, Radar Set	C-1272A/APA-89	----	--
21	Control, Radio Set	C-1457/ARR-40	----	--

Page 1: Add

"1.2.1 Types - The Electronic Centrals covered by this specification shall include the following equipments. Each central shall consist of the items and quantities as specified below:

*Items Required for Each Central

AN/ASQ-56A	AN/ASQ-56B
Item 1	Item 2
3	3
4	5
6	6
7	7
8(2)	8(2)
9	10
11	11
12(2)	12(2)
13	13
14	14
15(2)	15(2)
	16
	17
18	
	19
20	
21	21

*Item numbers correspond to items of paragraph 1.2. Quantity of each item is one unless otherwise designated by quantity in parenthesis.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:54Z
Check the source to verify that this is the current version before use.

Page 2, paragraph 2.1, under SPECIFICATIONS Military: Delete "MIL-R-23094" and title and Add "MIL-C-38357 Control, Transponder Set C-6280(P)/APX" and "MIL-C-81470(AS) Control, Radio Set C-8057/ARC."

Page 3, paragraph 2.1, under STANDARDS Military: Add "MIL-STD-781 Reliability Tests, Exponential Distribution."

Page 4, paragraph 3.2.2: Add

"For the AN/ASQ-56A and 241.0 pounds for the AN/ASQ-56B."

Page 5, paragraph 3.2.4.3: Add "RT-542A/ASQ KY-533A/ASQ"

Page 6, paragraph 3.2.8: Delete and Substitute

"Unless otherwise specified in the individual equipment specification, the generation of radio interference by the equipment and the vulnerability of the equipment to radio interference shall be controlled within the limits of Specification MIL-I-6181B except that an additional 54 db, 43 db and 58 db shall be added to the limits of curves 1, 16 and 17 respectively using a 1 KC bandwidth for tests conducted in accordance with Paragraph 3.1.1 (MIL-I-6181B)."

Page 7, paragraph 3.2.12: Add

"Receiver-Transmitter, Radio	RT-542A/ASQ	Class 2
Coder-Receiver-Transmitter	KY-533A/ASQ	Class 2
Mounting Plenum	MT-3946/ASQ-56B	Class 2

Page 8, paragraph 3.3.1: Delete "RT-542/ASQ" and substitute "RT-542/ASQ or RT-542A/ASQ."

Page 8, paragraph 3.3.4: Delete "KY-533/ASQ" and substitute "KY-533/ASQ or KY-533A/ASQ."

Page 8, Paragraph 3.3.7: Delete and substitute

"3.3.7 Mounting Plenum - The mounting-plenum function for the Integrated Electronic Centrals shall be performed by mounting-plenum MT-2243/ASQ-56A or MT-3946/ASQ-56B in accordance with Specification MIL-M-22673."

Page 8, Add

"3.3.9 Control, Radio Set - The remote control function required for the operation of Juliet equipment shall meet the requirements of Control, Radio Set C-8057/ARC Specification MIL-C-81470(AS).

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:54Z
Check the source to verify that this is the current version before use.

Page 8, paragraph 3.4.2: Add

"for the AN/ASQ-56A or Control, Transponder Set C-6280(P)/APX in accordance with Specification MIL-C-38257 for the AN/ASQ-56B."

Page 9, paragraph 3.4.3: Add

"for the AN/ASQ-56A".

Page 9: Add

"3.4.5 Juliet-28 - The AN/ASQ-56B may be operated with Juliet-28 equipment and the Control, Radio Set C-8057/ARC."

Page 10, paragraph 4.2.1.1, last sentence: Delete

Page 10, paragraph 4.2.3: Add

"During temperature/altitude tests outlined in Specification MIL-T-5422, steps 2,3,4,6,7,9,10,11,12 and 14 cooling air may be supplied at all times.

Page 10, paragraph 4.2.4, last sentence: Delete all after "under the contract".

Page 12, paragraph 4.4.1.3: sentence 7, Delete and substitute

"The direction of vibration shall be either (a) vertical to the normal mounting plane for 5 minutes and lateral to that plane for 5 minutes or (b) rotary for 10 minutes."

Page 13, paragraphs 4.4.3 4.4.3.1. and 4.4.3.2: Delete and substitute

"4.4.3 Reliability Assurance Tests - Reliability Assurance Tests shall be conducted using MIL-STD-781. Qualification Phase and Sampling Phase Tests shall be conducted.

4.4.3.1. Qualification Phase - Prior to the acceptance of equipments under the contract or order, a minimum of three (3) equipments shall be tested as outlined in MIL-STD-781, under the section entitled "Qualification Phase of Production Reliability Tests". The maximum number of equipments to be used shall be those listed in Table 5 of MIL-STD-781. For the Qualification Phase, Test Level E shall be used. The Accept-Reject Criteria for Test Plan III shall be used.

4.4.3.2. Reliability Sampling Phase Tests - Samples of the equipment shall be tested as outlined in MIL-STD-781, under the Section entitled "Sampling Phase of Production Reliability Tests". For the Sampling Phase, Test Level E shall be used. The Accept-Reject criteria for Test Plan III shall be used to determine the length of the tests (until an accept or reject decision is reached).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.

4.4.3.2.1. Lot Size for Sampling Phase - The entire contract quantity (with the exception of those equipments used in the Qualification Phase) shall be evaluated as one lot. The test program shall start the first month after the Qualification phase has been completed. Samples of each month's production shall be selected and placed on test in the same manner as though one month's production was a lot. The samples shall be tested until an accept or reject decision is reached. In the meantime other equipments constructed shall be shipped. The test results shall be summarized monthly for the procuring activity. The procuring activity reserves the right to stop the acceptance of equipment at any time after one or more reject decisions have been reached, pending a review of the contractor's efforts to improve the equipment, the equipment parts, the equipment quality control, etc. so that the entire contract quantity will show an accept decision."

Page 14, paragraph 4.4.3.4(1): Delete and substitute

"(1) UHF Communication - RT-542/ASQ or RT-542A/ASQ

Characteristic	Specification Requirement	Acceptance Requirement
"Receiver Sensitivity	Standard 5 uv/10 db Service 20 uv/10 db	20 uv/10 db
Audio Capability	Standard not less than 250 mw Service not less than 62.5 mw	Not less than 62.5 mw
R-F Power Output	Standard not less than 16 w Service not less than 9 w	Not less than 9 w
Modulation Capability (input to clipping)	Not less than 80%	Not less than 70%
Tone Modulation Capability	Not less than 70%	Not less than 70%
Side Tone Level	Standard not less than 250 mw Service not less than 75 mw	Not less than 75 mw"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.

Page 15, paragraph 4.4.3.4(2) - Revise the specification requirements and acceptance requirements as follows:

Characteristic	Specification Requirement	Acceptance Requirement
"Audio Capability	Standard not less than 250 mw	
	Service not less than 62.5 mw	Not less than 62.5 mw "

Delete:

"ADF 100 cps Inverter and ADF Motor Control"

Page 16, paragraph 4.4.3.4(4): Delete and substitute

"IFF/Coder performance characteristics to be measured on the KY-533/ASQ and KY-533A/ASQ shall be in accordance with Specification MIL-C-22672."

Page 17: Add

"4.4.3.6 Determination of Compliance - Compliance shall be determined in accordance with Test Plan III of MIL-STD-781."

Page 20, paragraph 6.2: Add

"The d-c power requirement shall be as specified in 3.2.1.5 and MIL-STD-704 except that the lower voltage limit under emergency condition shall be 21 volts in lieu of 17 volts."

Page 22, Figure 1 title: Delete "AN/ASQ-56A and substitute "AN/ASQ-56A or AN/ASQ-56B..."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:54Z
Check the source to verify that this is the current version before use.