INCH-POUND


MIL-PRF-55339/17B
w/AMENDMENT 2
03 September 2024
SUPERSEDING
MIL-PRF-55339/17B
w/AMENDMENT 1
15 February 2019

PERFORMANCE SPECIFICATION SHEET

ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, "T", (WITHIN SERIES BNC JACK TO JACK AND SERIES BNC PLUG TO JACK) CLASS 2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the document described herein shall consist of this specification sheet and MIL-PRF-55339.



Part or Identifying Number (PIN): M55339/17-00274 or M55339/17-70001

FIGURE 1. General configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.

Reference	Series	Contact
A	BNC	Pin
B and C	BNC	Socket

NOTES:
1. Dimensions are in inches.
2. All undimensioned pictorial representations are for reference purposes only.
3. Interfaces to be in accordance with MIL-STD-348, series BNC pin contact and series BNC socket contact.

FIGURE 1. General configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.




Reference	Series	Contact
A	BNC	Pin
B and C	BNC	Socket

PIN M55339/17-00001 or M55339/17-70002

NOTES:
1. Dimensions are in inches.
2. All undimensioned pictorial representations are for reference purposes only.
3. Interfaces to be in accordance with MIL-STD-348, series BNC pin contact and series BNC socket contact.

FIGURE 2. General configuration, plug - jack - jack.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.



Reference	Series	Contact
A, B, and C	BNC	Socket

PIN M55339/17-00002 or M55339/17-70003

NOTES:
1. Dimensions are in inches.
2. All undimensioned pictorial representations are for reference purposes only.
3. Interfaces to be in accordance with MIL-STD-348, series BNC socket contact.

FIGURE 3. General configuration, jack - jack - jack.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.

DESIGN AND CONSTRUCTION

General configuration: See figures 1, 2, and 3.

Impedance: 50 ohms, nom.

Working voltage: Sea level – 500 V rms, 70,000 feet (4.437 kPa) – 125 V rms.

Frequency range: 0 to 4 GHz.

Temperature range: -65°C to +165°C.

PERFORMANCE (installation torque is not applicable)

Dimensions: See figures 1, 2, and 3 and MIL-STD-348.

Center contact retention: Axial force 6 pounds, minimum; torque – 4 inch-ounces, minimum.

Force to engage and disengage: Longitudinal force – 3 pounds, maximum;
torque – 2.5 inch-pounds, maximum.

Coupling proof torque: Not applicable.

Mating characteristics:
Center contact (socket):
Oversize test pin dia - .057 inch, minimum.
Insertion depth - .125 inch, minimum.
Number of insertions – 1.
Max test pin (insertion force test):
Steel test pin dia - .054 inch, minimum.
Pin finish – 16 microinches.
Insertion force – 2 pounds, maximum.
Number of insertions – 1.
Min test pin (withdrawal force):
Steel test pin dia - .052 inch, maximum.
Pin finish – 16 microinches.
Withdrawal force – 2 ounces, minimum.
Number of withdrawals – 1.
Outer contact:
Min test ring ID - .319 inch, maximum.
Ring finish – 16 microinches.
Insertion force – 5 pounds, maximum.
Insertion depth - .093 inch, minimum.
Number of insertions – Not applicable.
Max test ring ID - .324 inch, minimum.
Test ring finish – Not applicable.
Insertion depth - .031 inch, maximum.
Number of insertions – Not applicable.

Permeability: Less than 2.0.

Seal: Hermetic – Not applicable.
Pressurized – Not applicable.
Weatherproof – Not applicable.

Insulation resistance: 5,000 megohms, min.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.

VSWR: Not applicable.

RF leakage (total): Not applicable.

RF insertion loss: Not applicable.

Durability: 500 cycles minimum at 12 cycles/min maximum. The connector shall meet the mating characteristics and force to engage and disengage requirements.

Dielectric withstanding: Test voltage – 1,500 V rms, minimum (sea level).

Contact resistance (milliohms, max):

Contact	Initial	After
Center	2.0	2.5
Outer	0.2	N/A
Outer (-70001, -70002 and -70003)	0.4	N/A

Vibration, high frequency: Interruptions – 1 μs, max.

Shock: Test condition I.

Thermal shock: Test condition C.

Moisture resistance: 200 megohms, min.

Corona level: Voltage – 375 V, minimum; altitude - 70,000 feet (4.437 kPa), minimum.

RF high potential withstanding voltage: RF voltage – 1,000 V rms minimum;
frequency – 5 MHz, minimum.

Salt spray (corrosion): Applicable.

Coupling mechanism retention force: 100 pounds, minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.

Cross reference: See table I.

TABLE I. Cross reference of PIN.

PIN	Superseded PIN or type designation 1/
M55339/17-00001	-
M55339/17-00002	-
M55339/17-70001	-
M55339/17-70002	-
M55339/17-70003	-
M55339/17-00274	MS35173 UG-274C/U

1/ The superseded PIN or the type designation is for cross reference only. Where a superseded PIN or type designation is not given, none was assigned or will be assigned. PIN M55339/17-00274 shall be used in all cases for marking and identifying the adapter.

The following PIN's are also available and shall be marked specifically with this PIN:

PIN M55339/17-70001, -70002 or -70003. **CAUTION: THIS PART HAS A NICKEL PLATED BODY AND IS NOT FOR USE IN APPLICATIONS WHERE PASSIVE INTERMODULATION GENERATION (PIM) MAY BE A CONCERN.**

Group qualification: Submission and qualification of any one of the adapters described herein qualifies the respective group in which it was submitted (see table II).


TABLE II. Group qualification.

Qualifying PIN	Group qualification
M55339/17-00274 or M55339/17-00001	Group I accepted 1/

1/ Group I is composed of PIN M55339/17-00294, M55339/17-00001 and M55339/17-00002.

PIN M55339/17-70001, -70002 or -70003 may be approved by the qualifying activity with limited testing as directed by the qualifying activity.

PIN configuration:



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-55339, this document references the following:

MIL-STD-348

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force –85
DLA - CC

Review activities:
Army – AR, AT, EA
Navy – AS, MC, OS
Air Force – 19

Preparing activity:
DLA - CC

(Project 5935-2024-195)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:05Z
Check the source to verify that this is the current version before use.