INCH-POUND


MIL-PRF-55339/24B
w/AMENDMENT 1
12 May 2023
SUPERSEDING
MIL-PRF-55339/24B
17 September 2004

PERFORMANCE SPECIFICATION SHEET

ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, FLANGE MOUNTED, (WITHIN SERIES BNC PLUG TO SERIES N JACK), CLASS 2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the document described herein shall consist of this specification sheet and MIL-PRF-55339.



Reference	Series	Contact
A	BNC	Pin
B	N	Socket

NOTES:
1. Dimensions are in inches.
2. All undimensioned pictorial representations are for reference purposes only.
3. Interface dimensions shall be in accordance with MIL-STD-348, series BNC pin contact and series N socket contact.

FIGURE 1. General configuration

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:06Z
Check the source to verify that this is the current version before use.

DESIGN AND CONSTRUCTION

General configuration: See figure 1.

Impedance: 50 ohms, nom.

Working voltage: Sea level – 500 V rms.
70,000 feet (4.437 kPa) – 125 V rms.

Frequency range: 0 to 4 GHz.

Temperature range: -65° to +165°C.

PERFORMANCE (installation torque of 6 to 10 in. lb (0.68 to 1.13 Nm), series N)

Dimensions: See figure 1 and MIL-STD-348.

Center contact retention:	Series BNC	Series N
Axial force (lb. min)	6 (26.7 N)	6 (26.7 N)
Torque (in. oz, min)	N/A	N/A

Force to engage and disengage:	Series BNC	Series N
Longitudinal force (lb. max)	3.0 (13.3 N)	N/A
Torque (in. lb, max)	2.5 (0.34 Nm)	6.0 (0.68 Nm)

Coupling proof torque: Not applicable.
Mating characteristics, series N:
Center contact (socket):
Oversize test pin dia - .074 in., min.
Insertion depth - .125 in., min.
No. of insertions – 1.
Max test pin (insertion force test), series N:
Steel test pin dia - .066 in., min.
Pin finish – 16 microinches.
Insertion force – 2 lb (8.89 N), max.
No. of insertions – 1.
Min test pin (withdrawal force), series N:
Steel test pin dia - .063 in., max.
Pin finish – 16 microinches.
Withdrawal force – 2 oz (0.56 N).
No. of withdrawals – 1.
Outer contact, series BNC:
Min test ring ID - .319 in., max.
Ring finish – 16 microinches.
Insertion force – 5 lb (22.24 N), max.
Insertion depth - .093 in., min.
No. of insertions – 1.
Max test ring ID - .324 in., min.
Test ring finish – 16 microinches.
Insertion depth - .031 in., max.
No. of insertions – 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:06Z
Check the source to verify that this is the current version before use.

Permeability: <2.0.

Seal: Hermetic – Not applicable.
Pressurized – Not applicable.
Weatherproof – Not applicable.

Insulation resistance: 5,000 megohms, min.

VSWR: 1.35, max .5 to 4 GHz.

RF leakage (total): -55 dB, min, 2 to 3 GHz.

RF insertion loss: .1 dB, max, 3 GHz ($.06\sqrt{F\ (GHz)}\ dB$ max tested at 3 GHz).

Durability: 500 cycles minimum at 12 cycles/min, maximum. The connector shall meet the mating characteristics and force to engage and disengage requirements.

Dielectric withstanding: Test voltage – 1,500 V rms, min (sea level).

Contact resistance (milliohms, max):

Contact	Initial	After
Center	1.0	1.5
Outer	1.5	N/A
Outer (-7001)	3.0	N/A

Vibration, high frequency: Interruptions – 1 μs, max.

Shock: Test condition I.

Thermal shock: Test condition C.

Moisture resistance: 200 megohms, min.

Corona level: Voltage – 375 V, min.
Altitude - 70,000 feet (4.437 kPa), min.

RF high potential withstanding voltage: RF voltage – 1,000 V rms. min.
Frequency – 5 MHz, min.

Salt spray (corrosion): Applicable.

Coupling mechanism retention force: Not applicable.

Part or Identifying Number (PIN): M55339/24-00335.

PIN: M55339/24-70001. **CAUTION: THIS PART HAS A NICKEL PLATED BODY AND IS NOT FOR USE IN APPLICATIONS WHERE PASSIVE INTERMODULATION GENERATION (PIM) MAY BE A CONCERN.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:06Z
Check the source to verify that this is the current version before use.

TABLE I. Cross reference of PIN's.

PIN	Superseded PIN or type designation 1/
M55339/24-00335	REB49103 UG-335A/U

1/ The superseded PIN or the type designation is for cross reference only. Where a superseded PIN or type designation is not given, none was assigned or will be assigned. The PIN M55339/24-00335 shall be used in all cases for marking and identifying the adapter.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-55339, this document references the following:

MIL-STD-348

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2022-221)

Review activities:
Army – AR, AT, EA
Navy – AS, MC, OS
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:06Z
Check the source to verify that this is the current version before use.