INCH-POUND


MIL-PRF-55339/49A
w/AMENDMENT 1
12 January 2023
SUPERSEDING
MIL-PRF-55339/49A
10 January 2005

PERFORMANCE SPECIFICATION SHEET

ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY
(BETWEEN SERIES N JACK TO SERIES BNC PLUG)

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-55339.



Reference	Series	Contact
A	BNC	Pin
B	N	Socket

NOTES:
1. Dimensions are in inches.
2. All undimensioned pictorial representations are for reference purposes only.
3. Interface shall be in accordance with MIL-STD-348.

FIGURE 1. General configuration.

AMSC N/A FSC 5935
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:07Z
Check the source to verify that this is the current version before use.

DESIGN AND CONSTRUCTION:

General configuration: See figure 1.

Impedance: 50 ohms, nominal.

Working voltage:

Sea level: 500 Vrms.

70,000 feet (4.437 kPa): 125 Vrms

Frequency range: 0 to 4 GHz.

Temperature range: -65º to +165ºC.

PERFORMANCE:

Dimensions: See figure 1 and MIL-STD-348.

Center contact retention:	Series BNC	Series N
Axial force (lb, minimum)	6 (26.69 N)	6 (26.69 N)
Torque (in. lb, maximum)	N/A	N/A

Force to engage and disengage:	Series BNC	Series N
Longitudinal force (lb, maximum)	3.0 (13.34 N)	N/A
Torque (in, lb, maximum)	2.5 (0.28 Nm)	6.0 (0.68 Nm)

Coupling proof torque: Not applicable.

Mating characteristics:

Outer contact:	Series BNC
Minimum test ring ID (in., maximum)	.319
Ring finish (microinches)	16
Insertion force (lb, maximum)	5 (22.24 N)
Insertion depth (in., minimum)	.093
Number of insertions	1
Maximum test ring ID (in., minimum)	.324
Test ring finish (microinches)	16
Insertion depth (in., min)	.031
Number of insertions	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:07Z
Check the source to verify that this is the current version before use.

Center contact (socket):	Series N
Oversize test pin diameter (inch, minimum)	.074
Insertion depth (inch, minimum)	.125
Number of insertions	1
Maximum test pin (insertion force test):	
Steel test pin diameter (inch, minimum)	.066
Pin finish (microinches)	16
Insertion force (lb, maximum)	2 (8.90 Nm)
Number of insertions	1
Minimum test pin (withdrawal force):	
Steel test pin dia (in., maximum)	.063
Pin finish (microinches)	16
Withdrawal force (oz, minimum)	2 (0.56 Nm)
Number of withdrawals	1

Permeability: <2.0

Seal:

Hermetic: Not applicable.

Pressurized: Not applicable.

Weatherproof: Not applicable.

Insulation resistance: 5,000 megohms, minimum.

VSWR: 1.35:1, max at .5 to 4 GHz.

RF leakage (total): -55 dB, min, 2 to 3 GHz.

RF insertion loss: .1 dB, max 3 GHz ($.06\sqrt{F\ (GHz)}\ dB$ max tested at 3 GHz).

Durability: 500 cycles minimum at 12 cycles/min maximum The connector shall meet the mating characteristics and force to engage and disengage requirements.

Dielectric withstanding:

Test voltage: 1,500 Vrms, minimum (sea level).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:07Z
Check the source to verify that this is the current version before use.

Contact resistance (milliohms, maximum).

Contact	Initial	After environment
Center	2.0	2.5
Outer	1.5	N/A
Outer (-70001)	3.0	N/A

Vibration, high frequency:

Interruptions: 1 microsecond (μs), max.

Shock: Test condition I.

Thermal shock: Test condition C.

Moisture resistance: 200 megohms, min.

Corona level:

Voltage: 375 V, minimum.

Altitude: 70,000 feet (4.437 kPa), minimum.

RF high potential withstanding voltage:

RF voltage: 1,000 Vrms. minimum.

Frequency: 5 MHz, minimum.

Salt spray (corrosion): Applicable.

Coupling mechanism retention force: 100 lb (444.82 N), minimum.

Part or Identifying Number (PIN): M55339/49-00349 or:

PIN: M55339/49-70001 **CAUTION: THIS PART HAS A NICKEL PLATED BODY AND IS NOT FOR USE IN APPLICATIONS WHERE PASSIVE INTERMODULATION GENERATION (PIM) MAY BE A CONCERN.**

TABLE I. Cross reference of PINs.

PIN	Superseded PIN or type designation 1/
M55339/49-00349	UG-349/U

1/ The superseded PIN or the type designation is for cross reference only. Where a superseded PIN or type designation is not given, none was assigned or will be assigned. The PIN M55339/49-00349 shall be used in all cases for marking and identifying the adapter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:07Z
Check the source to verify that this is the current version before use.

Reference documents. In addition to MIL-PRF-55339, this document references the following:

MIL-STD-348

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2022-129)

Review activities:
Army - AR, AT, EA
Navy - AS, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:07Z
Check the source to verify that this is the current version before use.