MILITARY SPECIFICATION

PERISCOPES, TANK: XM44E1 AND XM44E2
WITH ASSOCIATED EQUIPMENT

This amendment forms a part of Military Specification MIL-P-60649B(MU), dated 30 September 1969 and is approved for use by all Departments and Agencies of the Department of Defense.

* Paragraph 1. SCOPE

* Paragraph 1.2.2, Delete and substitute. "This assembly positions and secures the periscope, a ballistic guard and manually operable shield provide protection against blast damage"

* Paragraph 1.2.6, Delete.

* Paragraph 2.1, "Specifications" - Delete "MIL-I-55536" and substitute "MIL-I-55340"

Paragraph 2.1, "DRAWINGS": Delete "F10542200-2 Periscope, Tank, XM44E2" and substitute "F11731100 Periscope, Tank, XM44E2".

Paragraph 2.1, "DRAWINGS": Add the following:

F11738174 Gage - interchangeability - Body Maximum
F11738175 Gage - interchangeability - Body Minimum
F11738176 Gage - interchangeability - Head Minimum
F11738177 Gage - interchangeability - Head Maximum
F11738178 Gage - interchangeability - Mount Maximum
F11738179 Gage - interchangeability - Mount Minimum

* Paragraph 2.1 "DRAWINGS", Delete F8589797
TABLE I, Delte, "Washer, Pump and Reservoir Assembly, 8589797"

* Paragraph 3.7e, Delete the word "wiper"

* Paragraph 3.8.c , Delete and substitue: "The periscope switch in the On position, and the Reset Switch operated."

* Paragraph 3.8.d, Delete and substitute: "The reticle light intensity and panel light intensity knobs at the limit of their clockwise rotation"

* Paragraph 3.8.e, Delete and substitute: "The linkage assembly, plate assembly, battery mounting bracket and boresight aid assembly vibrated as separate assemblies.

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:53Z
Check the source to verify that this is the current version before use.

* Paragraph 3.8.f, Delete.

* Paragraph 3.10.1.1, Change "JI-J" to "JI-H"
Change "JI-K" to "JI-J"

Delete: Drawing "F10542023" and substitute "F11748431"

* Paragraph 3.10.2.1, Delete words "and Wiper R3"

* Paragraph 3.10.2.2, Delete last sentence and substitute: "primary power shall be applied as follows: +30 VDC to JI-H, GRD to JI-J"

* Paragraph 3.10.2.3, Change: "Primary Power" to "Battery Power" Add to last sentence "and Switch S2 shall be operated"

* TABLE III, Change: "Primary Power" to "Battery Power"
Change: "5.6 + .4" to "5.6 $\pm$ .4"
Change: "1.7 + .2" to "1.7 $\pm$ .2"

* Paragraph 3.10.2.4, Delete.

* TABLE IV, Delete.

* TABLE V, Add new heading, "S2 Position" switch unoperated for battery charging off (center); switch operated for all other outputs.

Change: "5.9 $\pm$ .01 Volts" to "6.5 $+\,^{.25}_{.00}$ Volts"

* Paragraph 3.10.3-Delete words "and wiper knob"

* Paragraph 3.11.3, Delete words "and wiper mechanism"

* Paragraph 3.11.3.4 through 3.11.3.4.3, Delete.

* Paragraph 3.12.3.3, Add at end of third sentence - - - respectively, "and Switch S2 operated".

* Paragraph 3.13.1: Delete sub-paragraph "b" and substitue "b". The 2-1/4" x 2.499" mounting surface located by the 0.250 inch dimension (shown on Drawing F10542037) horizontal within 30 minutes of arc."

Paragraph 3.13.1.c: Delete "2-1/4" by 1-1/4" mounting surfaces" and substitute "2-1/4 inches x 2.449 inches mounting surface".

* Paragraph 3.13.2: Add the following:

"3.13.2 Interchangeability.

3.13.2.1 The Mount Assembly (10513360) shall be capable of accepting all Head Assemblies (10542204) and Body Assemblies (10542201, 11731101 and shall meet the requirements of 3.12.4.a.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:53Z
Check the source to verify that this is the current version before use.

3.13.2.2 The Head Assembly 10542204 shall be capable of accepting all Body Assemblies (10542204) and Mount Assemblies 10513360 and shall meet the requirements of paragraph 3.12.4a.

3.13.2.3 The Body Assembly 10542201, 11731101 shall be capable of accepting all the Head Assemblies (10542204) and Mount Assemblies 10513360 and shall meet the requirements of paragraph 3.12.4.a."

* TABLE VI, Delete: "105 Rheostat R3"

* TABLE VII, Delete: "121 Limit Switch, Wiper Assym"
"122 Circuit Breaker"
"120 Motor and Linkage"

* TABLE XII, Delete: "310 Motor and Linkage"
"311 Limit Switch"

Paragraph 4.4.2.1: Delete and substitute -

"4.4.2.1 Panel assembly.- Three panel assemblies shall be selected at random as samples from each 50 produced, or from each month's production whichever, occurs first. Each sample shall meet the requirements and tests in Table XII, and shall then meet the requirements and tests in Table VII."

Paragraph 4.4.2.6: Add the following:

"4.4.2.6 Periscope, Tank, XM44E1 and XM44E2.- Three periscopes shall be selected at random as samples from the first month's production and at 25%, 50%, and 75% completion of the contract production. Each sample shall meet the interchangeability requirements of 3.13.2 when tested in accordance with test method specified in 4.6.10.13."

Paragraph 4.5.2.3.3.b: Delete "2-1/4 by 1-1/4" mounting surfaces" and substitute "2-1/4 inches x 2.400 inches mounting surfaces".

Paragraph 4.5.3: Add the following

"Oscilloscope Accuracy: $\pm$ 1% of reading
(peak-to-peak)"

* Paragraph 4.5.7.3.4, Delete "Rheostat R3"

* Paragraph 4.6.7.3.5.e, Change "+5.9 Volts" to "6.5 Volts"

* Paragraph 4.6.8.3.4, Delete.

* Paragraph 4.6.8.3.5, Delete.

* Paragraph 4.6.8.4, Delete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:53Z
Check the source to verify that this is the current version before use.

Paragraph 4.6.10.13, Add the following:

"4.6.10.13 Interchangeability.- Each sample periscope (See 4.4.2.6) shall be disassembled to permit interchange of the Head, Mount, and Body Assemblies.

Each component part (head, mount, and body assemblies) shall be inserted into their respective minimum and maximum interchangeability gages (See 2.1) and shall be capable of being firmly secured and removed without interference.

After each component part has been gaged and found acceptable, the components shall be identified and assemblied as shown in TABLE XVI.

TABLE XVI

Original Component Positions

Periscope No. 1 - Head No. 1 Mount No. 1 Body No. 1
Periscope No. 2 - Head No. 2 Mount No. 2 Body No. 2
Periscope No. 3 - Head No. 3 Mount No. 3 Body No. 3

Interchanged Component Positions

Periscope No. 4 - Head No. 1 Mount No. 3 Body No. 2
Periscope No. 5 - Head No. 3 Mount No. 2 Body No. 1
Periscope No. 6 - Head No. 2 Mount No. 1 Body No. 3

Upon reassembly of the three interchanged periscopes, each periscope shall be subjected to the sealing test specified in 4.6.10.8 and meet the requirements of 3.12.4a.

The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A710

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:53Z
Check the source to verify that this is the current version before use.