MIL-P-63143A (AR)
AMENDMENT 2
24 March 1988
SUPERSEDING
AMENDMENT 1
23 August 1983

MILITARY SPECIFICATION

PROJECTILE, 8 INCH, HE, RA, M650
ACCESSORIES FOR

This amendment forms a part of Military Specification MIL-P-63143A (AR), dated 01 February 1979, and is approved for use within the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, Drawings, ARRADCOM, Product and Packaging, delete the following drawings:

"9287978 - Pad
9287979 - Disk"

Add the following drawings:

"9370181 - Cup
9370182 - Pad
9370183 - Disc
9370215 - Disk"

PAGE 4

4.3.1, delete the following drawings:

"Pad - 9287978 - 10*
Disk - 9287979 - 10"

Add the following drawings:

"Cup - 9370181 - 10*
Pad - 9370182 - 10*
Disc - 9370183 - 10*
Disk - 9370215 - 10"

PAGE 6

Table I, Sheet 2:

Delete "9287978" and substitute "9370182"
Delete "9287979" and substitute "9370215"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

PAGE 7

Table I, Sheet 3, add the following:

"Cup
(Dwg. 9370181)
Examination for Defects 10 3.2 4.4.2.16

Disc
(Dwg. 9370183)
Examination for Defects 10 3.2 4.4.2.17"

PAGE 16

4.4.2.8: Delete "9287978" and substitute "9370182"

Add Major defects 103 and 104 as follows:

Major category:

"Major 103: Hole diameter (a) 3.2 Ruler

Major 104: Hole missing or off center 100% 3.2 Visual"

PAGE 17

4.4.2.9: Delete "9287979" and substitute "9370215"

Add Major defects 105, 106, 107 and 108 as follows:

Major category:

"Major 105: Hole diameter, max. 0.40% 3.2 Gage

Major 106: True position of hole 0.40% 3.2 Gage

Major 107: Hole missing 100% 3.2 Visual

Major 108: Thickness through web, min. 0.40% 3.2 Gage"

PAGE 24

Add 4.4.2.16 and 4.4.2.17 as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 of 1		DRAWING NUMBER
4.4.2.16	Cup				9370181
					NEXT HIGHER ASSEMBLY
					9370179
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Crack, split, puncture or similar damage extending through material		0.40%	3.2	Visual
Minor					
201	Thickness		(a)	3.2	Gage
202	Inside diameter		(a)	3.2	Gage
203	Outside diameter		(a)	3.2	Gage
204	Total length		(a)	3.2	Gage
205	Evidence of poor workmanship		(a)	3.5	Visual

NOTES:
(a) See 4.4.3.1 and 4.4.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9370138
4.4.2.17	Disc				NEXT HIGHER ASSEMBLY 9287993
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness, min.		(a)	3.2	Gage
102	Diameter		(a)	3.2	Gage
Minor					
201	Evidence of poor workmanship		(a)	3.5	Visual

NOTES: (a) See 4.4.3.1 and 4.4.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

* Add 4.4.3.6.1 and 4.4.3.6.2 as follows:

4.4.3.6.1 Inspection at 0% moisture. 0% moisture (dry) is the normal post molding condition. All inspections and tests may be conducted on dry bands. The diameter of a dry band equivalent to a band at 6% moisture is as follows:

6% Reg	0% Equivalent
7.74 + .08	7.52 + .08

All other dimensions shall apply between dry and 6% moisture.

4.4.3.6.2 Procedures for dry inspection. To inspect the bands dry the following procedures must be used to assure a moisture content near 0%.

a. Weigh sample band to nearest 0.001g.
b. Dry band for 24 hours minimum at 120°F minimum.
c. Cool band in desiccator.
d. Weigh sample band to nearest 0.001g.

If weight loss in 24 hours does not exceed 0.050g, the band can be considered to have 0% moisture content."

* Add 4.4.3.7, 4.4.3.7.1 and 4.4.3.7.2 as folllows:

"4.4.3.7 Alternate inspection - case, adapter-booster. If the case is produced on an automatic screw machine, NC machine, or similar automatic tool, and the features in 4.4.2.6 cannot be inspected without removal from the tool, the following alternate inspection may be utilized.

4.4.3.7.1 Initial sampling. The first pieces from each tool shall be inspected for both defects listed in 4.4.2.6 until 20 consecutively produced parts have been found acceptable. Changes to the set-up or tool developing the large outside diameter, other than normal wear, shall require requalification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.

4.4.3.7.2 Subsequent sampling. One piece from each hour's production shall be inspected for both defects listed in 4.4.2.6. If any defect is found, all production since the previous acceptable piece shall be rejected and sampling shall return to 4.4.3.7.1."

PAGE 26

6.3: Delete "Command, Attn: DRDAR-QAR-I" and substitute "Center, Attn: AMSMC-QAR-I (D)".

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-AB16)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:19Z
Check the source to verify that this is the current version before use.