
MIL-L-15098/2B
16 December 1977
SUPERSEDING
MIL-L-15098/2A
14 December 1973

MILITARY SPECIFICATION SHEET

LAMPS, GLOW, CIRCUIT CONTROL, TYPES 5AC, 5AG-A, 5AH, RT2-32-1A, AND 5AJ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the glow lamps described herein shall consist of this document and the latest issue of Specification MIL-L-15098.



REQUIREMENTS:

Design and configuration - See figure.
Vibration - See table I.
Shock - Method II.
Part number: M15098/2 - (dash number from table I).

Ⓑ TABLE I. Dash number and characteristics.

Characteristics	Dash no. 001	Dash no. 002	Dash no. 003	Dash no. 004	Dash no. 005
Bulb, T2, diameter (inches)	0.244	0.244	0.244	0.244	0.244
Bulb length (inch maximum)	1.000	1.000	0.938	1.000	0.938
Base	NB	NB	NB	NB	NB
Electrode shape	W11	W11	W11	W11	W11
Electrode length (millimeter minimum)	7.0	7.0	11.5	11.5	11.5
End of electrode to bulb tip (maximum inch)	0.500	0.500	0.312	0.375	0.312
Lead length (inch) (±.062)	1.000	1.500 anode (+) 1.000 cathode (-)	1.000	0.750 anode (+) 1.000 cathode (-)	1.000
Preaged	No	Yes	No	Yes	No
Preage marking	---	Dot at anode	---	Dot at anode	---
Characteristic gas	Neon	Neon	Neon	Neon	Neon
Glow color	Red	Red	Red	Red	Red
Series resistor external (ohms)	200,000	150,000	5,600	5,000	47,000
Application	CKT Comp	CKT Comp	CKT Comp	CKT Comp	CKT Comp
Watts, nominal	---	---	---	---	---
Nominal circuit voltage (volts)	120	120	120	120	120
Initial starting voltage: In light (volts) In dark (volts)	 60-90 dc 60-100 dc	 68-76 dc 68-86 dc	 60-100 dc 60-110 dc	 70-82 dc 70-90 dc	 55-90 dc 110 dc max
Initial maintaining voltage (volts)	52-65 dc	50-60 dc	50-70 dc	50-65 dc	60-65 dc

Ⓑ denotes changes

FSC 6240

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:31Z
Check the source to verify that this is the current version before use.

Ⓑ TABLE I. Dash number and characteristics -Continued

Characteristics	Dash no. 001	Dash no. 002	Dash no. 003	Dash no. 004	Dash no. 005
Initial extinguishing voltage (volts)	50 dc, min	50 dc, min	50 dc, min	50 dc, min	50 dc, min
Vibration	Applicable	Applicable	Not applicable	Not applicable	Not applicable
Design current (milliamperes)	0.3	0.4	10	10	1.5
Life at design current (hours avg)	2,000	2,000	500	2,500	2,000
Industry numbers (ANSI) (Former lamp number)	5AC (NE-68)	5AG-A (NE-76)	5AH (NE-83)	RT2-32-1A -------	5AJ (NE-86)

Custodians:
Army - EL
Navy - SH
Air Force - 99

Review activities:
Army - MI, AR
Navy - CG
Air Force - 11
DLA - GS

User activities:
Army - ME
Navy - AS, MC

Preparing activity:
Navy - SH

Agent:
DLA - ES

(Project 6240-0293-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:31Z
Check the source to verify that this is the current version before use.