[INCH-POUND]
A-A-59399
28 September 1999
SUPERSEDING
MIL-P-80008D
16 March 1990

COMMERCIAL ITEM DESCRIPTION

PUNCHING MACHINE, METAL, TURRET TYPE, HAND OPERATED

The General Services Administration has authorized the use of this commercial item description as a replacement for MIL-P-80008D for all federal agencies.

1. SCOPE. This commercial item description (CID) covers hand operated metal turret punch machines of the multi-station turret type, complete with equipment and accessories as specified herein.

2. CLASSIFICATION. The multi-station turret punch shall be of the following types, and sizes:

2.1 Type. Type refers to the method used to rotate the turret. Unless otherwise specified (see 7.2(b)), the types described herein are as follows:

Type I - Hand synchronized turret rotation
Type II - Hand wheel/gear synchronized turrets
Type III - Non synchronized turrets

2.2 Size. Size is determined by rated capacity in tons, throat depth and number of punching stations. Unless otherwise specified (see 7.2(c)), the sizes described herein are as shown in table 1:

TABLE I. Machine sizes and capacities.

Size	Capacity	Throat Depth	Number of Stations	Size	Capacity	Throat Depth	Number of Stations
07	5 tons	12 inch throat	10	17	12 tons	12 inch throat	15
09	8 tons	12 inch throat	12	18	12 tons	26 inch throat	18
13	5 tons	18 inch throat	18	19	12 tons	26 inch throat	20
14	8 tons	18 inch throat	18	20	15 tons	20 inch throat	18
15	10 tons	18 inch throat	18	21	15 tons	26 inch throat	20
16	10 tons	26 inch throat	18	22	20 tons	26 inch throat	20

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent to: Defense Supply Center Richmond (DSCR), ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond, VA 23297-5610.

AMSC N/A FSC 3445

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 Design. The punch machine shall be new and one of the manufacturer's current production models offered for sale on the commercial market. The punch machine shall be a self-contained unit and shall include all components, parts, and features necessary to meet the requirements of this commercial item description. The design shall include two multi-punch station type turrets, mounted on a "C" type frame. The upper turret shall be provided with punch holders and the lower turret will be provided with die holders.

3.2 Controls. The punch machine shall be equipped with all the controls required for the complete control of pressing operations. All operating controls shall be located convenient to the operator at his normal workstation.

3.3 Components. The punch machine shall consist of not less than a frame, turrets, punch holders, die holders, punches and dies, strippers, and ram.

3.3.1 Frame. The frame structure shall be of the mass, weight, and rigidity to withstand stresses produced when operating the punch machine at its maximum capacity without permanent deformation or failure. The frame shall be of the "C" frame style, stress relieved, with a throat depth not less than that specified for the size ordered. The frame shall have a tensile strength of not less than 45,000 pounds per square inch (P.S.I.). The frame shall have provisions for mounting the punch machine to a work surface or stand.

3.3.2 Turrets. The punch machine shall be provided with upper and lower rotating turrets mounted on bearing surfaces. The punch machine shall be arranged to allow rotation of the turrets for positioning the selected punch station under a lever actuated ram. Unless otherwise specified (see 7.2(d)), each turret shall be provided with the number of stations specified for the size ordered. The turrets shall be provided with indexing pins for aligning the punches of the upper turret with the corresponding dies of the lower turret. The punch machine shall be provided with the means for preventing the ram from being actuated until the turrets are locked into the punching position. The turrets for type I and II machines shall be synchronized to rotate as a single unit.

3.3.2.1 Punch holders. Each punch station shall be provided with a punch holder. The punch holder shall be arranged to securely hold the punch in position. The punch holders shall be designed to accommodate round and shaped punches. The punch holders shall be keyed to assure positive alignment with the dies.

3.3.2.2 Die holders. Each punch station shall be provided with a die holder. The die holder shall be arranged to securely hold the die in position. The die holder shall be designed to hold round and shaped dies. The die holder shall be keyed to assure positive alignment with the punch.

3.3.3 Punches and dies. The punch machine shall be furnished with one set of punches and dies. Unless otherwise specified (see 7.2(e)), the punch and die set shall be the sizes normally provided by the manufacturer for the size machine specified. The punches and dies shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.

constructed of tool steel, hardened and ground for accuracy. The punches and dies shall be marked to identify each punch with the corresponding die.

3.3.4 Nibbling shear. When specified (see 7.2(f)), the punch machine shall be furnished with a manually operated nibbling shear. The nibbling action of the shear shall be accomplished by the use of the hand lever actuated ram. The nibbling shear shall be capable of performing cutouts in mild steel with a thickness not more than 12 gauge.

3.3.5 Strippers. The punch machine shall be provided with strippers or other means for automatically releasing the workpiece from the punch when the punch is withdrawn from the die.

3.3.6 Ram. A hand lever actuated ram shall accomplish the punching action of the punch machine. The ram shall be designed to assure that sufficient energy is developed by a single stroke of the hand lever to accomplish the performance requirements specified herein. The hand lever shall be not more than 36 inches in length.

3.4 Worktable. When specified (see 7.2(g)), each machine shall be provided with either a steel plate, stress relieved, production worktable with manual adjustment back and side gauges, or a precision worktable with manual micrometer adjustment back and side gauges. The back gauge shall provide workpiece adjustment in the "Y" axis direction from the ram center through not less than two-thirds of the throat depth. The side gauge shall provide workpiece adjustment not less than 12 inches from the ram center to either side in the "X" axis direction.

3.5 Floor stand. When specified (see 7.2(h)), each machine shall be equipped with a floor stand. The floor stand shall be designed and constructed to provide machine stability during punching operations.

3.6 Standard equipment. All standard equipment normally provided with the manufacturers commercial press shall be furnished.

3.7 Optional equipment. When specified (see 7.2(i)), optional equipment shall be furnished as specified and shall be fully described by the procuring activity.

3.8 Physical size limitations. When specified (see 7.2(j)), the physical size of the press shall not exceed the height, width, and length restrictions specified by the procuring activity to ensure the press will fit into its future operating location.

3.9 Marking on instruments, control panels, charts, and plates. All words on the press, including all instruments, control panels, charts, plates and related attachments, shall be in the English language. Characters shall be marked in boldface on a contrasting background. All plates shall be corrosion resistant.

3.10 Data plates. All standard data plates normally provided with the manufacturers standard commercial press shall be furnished. Additional data plates, if required (see 7.2(k)), shall be provided as specified and fully described by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.

3.10.1 Nameplate. A nameplate shall be securely attached to each press. Unless otherwise specified (see 7.2(l)), the nameplate shall contain the information listed below.

a. Nomenclature
b. Manufacturer Name
c. Manufacturer Model
d. Manufacturer Serial Number
e. Contract Number or Order Number
f. National Stock Number
g. Date of Manufacture

3.11 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, "Preferred Metric Units For General Use By the Federal Government", and all other requirements of this commercial item description are met.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE

5.1 Product conformance. The product provided shall meet the salient characteristics of this commercial item description; conform to the producer’s own drawings, specifications, standards and quality assurance practices; and is the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

6. PACKAGING

6.1 Preservation, packing, and marking. For acquisition purposes, the products shall be preserved, packed, and marked as specified in the acquisition order (see 7.2(m)).

7. NOTES

7.1 Sources of documents

7.1.1 Government documents. Printed FAR and Federal Standards may be obtained from the U.S. Government Printing Office, Superintendent of Documents, Mail Stop: SSOP, Washington, DC 20402-9328. Electronic copies of FAR documents may be obtained from http://www.access.gpo.gov. Electronic copies of Federal Standards may be obtained from http://astimage.daps.dla.mil/quicksearch/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.

7.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in the order:

a. Title, number, and date of this specification
b. Type (see 2.1)
c. Size (see 2.2)
d. Turrets, specify punching stations, if different (see 3.3.2)
e. Specify punch and die sizes, if different (3.3.3)
f. Nibbling shear, if required (see 3.3.4)
g. Worktable, if required, specify production or precision (see 3.4)
h. Floor stand, if required (see 3.5)
i. Optional equipment, if required (see3.7)
j. Physical size limitations, if required (see 3.8)
k. Additional data plate, if required (see 3.10)
l. Nameplate requirements, if different (see 3.10.1)
m. Packaging requirements (see 6.1)

7.3 Part identification number (PIN). The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

AA59399 – X XX

Size:
07 - 5 tons, 12 inch Throat, 10 Station
09 - 8 tons, 12 inch Throat, 12 Station
13 - 5 tons, 18 inch Throat, 18 Station
14 - 8 tons, 18 inch Throat, 18 Station
15 - 10 tons, 18 inch Throat, 18 Station
16 - 10 tons, 26 inch Throat, 18 Station
17 - 12 tons, 12 inch Throat, 15 Station
18 - 12 tons, 26 inch Throat, 18 Station
19 - 12 tons, 26 inch Throat, 20 Station
20 - 15 tons, 20 inch Throat, 18 Station
21 - 15 tons, 26 inch Throat, 20 Station
22 - 20 tons, 26 inch Throat, 20 Station

Type:
A - Type I Hand Synchronized Turret Rotation
B - Type II Hand Wheel/Gear Synchronized Turrets
C - Type III Non Synchronized Turrets

CID number

7.4 National stock numbers (NSNs). The following NSNs correspond to this CID. The list is not indicative of all possible NSNs associated with this document.

3445-01-051-9998
3445-00-263-0103
3445-00-357-6789

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Air Force - 99
Army - AL
Navy - SH

Reviewer:
Air Force - 84

CIVIL AGENCY
COORDINATING ACTIVITY:

GSA - 6FET

Preparing activity:
DLA - GS

(Project 3445-0151)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.