[INCH-POUND]
A-A-59409
March 22, 1999

COMMERCIAL ITEM DESCRIPTION

LUBRICATING UNIT, POWER-OPERATED

The General Services Administration has authorized the use of this commercial item description for all Federal agencies.

1. SCOPE. This Commercial Item Description (CID) covers a portable, self contained, electrically powered lubricating unit. This unit supplies grease of viscous lubricant with high load carrying capacity for a temperature range of -80°F to +250°F. The grease is intended for use in bearings (roller, ball, and needle), gears, and on sliding and rolling surfaces. Usage includes equipment such as: instruments, cameras, electronic gear, aircraft gears and control systems, actuator screws, and equipment recommended by the manufacturer that requires this lubricant.

2. SALIENT CHARACTERISTICS.

2.1 Design and construction. The portable unit shall be mounted on wheels or casters. The chassis shall provide mounting for the following: handle, lubricant container, automatic mechanical feed device, pressure pump, discharge hose, control valve, swivels, pressure switch, safety valve, hose and cord racks, electric motor and power supply cord. The handle height shall be 36 inches to 42 inches from the floor level when in the vertical position.

2.2 Dimensions and weight. The unit is mounted on an integral chassis and shall be approximately 39 inches in height, 20 inches in width, and 30 inches long. The unit without lubricant shall weight not more than 130 pounds.

2.3 Components and features. The grease container shall have a 30 to 40 pound capacity for lubricant with a discharge hose minimum length of 15 feet. The automatic pressure switch shall maintain discharge pressure between 4000 psig and 6000 psig. The safety valve shall bypass

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: The Technology and Industrial Services Division, SA-ALC/TILDD, 485 Quentin Roosevelt Rd., Bldg. 171, Kelly AFB, TX 78241-6524

AMSC N/A FSC 4930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.

grease back into the container to safeguard the lubricator when a pressure exceeding 6000 psig has been reached and shall activate a manual reset-type circuit breaker as back-up should the main pressure switch fail. The electric DC motor shall be 115 volts, minimum 1/3 horsepower, be permanent magnet brushless, and capable of accepting standard 115-120 volt, 60 Hz, single phase, electrical power input. The motor drive shall be capable of disengaging electrical power when the safety valve is activated and a manual reset button shall re-activate the motor. The motor shall trip off a breaker and shut down if overheated and automatically cutoff motor operation once the unit reaches maximum pressure. The power supply cord shall be a 3-conductor, Type S, heavy-duty, and a minimum length of 20 feet.

2.4 Performance specifications. The unit shall be capable of producing a discharge pressure of 4000 to 6000 psig at the discharge nozzle. The discharging grease shall conforming to MIL-G-23827 at 8 oz per min. (minimum) under free flow, 6 oz. per min., against 1000 psig back pressure at 70°F and 6 oz. per min. under free flow, 4 oz. per min. against 1000 psig back pressure of 0°F. The electrical circuits shall be capable of withstanding, without damage, the application of 1000 volts root mean square (rms), 60 Hz, AC, plus twice the normal operating voltage for not less than 1 minute, when applied between the frame and the current-carrying components.

2.5 Unit identification plate. The following information will be attached to the unit:

a. Manufacturer Name

b. Manufacturer CAGE Code

c. Manufacturer Model and Part Number

d. Contract Number

3. REGULATORY REQUIREMENTS.

3.1 Recycled, recovered, or environmentally preferable materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

3.2 Safety. All units shall comply with Federal OSHA and NFPA standards in effect at the time the proposal is issued.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producers' own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.

4.2 Market acceptability. All offerors shall submit descriptive literature to be considered for approval. Descriptive literature shall consist of the following:

a. Literature describing the lubricating unit and performance characteristics (catalogs, brochures, specification sheets).

b. Compete set of drawings for the lubricating unit.

c. Documentation showing that the same/similar unit has been sold to the Department of Defense. If identical production units have been sold to the Government, evidence to allow the Government to substantiate the safe, reliable performance and satisfactory quality of the production units must be submitted with the offeror's request for waiver consideration for bid sample testing. This evidence shall include contract numbers, quantities sold, location of the procuring activity and names and telephone numbers of the contracting officer(s). The Government reserves the right to make a determination as to whether this condition has been met when it can be shown that the units are safe, reliable, and satisfactory in performance, materials, and quality of construction by making use of evidence submitted by the offeror as well as evidence available within official Government records.

d. Documentation showing the same/similar item has been sold commercially. If identical production units have been sold to commercial customers in sufficient quantities so as to demonstrate reliability of the units in their application, performance, safety and acceptance of the units by the commercial market through continued procurement and usage. This evidence must be submitted with the offeror's request for waiver consideration for bid sample testing. The evidence shall include: customer names, addresses, dates of contract, quantity sold to each customer, and contact's telephone numbers.

e. Identification of differences between the lubricating unit being considered for approval and the Government commercial item description.

f. Description of quality program.

g. Copy of the warranty will be provided.

4.3 Bid sample. Descriptive literature will be evaluated by engineering for a period not exceeding 14 days. If the descriptive literature provided is not satisfactory, offerors shall submit bid samples. The contractor shall furnish continuous maintenance support (parts and labor) during the evaluation testing. One bid sample shall be submitted for testing by the Government for an evaluation period of 14 to 30 days. Bid sample testing shall be conducted at the following location:

433rd AGS/Building 826
216 Galaxy Rd.
Kelly AFB, TX 78241
Telephone No. (210) 926-6166

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.

5. PACKAGING.

5.1 Preservation, packaging, and marking. Preservation, packaging, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents. Copies of the Military Specification may be obtained from the Standardization Document Order Desk, 700 Robins Avenue, Building 4D, Philadelphia, PA 19111-5094.

6.2 Ordering data.

a. CID Title, Number, and Date of this CID

b. Packaging requirements (see 5.1)

MILITARY INTERESTS:

CUSTODIAN:
Air Force - 99
DLA - CC

CIVIL AGENCY and
COODINATING ACTIVITY

GSA-FSS

PREPARING ACTIVITY:
Air Force - 82

AGENT:
Air Force - 99

(Project Number 4930-0029)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:13Z
Check the source to verify that this is the current version before use.