MILITARY SPECIFICATION
EMITTER, INTEGRATED EXPENDABLE AN/DPT-2

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. The emitter covered by this specification is for airborne use and shall function to simulate radar transmissions.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-W-5088	Wiring, Aerospace Vehicle
MIL-E-5400	Electronic Equipment, Airborne, General Specification for
MIL-T-5422	Testing, Environmental, Aircraft Electronic Equipment
MIL-E-17555	Electronic and Electrical Equipment, Accessories and Repair Parts; Packaging and Packing of
MIL-T-18303	Test Procedures; Preproduction, Acceptance, and Life for Aircraft Electronic Equipment, Format for
MIL-N-18307	Nomenclature and Identification for Electronics, Aeronautical and Aeronautical Support Equipment Including Ground Support Equipment

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Engineering Specifications and Standards Department (Code 93), Naval Air Engineering Center, Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-461	Electromagnetic Interference Characteristics, Requirements for Equipment
MIL-STD-704	Aircraft Electric Power Characteristics
MIL-STD-781	Reliability Design and Production Acceptance Tests: Exponential Distribution
MIL-STD-785	Reliability Program for Systems and Equipments Development and Production
MIL-STD-794	Parts and Equipment, Procedures for Packaging and Packing of
MIL-STD-810	Environmental Test Methods
MIL-STD-965	Parts Control Program
MIL-STD-1311	Test Methods for Electron Tubes
MIL-STD-2074	Failure Classification for Reliability Testing

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.3), the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.4)

3.2 Parts, materials, and processes. In the selection of parts and materials, fulfillment of major design objectives shall be the prime consideration. In so doing, the following shall govern:

a. Microelectronic technology shall be considered and microelectronic items shall be in accordance with the requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

b. Other parts and materials requirements shall be in accordance with MIL-E-5400.

c. When previously produced models of this emitter did not use nonrepairable subassemblies, the design shall not be changed to employ nonrepairable assemblies without written approval from the procuring activity.

3.2.1 Nonstandard parts and materials approval. Approval for the use of nonstandard parts and materials (including electron tubes, transistors and diodes) other than microelectronic devices shall be in accordance with MIL-E-5400. Approval for microelectronic devices shall be in accordance with MIL-STD-965.

3.2.2 Microelectronic modular assemblies. When used, microelectronic modular assemblies shall meet the requirements of MIL-STD-965.

3.2.3 Modules. Conformal coatings, encapsulants, embedments or potting materials used with modular assemblies containing integrated circuits and discrete parts shall be easily removable without damage to the assembly.

3.3 General design and construction. Unless otherwise specified herein, the emitter shall be in accordance with all applicable design, construction, and workmanship requirements of MIL-E-5400.

3.3.1 Total weight. The total weight of the emitter, excluding cables, shall be a minimum consistent with good design and shall not be greater than 18 pounds (8.18 kg).

3.3.2 Reliability program. The contractor shall conduct a reliability program in accordance with MIL-STD-785. On a reorder from a supplier who is producing the emitter, the program previously approved may be continued unless otherwise specified in the contract or order.

3.3.2.1 Operational stability. The emitter shall operate with satisfactory performance, continuously or intermittently, for a period of at least 30 hours without the necessity for readjustment of any controls which are inaccessible to the operator during normal use.

3.3.2.2 Operating life. The emitter shall have a minimum total operating life of 100 hours with reasonable servicing and replacement of parts. Parts requiring scheduled replacement shall be identified by the contractor.

3.3.2.3 Reliability. The emitter, including any Built-in-Test (BIT) provisions, shall have a lower test MTBF (θ_L) of 30 hours with 80 percent confidence when tested and accepted as specified in 4.5.2.

3.3.2.4 Storage service life. At any time within, or immediately following an 18 month storage period, under any combination of environments specified herein, the emitter shall be capable of meeting all the requirements of this specification without component or part replacement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

3.3.3 Cabling and connections.

3.3.3.1 Cables and connectors. The emitter shall provide for the use of wiring and connectors in accordance with MIL-E-5400.

3.3.3.2 Interconnection cabling. The emitter shall be capable of satisfactory operation using external wiring in accordance with the applicable requirements of MIL-W-5088. Such external wiring shall be unshielded, except that a minimum number of the individual wires may be shielded when demonstrated as necessary to meet interference control requirements.

3.3.4 Interchangeability. The emitter shall meet the interchangeability requirements of MIL-E-5400.

3.3.5 Interference control. The generation of radio interference by the emitter and the vulnerability of the emitter to radio interference shall meet the requirements of MIL-STD-461 for class IB equipment.

3.3.6 Maintainability. The maintainability program, built-in test features, construction and packaging, provisions for test points, and other maintainability parameters shall be in accordance with MIL-STD-454.

3.3.7 Nomenclature, nameplates and identification marking. Nomenclature, serial number assignment, nameplate approval and identification marking shall be in accordance with MIL-N-18307.

3.3.8 Standard conditions. The following conditions shall be used to establish normal performance characteristics under standard conditions and for making laboratory bench tests.

a.	Temperature	Room ambient (25 $\pm$ 5)^{o}C
b.	Altitude	Normal ground
c.	Vibration	None
d.	Humidity	Room ambient up to 90 percent relative humidity
e.	Input voltage	+ 28 $\pm$ 0.5 Vdc

3.3.9 Service conditions. The emitter shall operate satisfactorily under any of the environmental service conditions or combination of these conditions as specified herein.

3.3.9.1 Vibration. The emitter shall operate satisfactorily when subjected to a 10G sinusoidal vibration.

3.3.9.2 Temperature. The emitter shall operate satisfactorily over the temperature range of -40°C to +71°C after nonoperational storage at temperatures of -62°C and +95°C.

3.3.9.3 Altitude. The emitter shall operate satisfactorily at altitudes up to and including 40,000 feet (12,192 meter (m)).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

3.3.9.4 Shock. The emitter shall operate satisfactorily after 20G, 11 millisecond shocks.

3.3.9.5 Degree of enclosure. The enclosure of the emitter including associated waveguide shall be watertight and the exterior surfaces shall show no signs of corrosion after immersion in sea water.

3.3.10 Primary input power. The emitter shall be designed to meet all applicable requirements of MIL-STD-704 and shall give specified performance from the following power sources with characteristics as defined in MIL-STD-704 having limits as defined therein. The power required shall not be greater than the specified amount.

a. DC power, +28V ± 10 percent, 7.0 A.

3.3.10.1 Degraded performance. Degraded performance is permissible for all voltage transients from 50 microseconds to 0.5 second duration in accordance with MIL-STD-704 for normal electric system operation. Operation shall return to normal within 5.0 seconds after the 50 microsecond to 0.5 second transient expires.

3.3.11 Overload protection. Overload protection for the emitter shall be provided in the emitter. All parts and circuits of the emitter which are likely to carry an overload due to any failures or poor adjustments shall be proportioned to withstand such overload without permanent damage to the emitter or shall have suitable protective devices. The use of fuses and other manually resettable protective devices shall not be allowed.

3.3.11.1 Undervoltage protection. The emitter shall not be damaged by voltages below the minimum specified herein and shall automatically resume normal operation within 5.0 seconds after the voltage returns within limits.

3.3.11.2 Polarity protection. The emitter shall operate from a +28 ± 2.8 Vdc power source and reverse polarity protection shall be provided.

3.3.12 Standby condition. The emitter shall be designed so the application of primary input power provides a standby condition whereby rated voltage shall be applied to all tube filaments and circuits requiring a warm-up period. Except for the associated filament circuits, voltages shall not be applied to other parts of the emitter.

3.3.13 Warm-up time. The maximum warm-up time for the emitter shall not be greater than 5 minutes under standard and extreme service conditions.

3.3.14 Cooling. Except as specified herein, the design for cooling the emitter shall be in accordance with MIL-E-5400.

3.3.14.1 Natural cooling. Natural cooling in accordance with the thermal design requirements of MIL-STD-454 is preferred; however, other cooling methods may be used.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:50Z
Check the source to verify that this is the current version before use.

3.3.14.2 Other cooling. If other cooling methods are used, such as forced air, liquids, refrigerants, etc., these methods and associated application devices shall be considered as an integral part of the emitter furnished under contract and the use thereof shall comply with all of the requirements specified herein for the emitter including form factor, weight, and mounting.

3.4 Performance. Unless otherwise specified, values set forth to establish the requirements for satisfactory performance apply to performance under both standard and extreme service conditions. When reduced performance under the extreme conditions is acceptable, tolerances or values setting forth acceptable variations from the performance under the standard conditions will be specified.

3.4.1 Operation. The emitter shall operate by transmitting radio signals at the frequency, power, modulation, and accuracy specified herein to simulate radar transmissions.

3.4.2 Output frequency. The output frequency shall be 9.375 GHz ± 0.100 GHz.

3.4.2.1 Stability. The output frequency shall be stable to within ± 0.1 percent.

3.4.2.2 Side lobes. Transmitter frequency side lobes shall be 8 dB minimum below the set output frequency.

3.4.3 Power output. RF peak power output shall be 20 kilowatts, minimum.

3.4.4 Modulation characteristics.

3.4.4.1 Pulse recurrence frequency (PRF). The PRF shall be continuously adjustable manually to any one PRF setting ± 5.0 Hz over the range of from 400 Hz to 1400 Hz.

3.4.4.1.1 Stability. PRF stability shall be ± 2.0 percent of the set PRF.

3.4.4.2 Pulse shape. Unless otherwise specified herein, the detected RF output pulse shape shall conform with the requirements for pulse characteristics of MIL-STD-1311.

3.4.4.2.1 Pulse width. The pulse width shall be 0.8 microsecond ± 0.1 microsecond.

3.4.4.2.2 Pulse rise and fall time. Pulse rise time shall be 100.0 nanoseconds maximum. Pulse fall time shall be 300.0 nanoseconds maximum.

3.4.4.3 Duty cycle. The emitter shall withstand without damage or degradation of performance a duty cycle of 0.00125 minimum.

3.4.4.3.1 Duty cycle warning. The exterior surface of the emitter shall be permanently and legibly marked as appropriate with a warning, advising the user not to exceed a combination setting of pulse width-pulse recurrence frequency

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

equal to or greater than the duty cycle capability of the magnetron tubes used. The warning shall be stated in quantitative terms of pulse width and pulse recurrence frequency and shall be affixed to the emitter in a conspicuous location.

3.4.5 Control inputs. The emitter shall have electrical inputs for remote control of the following modes of operation:

a. STANDBY - (see 3.3.12)

b. ON - Fully operational

3.4.5.1 Remote control. Remote control operation shall be accomplished by the application of an externally generated +28 Vdc ± 10 percent control voltage to the emitter. The maximum current shall be 0.250 A.

3.5 Detail design requirements.

3.5.1 Function. The emitter shall function, when energized by an external ± 28 Vdc ± 10 percent control voltage, by internally generating a pulse-modulated radio frequency signal at the power specified herein.

3.5.2 Form factor. The dimensions (HXWXD) of the emitter including mounting shall be 8.00 x 5.00 x 13.7 inches (20.32 x 12.70 x 34.80 centimeters). This defines the maximum volume available for the design of emitter form factor and the location for inputs, outputs, adjustments and mounting.

3.5.3 Weight. The weight of the emitter shall not be greater than 18.0 pounds (8.18 kg).

3.5.4 Controls. The controls shall be easily accessible and shall be appropriately marked for identification on the exterior surface of the emitter.

3.5.5 Electrical connections. The emitter shall utilize one receptacle for primary input power and remote control. A waveguide port shall be provided for E-plane horizontal polarization transmission of the specified RF power.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified herein, all inspections shall be performed in accordance with the test conditions specified herein. Inspections to demonstrate compliance with the requirements of MIL-E-5400 shall use the procedures of MIL-T-5422.

4.4 First article inspections. First article inspections, when required, (see 3.1) shall be conducted by the contractor on an emitter representative of the production emitters to be supplied under the contract. The Government inspector and the procuring activity shall be advised 10 days in advance of when inspections are to be conducted so that a Government representative may be designated to witness or supervise the inspections when so desired.

4.4.1 First article inspection procedures. First article inspection procedures shall be prepared as specified in 4.6.

4.4.2 First article inspection report. The contractor shall prepare a first article inspection report containing all the data collected in conducting these inspections (see 6.2).

4.4.3 Scope of inspections. First article inspections shall include all tests deemed necessary by the procuring activity to determine that the emitter meets all the requirements of this specification, other applicable specifications and the contract.

4.4.3.1 Vibration test. The emitter shall operate satisfactorily when subjected to the 10G, 5-500Hz sinusoidal vibration requirement as specified in MIL-STD-810, method 514.2, category e, procedure V, part 1, figure 514.2-5, curve Q. Sinusoidal cycling test time shall be 3 hours per axis (less dwell time).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

energy

4.4.3.2 Temperature/altitude tests. The emitter shall operate satisfactorily when subjected to the temperature/altitude test of MIL-T-5422 for class 2 equipment as modified below:

a. Test altitude for step 3, 9, 10 and step 11 shall be 40,000 feet (12,192 m).

b. Test temperature for steps 2 and 3 shall be -40°C.

c. Test time for steps 6, 9, and 11 shall be 2 hours minimum.

d. Step 7 and step 12 shall be omitted.

4.4.3.3 Shock. The emitter shall operate satisfactorily when subjected to the shock requirements of MIL-T-5422 except that the shock level shall be 20G for the basic design test.

4.4.3.4 Enclosure test. The emitter shall be tested for compliance with the water-tight requirement of 3.3.9.5 in accordance with the leakage test of MIL-STD-810, method 512, procedure I, as modified herein. The emitter shall be preconditioned at the temperature specified in MIL-STD-810 and a pressure of 5.6 inches (142.24 mm) of mercury (40,000 feet, 12,142 m altitude) for a minimum of two hours. After this period the pressure shall be returned to normal atmospheric at a rate of 1200 feet (365.76 m) per minute (minimum) and the emitter immediately (within one minute) immersed in a 5 percent sodium chloride and distilled water solution, to the depth specified in MIL-STD-810 for a minimum of 12 hours. Within 30 minutes after ending the immersion period, the emitter shall be rinsed with tap water, wiped dry, checked for satisfactory operation and the interior examined for evidence of leakage. The emitter shall then be stored nonoperating under standard conditions for 72 hours. At the end of the 72 hour storage period, the emitter shall be examined for evidence of corrosion and checked for satisfactory operation.

4.4.3.5 Electromagnetic interference test. The emitter shall be subjected to the test requirements and shall be in accordance with the limits of MIL-STD-461 for class IB equipment.

4.4.4 First article approval. Written approval of the first article (see 6.3) shall be by the procuring activity upon satisfactory completion of all inspections. No production emitters shall be delivered prior to the approval of the first article. Prefabrication of production emitters prior to the approval of the first article is at the contractor's own risk. The approved first article shall be retained by the contractor for his use in the fabrication and testing of emitters to be submitted for acceptance. The first article shall not be considered as one of the emitters under the contract.

4.4.5 Production emitters. Emitters supplied under the contract shall in all respects, including design, construction, workmanship, performance and quality, be equivalent to the approved first article. Each emitter shall be capable of successfully passing the same tests as imposed on the first article. Evidence of noncompliance with the above shall constitute cause for rejection, and, for emitters already accepted by the Government, it shall be the obligation of the contractor to make necessary corrections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection. The contractor shall furnish all samples and shall be responsible for accomplishing the quality conformance inspections. All inspection and testing shall be subject to monitoring by the Government inspector. The contractor shall prepare test reports showing quantitative results for all quality conformance inspections. Such reports shall be signed by an authorized representative of the contractor. Acceptance or approval of material during the course of manufacture shall not be construed as a guarantee of the acceptance of the finished product. Quality conformance inspections shall consist of the following:

a. Individual tests

b. Reliability assurance tests

c. Special tests

4.5.1 Individual tests. Each emitter submitted for acceptance shall be subjected to the individual tests. These tests shall demonstrate compliance with the requirements of material, workmanship, operational adequacy and reliability. As a minimum, each emitter accepted shall have passed the following tests:

a. Examination of product

b. Operational test

4.5.1.1 Examination of product. Each emitter shall be examined carefully to determine that the material and workmanship requirements have been met.

4.5.1.2 Operational test. Each emitter shall be operated long enough to permit the emitter temperature to stabilize and to check sufficient characteristics and adequate data to assure satisfactory emitter operation.

4.5.2 Reliability assurance tests. Reliability assurance tests shall be conducted in accordance with MIL-STD-781. Reliability assurance tests shall include the reliability qualification test and the all equipment test. Classification of failures shall be in accordance with MIL-STD-781 and MIL-STD-2074.

4.5.2.1 Reliability qualification test. Prior to the acceptance of emitters under contract or order, a minimum of three (3) emitters shall be tested as outlined in MIL-STD-781. Test plan XIC shall be used with the lower test MTBF equal to 30 hours. Current values of demonstrated MTBF ($\bar{\theta}$) shall be determined using the 60 percent confidence interval and reported as defined in MIL-STD-781.

4.5.2.1.1 Test details. The test details such as the length of the test cycle, the length of the heat portion of the cycle, the performance characteristics to be measured, special failure criteria, preventive maintenace to be allowed during the test, etc., shall be part of the test procedures to be prepared prior to the beginning of the qualification test.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:50Z
Check the source to verify that this is the current version before use.

4.5.2.1.2 Qualification test report. The contractor shall prepare a test report containing all data collected in conducting the qualification test.

4.5.2.2 All equipment test. Each emitter produced, except those submitted for the reliability qualification test, shall be tested for 3 operating hours. Prior to the 3 hour test on each emitter, if a burn-in period is to be used, the details thereof must be included in the approved test procedures. To determine whether the MTBF is being met at any time during the contract, the operating test hours and the failures thereon (not counting burn-in failures or burn-in operating time) shall be totaled and the results compared with the reject line of figure C-11 of MIL-STD-781. These totals shall accumulate so that at any one time the experience from the beginning of the contract is included. At any time that the current totals of test hours and test failures plotted on figure C-11 curves show a reject situation, the procuring activity shall be notified immediately. The procuring activity reserves the right to stop the acceptance of emitters at any time that a reject situation exists pending a review of the contractor's efforts to improve the emitter, the emitter parts, the emitter workmanship, etc., so that the entire compilation will show other than a reject decision.

4.5.2.2.1 All equipment test details. The test details shall be as defined in 4.5.2.1.1 herein.

4.5.2.2.2 All equipment test data. The contractor shall prepare a test report containing all data collected in conducting the all equipment test.

4.5.3 Special tests. Special tests shall be conducted as required by the procuring activity for the purpose of checking the effect of any design or material change on the performance of the emitter and to assure adequate quality control. The emitters selected for special tests may be selected from emitters previously subjected to the reliability assurance tests.

4.5.3.1 Special test schedule. Selection of emitters for special tests shall be made as follows:

a. On an early emitter after an engineering or material change.

b. Whenever failure reports or other information indicate that additional tests are required. (This will be determined by the procuring activity).

4.5.3.2 Scope of tests. Special tests shall consist of such tests as required by the procuring activity. Test procedures previously approved for the preproduction tests shall be used where applicable. When not applicable, the contractor shall prepare a test procedure prior to conducting the tests.

4.5.4 Emitter failure. Should a failure occur during either the reliability assurance or the special tests, the following action shall be taken:

a. Determine the cause of failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

b. Determine if the failure is due to a material defect or a design defect.

c. Prepare a corrective action plan.

d. Where practical, include a test in the individual test to check all emitters for this requirement until reasonable assurance is obtained that the defect has been satisfactorily corrected.

4.6 Test procedures. The procedures used for conducting first article and quality conformance inspections shall be prepared by the contractor. The right is reserved by the procuring activity to modify the tests or require any additional tests deemed necessary to determine compliance with the requirements of this specification or the contract. MIL-T-18303 shall be used for preparation of test procedures. When approved test procedures are available from previous contracts, such procedures will be provided by the procuring activity and may be used. However, the right is reserved by the procuring activity to require modification of such procedures, including additional tests, when deemed necessary.

4.7 Reconditioning of tested emitters. Emitters which have been subjected to quality conformance inspections shall be reconditioned by the contractor by replacing all limited life or damaged items. After reworking the contractor shall resubmit the emitter for acceptance. Rework is not required after successful completion of such acceptance tests as are performed on each emitter.

4.8 Presubmission testing. No item, part or complete emitter, shall be submitted by the contractor until it has been previously tested and inspected by the contractor and found to comply with the applicable requirements.

4.9 Rejection and retest. Emitters which has been rejected may be reworked or have parts replaced to correct the defects and be resubmitted for acceptance. Before resubmitting, perform analysis of rejection and assure that positive action is taken to eliminate the cause of defect.

5. PACKAGING

5.1 General. All major units and parts of the equipment shall be preserved, packaged, packed, and marked for the level of shipment specified in the contract or order in accordance with MIL-E-17555 and MIL-STD-794. In the event the equipment is not covered in MIL-E-17555, the method of preservation for level A shall be determined in accordance with the selection chart in appendix D of MIL-STD-794.

6. NOTES

6.1 Intended use. The emitter shall be designed for use in Naval drone and manned aircraft and shall simulate radar transmissions.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:50Z
Check the source to verify that this is the currentversion before use.

6.2 Ordering data.

6.2.1 Procurement requirements. Procurement documents should specify:

a. Title, number, and date of this specification.

b. Which magnetrons, if any, are to be procured.

c. Procedure I or II for the parts control program of MIL-STD-965.

d. Level of packing required.

6.2.2 Data requirements. When this specification is used in a procurement which incorporates a DD Form 1423 and invokes the provisions of 7-104.9(n) of the Armed Services Procurement Regulations, the data requirements identified below will be developed as specified by an approved Date Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of ASPR-7-104.9(n) are not invoked, the data specified below will be delivered by the contractor in accordance with the contract requirements. Deliverable data required by this specification are cited in the following paragraphs:

Paragraph	Data requirement	Applicable DID
3.2.1	Nonstandard Part Approval Requests/Proposed Additions to an Approved PPSL	DI-E-7028
3.3.2	Plan, Reliability Program	DI-R-2113
3.3.7	Requests, Nomenclature and Identification Assignment and Approval	UDI-E-21336A
4.4.1	Procedures, Test	UDI-T-21347
4.4.2	Report, First Article (Preproduction) Test	UDI-T-21349
4.5.2.1.1 4.5.2.2.1	Procedures, Reliability Tests	DI-R-7035
4.5.2.1.2 4.5.2.2.2	Reports, Reliability Test and Demonstration	DI-R-7034
4.5.4	Plan, Corrective Action	DI-R-7038

(Copies of data item descriptions required by the contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article is required, it shall be tested and approved under the appropriate provisions of 7-104.55 of the Armed Services Procurement Regulation. The first article should be (a preproduction sample), (a first production item) (a sample selected from the first ___production items) (or it may be a standard production item from the contractor's current inventory as specified in 4.4). The first article should consist of (one), (two), etc. unit(s). The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, test and approval of the first article.

6.4 Test values. Normal and limiting values of performance data shall be determined at input voltages of +28 ± 2.8 Vdc. These voltage values are to be used in testing the emitter at installation points for compliance with minimum acceptance standards of performance.

6.5 Precedence of documents. When the requirements of the contract, this specification, or appicable subsidiary specifications are in conflict, the following precedence shall apply:

a. Contract. The contract shall have precedence over any specification.

b. This specification. This specification shall have precedence over all applicable subsidiary specifications.

c. Referenced specifications. Any referenced specification shall have precedence over all applicable subsidiary specifications referenced therein. All referenced specifications shall apply to the extent specified.

6.6 Type designations. The type designation may be modified by the procuring activity upon application by the contractor for assignment of nomenclature in accordance with 3.3.7. The correct type number shall be used on nameplates, shipping records and instruction books, as applicable.

Preparing activity:
Navy-AS

(Project 5841-N011)

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:50Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commanding Officer
Naval Air Engineering Center
Engineering Specifications and Standards Department
(ESSD) Code 93
Lakehurst, NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:50Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE: MIL-E-85380(AS) EMITTER, INTEGRATED EXPENDABLE AN/DPT-2

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:50Z
Check the source to verify that this is the current version before use.