MIL-C-12520/5A(EL)
5 November 1965
SUPERSEDES
MIL-C-12520/5
3 June 1959

MILITARY SPECIFICATION

CONNECTORS, PLUG, ELECTRICAL, WATERPROOF (ROUND SHAPE, SHELL SIZE 20, FEMALE INSERTS)

1. SCOPE

1.1 Scope.- This specification covers the detail requirements for the following types of field-serviceable, shell-size 20, round-shape, waterproof, electrical-plug connectors with female inserts:

UW1220FA11	UW1220FB17
UW1220FA13	UW1220FB19
UW1220FA15	UW1220FB21
UW1220FA17	UW1220FB23

1.2 Ratings.- Connectors covered by this specification shall have the electrical ratings specified in table 1.

Table 1 - Electrical ratings

	Limiting operating voltage (sea level)		Nominal current
Connector type	AC	DC	Amperes
UW1220FA11 to UW1220FA17, incl	900	1,250	41
UW1220FB17 to UW1220FB23, incl	900	1,250	22

2. APPLICABLE DOCUMENTS

2.1 The following specifications, of the issue in effect on date of invitation for bids, form a part of this specification:

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:55Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-C-12520	Connectors, Plug and Receptacle (Electrical, Waterproof; and Accessories; General Specification for.
MIL-C-12520/8A	Connectors, Receptacle, Electrical, Waterproof (Shell Size 20, Male Inserts).

(Copies of specifications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements.- Requirements shall be in accordance with Specification MIL-C-12520, and as specified herein.

3.2 Design and construction.- Connectors shall be of the design, construction, and physical dimensions specified on figure 1.

3.2.1 Assembly.- Connectors shall be capable of being disassembled to allow access to the contact terminals without the use of special tools.

3.3 Voltage drop.- The voltage drop shall not exceed 20 millivolts for insert-arrangement A, and 21 millivolts for insert-arrangement B. (See 4.4).

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection.- Sampling and inspection shall be in accordance with Specification MIL-C-12520, and as specified herein.

4.2 Test and mating receptacles.- The test and mating receptacles shall be in accordance with the applicable type covered by Specification MIL-C-12520/8A.


4.3 Dielectric withstanding voltage.- Connectors shall be subjected to a test potential of 2,800 volts root mean square (rms).

4.4 Voltage drop (see 3.3).- The test current for connectors shall be 35 amperes dc for insert-arrangement A, and 20 amperes dc for insert-arrangement B.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with Specification MIL-C-12520.

Source: https://assist.dla.mil -- Downloaded: 202640-17T22:55Z
Check the source to verify that this is the currentversion before use.



1. All dimensions in inches.
2. Unless otherwise specified, tolerances are ± [illegible] on fractions and ± 2° on angles.

FIGURE 1. *Plug shell and female insert dimensions*

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:55Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Notes.- In addition to the notes specified herein, the notes specified in Specification MIL-C-12520 are applicable to this specification.

6.2 Intended use.- Connectors covered by this specification are intended for use where field-serviceable, waterproof, electrical connectors are required.

6.2.1 Mating receptacle connectors.- Mating receptacle connectors are in accordance with Specification MIL-C-12520/8A.

6.2.2 Cover and chain assemblies.- Cover and chain assemblies are in accordance with style N3 of Specification MIL-C-12520/13A"Cover and Chain Assemblies (Internal Threads, for Use on Waterproof Connectors)".

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

CUSTODIAN

EL

Preparing activity

EL

Project Nr. 5935-A137

Source: https://assist.dla.mil -- Downloaded: 20261O-17T22:55Z
Check the source to verify that this is the current version before use.