MIL-C-12520/10A(EL)
5 November 1965
SUPERSEDES
MIL-C-12520/10
3 June 1959

MILITARY SPECIFICATION

CONNECTORS, RECEPTACLE, ELECTRICAL WATERPROOF (SHELL SIZE 26, MALE INSERTS)

1. SCOPE

1.1 Scope.- This specification covers the detail requirements for the following types of shell-size 26, waterproof, electrical-receptacle connectors with male inserts:

UW2026MC00
UW2026MD00
UW2026ME00
UW2026MF00
UW2026MG00

1.2 Ratings.- Connectors covered by this specification shall have the electrical ratings specified in table 1.

Table 1 - Electrical ratings

Connector type	Limiting operating voltage (sea level)		Nominal current
	AC	DC	Amperes
UW2026MC00	900	1,250	22
UW2026MD00	500	700	22
UW2026ME00	500	700	11
UW2026MF00	500	700	11
UW2026MG00	900	1,250	73

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:56Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

QQ-B-613	Brass, Leaded and Non-Leaded; Plate, Rolled Bar, Sheet and Strip.
QQ-P-416	Plating, Cadmium (Electrodeposited).

MILITARY

MIL-C-12520	Connectors, Plug and Receptacle (Electrical, Waterproof); and Accessories; General Specification for.
MIL-C-12520/3A	Connectors, Plug, Electrical, Waterproof (Cathedral Shape, Shell Size 26, Female Inserts).

(Copies of specifications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements.- Requirements shall be in accordance with Specification MIL-C-12520, and as specified herein.

3.2 Design and construction.- Connectors shall be of the design, construction, and physical dimensions specified on figure 1.

3.2.1 Mounting nut.- The mounting nut shall be of the dimensions specified on figure 2. Material shall be brass conforming to Specification QQ-B-613, and shall be cadmium plated conforming to class 1, type II, of Specification QQ-P-416. The resulting finish shall be olive drab in color.


3.3 Marking.- Marking shall be in accordance with Specification MIL-C-12520, except that connectors shall be marked with letters approximately 1/8 inch high.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection.- Sampling and inspection shall be in accordance with Specification MIL-C-12520, and as specified herein.


4.2 Test and mating plugs.- The test and mating plugs shall be in accordance with Specification MIL-C-12520/3A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:56Z
Check the source to verify that this is the current version before use.



1. All dimensions in inches.
2. Unless otherwise specified, tolerances are ± 1/64 on fractions, ± .005 on decimals, and ± 2° on angles.

FIGURE 1. *Receptacle shell and insert dimensions*



1. All dimensions in inches.
2. Unless otherwise specified, tolerances are ± 1/64 on fractions and ± .005 on decimals.

FIGURE 2. *Mounting nut dimensions*

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:56Z
Check the source to verify that this is the current version before use.

4.3 Dielectric withstanding voltage.- Connectors with insert-arrangements C and G shall be subjected to a test potential of 2,800 volts root mean square (rms). Connectors with insert-arrangements D, E, and F shall be subjected to a test potential of 2,800 volts.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with Specification MIL-C-12520.

6. NOTES

6.1 Notes.- In addition to the notes specified herein, the notes specified in Specification MIL-C-12520 are applicable to this specification.

6.2 Mating plug connectors.- Mating plug connectors are in accordance with Specification MIL-C-12520/3A.

6.2.1 Cover and chain assemblies.- Cover and chain assemblies are in accordance with style LN of Specification MIL-C-12520/13A"Cover and Chain Assemblies (Internal Threads, for Use on Waterproof Connectors".

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

CUSTODIAN

EL

Preparing activity

EL

Project Nr. 5935-A142

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:56Z
Check the source to verify that this is the current version before use.