

NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

NOTE.—This drawing was approved by joint action of the Air Force and Navy Department as the Air Force-Navy standard for this product. This drawing supersedes all antecedent standard drawings for the procurement of aeronautical supplies, or for use in new design, not later than six months after the latest date of approval shown.





(1) (1)

AN PART NO.	THREAD A	THREAD B	C	D	E
AN3059-16	1-7/16-18 NEF-2B	1-3/4-18 NS -2	3/8	1.447	1.668
AN3059-20	1-3/4 -18 NS -2B	2 -18 NS -2	7/16	1.760	1.918
AN3059-24	2 -18 NS -2B	2-1/4-16 UN -2A	7/16	2.010	2.158
AN3059-28	2-1/4 -16 UN -2B	2-1/2-16 UN -2A	1/2	2.260	2.408
AN3059-32	2-1/2 -16 UN -2B	3 -16 UN -2A	9/16	2.510	2.908

(1) THREADS SHALL BE IN ACCORDANCE WITH SPECIFICATION MIL-S-7742.EXCEPT 1-3/4 NS-2B AND 2-18 NS-2B THREADS WHICH SHALL BE IN ACCORDANCE WITH AMERICAN STANDARD ASA B-1.

MATERIAL: ALUMINUM ALLOY, SPECIFICATION QQ-A-351, CONDITION T.

(1) FINISH: CADMIUM PLATE, SPECIFICATION QQ-P-416, TYPE II, CLASS C.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: FRACTIONS ±1/64, DECIMALS ±.005, ANGLES ±1/2°.

REMOVE ALL BURRS AND SHARP EDGES.

APPROVED 14 Feb 42 REVISED (1) 16 Apr 53

PROCUREMENT SPECIFICATION	AIR FORCE–NAVY AERONAUTICAL STANDARD	AN3059
NONE	(1) BUSHING - ELECTRICAL CONDUIT	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:18Z
Check the source to verify that this is the current version before use.