MILITARY SPECIFICATION

RADIO SET, PORTABLE, SEARCH AND RESCUE OPERATION AN/PRC-96( )

This specification is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification includes the performance requirements for a complete two-channel, portable radio communication set (transceiver), with accessories, which provides homing information and two-way communication between life rafts and searching ships and aircraft. The equipment described herein is intended for shipboard and life raft use and will be subject to sea water immersion.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-S-901	Shock Tests, H.I. (High Impact), Shipboard Machinery, Equipment And Systems, Requirements For
MIL-E-16400	Electronic, Interior Communication And Navigation Equipment, Naval Ship And Shore, General Specification For
MIL-E-17555	Electronic And Electrical Equipment, Accessories, And Repair Parts, Packaging And Packing Of

STANDARDS

FEDERAL

FED-STD-595	Color

MILITARY

MIL-STD-105	Sampling Procedures And Tables For Inspection By Attributes
MIL-STD-108	Definition Of And Basic Requirement For Enclosure For Electric And Electronic Equipment
MIL-STD-109	Quality Assurance Terms And Definitions

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Electronic Systems Command (ELEX-5043), Washington, D.C. 20360, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:46Z
Check the source to verify that this is the current version before use.

MIL-STD-167-1	Mechanical Vibration Of Shipboard Equipment (Type 1- Environmental And Type 1i- Internally Excited)
MIL-STD-454	Standard General Requirements For Electronic Equipment
MIL-STD-781	Reliability Design Qualification And Production Acceptance Tests: Exponential Distribution
MIL-STD-810	Environmental Test Methods
MIL-STD-965	Parts Control Program

DRAWINGS

Microfilm reel #28652	AN/PRC-96( )
Microfilm reel #28653	TS-3527/PRC-96

(Copies of specifications, standards, handbooks, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.3 and 6.3).

3.2 General.

3.2.1 Transceiver description and operation. The transceiver shall be a two-channel miniature solid state hand-held radio set which will provide radio distress signals for search and rescue (SAR).

3.2.2 Frequency characteristics. The transceiver shall provide voice, beacon, and modulated continuous wave (MCW) communications on two fixed tuned crystal-controlled radio frequency (RF) channels. One RF channel shall be tuned to 121.500 megahertz (MHz) and the other channel shall be tuned to 243.000 MHz.

3.2.3 Modes of operation. The transceiver shall provide the following modes of operation:

a. Power OFF
b. Voice. In this mode, the tranceiver shall provide two-way, simplex, amplitude modulated voice communications on either 121.5 or 243.0 MHz (RF frequency selectable by switch).
c. Beacon. In this mode, the transceiver shall provide one-way continuous transmission with automatic equal time sharing between 121.5 and 243.0 MHz. Each RF carrier shall be amplitude modulated with a tone sweeping downwards over the frequency range from 1000 to 300 hertz (Hz) at a rate of two to three sweeps per second.
d. Code MCW. In this mode, the transceiver shall provide two-way, simplex, amplitude modulated tone communications on either 121.5 or 243.0 MHz (RF frequency selectable by switch). A 1000-Hz tone shall be used to modulate the carrier when the push-to-modulate switch is depressed.

3.2.4 Equipment. As a minimum, the following equipment shall be supplied, unless otherwise specified in the contract:

a. Transceiver, including internal battery
b. Antenna
c. Carrying case
d. Two spare internal batteries
e. Tester

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:46Z
Check the source to verify that this is the current version before use.

3.2.5 Size and weight. Maximum dimensions of the transceiver (not including antenna) are 15.24 centimeters (cm) (6 inches (in)) in height, 5.08 cm (2 in) in depth, and 10.16 cm (4 in) in width. Maximum weight including battery and antenna is 1.361 kilograms (kg) (48 ounces).

3.2.6 Construction. The transceiver shall be constructed in accordance with the drawings in microfilm reel #28652.

3.2.6.1 Material. The material used in the construction of the transceiver and accessories shall be consistent with the performance specified herein and in accordance with the material requirements specified in MIL-E-16400.

3.2.7 Parts. Selection of parts for the transceiver and accessories shall be in accordance with the parts requirements specified in MIL-E-16400.

3.2.7.1 Parts control program. The parts control program shall be in accordance with MIL-STD-965, Procedure I.

3.2.8 Coating and treatments. The transceiver and accessories shall be protected in accordance with the coatings and treatments requirements listed in MIL-E-16400.

3.2.9 Transceiver enclosure. The transceiver shall be designed to conform to the watertight requirement specified in MIL-STD-108. The submergence test is required.

3.2.10 Environmental range. The transceiver shall operate, within the allowable degradation specified herein, over a temperature range from -28° Celsius (C) to +65° C and at any relative humidity up to 95 percent. Also, the transceiver shall not be damaged and shall operate without any degradation after being exposed for an eight-hour period in the non-operating condition at -62°C and at +75°C.

3.2.11 Salt fog. The transceiver and antenna and the tester shall conform to the salt fog requirements of MIL-E-16400.

3.2.12 Shock. The transceiver and accessories (see 3.3.4) shall be designed to conform to the requirements for Grade A, Class I, lightweight, Type A equipment as specified in MIL-S-901. In addition, the transceiver shall operate without any degradation of performance after 10 test drops from a height of 1.83 meters (m) (6 feet (ft)) to a 1.27 cm (0.50 (1/2) in) steel plate.

3.2.13 Vibration. The transceiver and accessories (see 3.3.4) shall be designed to conform to the vibration requirements for Type I equipment as specified in MIL-STD-167. All failures shall be judged as major failures.

3.2.14 Battery compartment. The transceiver shall have a waterproof battery compartment. The cap on the compartment shall be a hand-screw or twist-on type with the cap attached to the transceiver case with a nylon cord to prevent loss of the cap while the cap is removed.

3.2.15 Overload. The transmitter shall not be damaged under variable load conditions such as grounding, partial grounding, or disconnecting of the antenna during transmitter operation. Also, a strong input signal (five VRMS measured at the antenna input) shall not damage or cause the receiver to be inoperative. Minimum test time for each of the above conditions shall be five minutes.

3.2.16 Crystals. Frequency determining crystal units and crystal holders shall conform to Requirement 38 of MIL-STD-454.

3.2.17 Active circuits. All active circuits (regulators, amplifiers, oscillators, and so forth) in the transceiver shall be solid-state or integrated circuitry, or both.

Source: https://assist.dla.mil -- Downloaded: 202640-20T13:46Z
Check the source to verify that this is the currentversion before use.

3.2.18 Quantitative reliability requirements. The equipment shall have an upper test limit mean-time-between-failures (MTBF) (θ_0 as defined by MIL-STD-781) of 3000 hours and a lower test limit MTBF (θ_1, as defined by MIL-STD-781) of 1000 hours.

3.2.19 Equipment compatibility. The transceiver shall have a built-in-test (BIT) connector which mates with the tester specified in 3.3.4.4.

3.2.20 Maintainability. The equipment shall be designed and constructed to assure ease of maintenance, alignment, accessibility, and replacement of parts and modules of the equipment.

3.3 Specific requirements.

3.3.1 Controls. The transceiver shall have the following external controls:

a. Power ON/OFF switch (part of mode of operation selector)
b. RF channel selector
c. Mode of operation selector
d. Push-to-talk/tone modulate switch
e. Volume control

3.3.1.1 Instruction plate. An instruction plate containing complete operating instructions shall appear on the housing of the transceiver.

3.3.1.2 Marking. Control and instruction plate markings shall be permanent and legible. Control markings shall be sufficiently luminous for night operations.

3.3.2 Transmitter characteristics. Unless otherwise specified, the transmitter shall conform to all the requirements specified herein throughout the environmental range (see 3.2.10) and battery life (see 3.3.4.3.1).

3.3.2.1 RF power output. The unmodulated RF carrier power output shall be at least 200 milliwatts (mW) average power.

3.3.2.2 Carrier frequency stability. Each of the two RF carriers shall remain within ±0.001 percent of the assigned frequency.

3.3.2.3 RF harmonic output. All harmonic emmissions shall be attenuated at least 20 decibels (dB) below the unmodulated carrier level.

3.3.2.4 Audio frequency response and distortion. The audio frequency response shall not vary more than +2 dB or -5 dB from the reference audio level at 1000 Hz over the frequency range from 300 to 3000 Hz with an RF input of six microvolts (uv). Audio distortion at 90 percent modulation shall be less than 10 percent.

3.3.2.5 Hum and noise level. The residual hum and noise level shall be at least 35 dB below the reference level established in 3.3.2.4 from a 30 percent modulated RF carrier.

3.3.2.6 Modulation capability. The transceiver shall be capable of at least 90 percent amplitude modulation in each of the three modes of operation. In the voice mode, the input signal shall be 1000 Hz with a sound pressure level not greater than +100 dB referenced to 0.0002 dynes per square centimeter at the face of the microphone.

3.3.2.7 Sidetone. An audible sidetone shall be available to the operator in the beacon and MCW modes of operation.

3.3.3 Receiver characteristics. Unless otherwise specified, the receiver shall conform to all the requirements specified in 3.3.3.1 through 3.3.3.8 throughout the environmental range (see 3.2.10) and battery life (see 3.3.4.3.1).

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:46Z
Check the source to verify that this is the current version before use.

3.3.3.1 Sensitivity. With an input RF signal of 6 µv modulated 30 percent at 1000 Hz applied to the receiver antenna input, the audio output shall be at least 50 mW and the signal-plus-noise-to-noise ratio shall be greater than 10 dB.

3.3.3.2 Selectivity and spurious response. The receiver response to all frequencies shall be as follows:

Frequencies	Attenuation
f_c -20 Hz $\leq f_o \leq f_c$ +20 kHz	6 dB maximum
$f \geq f_c$ +70 kHz; $f \leq f_c$ -70 kHz	40 dB minimum

3.3.3.3 Audio output power and distortion. The audio output level shall be adjustable to a minimum of 100 mW. Audio distortion at 100 mW shall be less than 10 percent.

3.3.3.4 Audio frequency response. The audio frequency response shall not vary more than +2 dB or -5 dB from the reference audio level at 1000 Hz over the frequency range from 300 to 3000 Hz.

3.3.3.5 Residual hum and noise. The ratio of residual hum and noise to rated audio output (100 mW) shall be greater than 30 dB.

3.3.3.6 Squelch. A squelch circuit shall be provided. The receiver squelch shall be non-adjustable with the squelch circuit designed to unsquelch with an RF input signal of less than 4 µv.

3.3.3.7 Automatic gain control. The audio output of the receiver shall remain within 10 dB for signal input levels from 6 µv to 100 mv with a constant 90 percent modulation.

3.3.3.8 Frequency stability. The center of the passband shall not vary more than ± 0.001 percent from the reference frequency (121.5 or 243.0 MHz). The passband is the frequency range measured between the 6 dB selectivity frequencies.

3.3.4 Accessories.

3.3.4.1 Antenna. A removable antenna shall be provided. The antenna electrical length shall be a half wavelength at 121.5 MHz. An internal antenna matching network shall be provided to optimize RF power transfer from the transmitter to the antenna.

3.3.4.2 Carrying case. The carrying case shall be designed to contain the transceiver, antennas, two spare batteries, and one technical manual in separate compartments. The spare batteries and technical manual shall be individually packaged in a waterproof wrapper prior to insertion in the separate compartments. The carrying case shall be designed so that the case, including transceiver, batteries, and technical manual, will float in fresh water. The transceiver shall be fastened to the carrying case with a 1.83 m (6-foot) length of detachable line.

3.3.4.2.1 Carrying case color and marking. The case shall be a bright orange color in accordance with FED-STD-595, Color No. 22246, and shall have the following information marked on two outside surfaces with gothic type lettering 1.91 cm (0.75 (3/4) in) in height:

a. The title Emergency Lifeboat Radio
b. Applicable National stock number
c. Equipment nomenclature

3.3.4.3 Battery. The battery required to operate the equipment shall be a single lithium sulfur dioxide battery of a diameter not greater than that of a standard D size cell. After a minimum of three years of storage the battery shall be capable of complying with the requirements of 3.3.4.3.1. The battery shall incorporate safety devices to protect against internal over-pressures, overloads, and cell reversal effects. The battery shall be marked with the date of manufacture and the National stock number.

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:46Z
Check the source to verify that this is the current version before use.

3.3.4.3.1 Battery operating life. The battery (one unit) shall have the capacity, at 25°C, to provide a minimum of 24 hours of continuous operation in the following modes of operation:

a. *Beacon*
b. Voice: 50 percent transmit and 50 percent receive duty cycle at 90 percent modulation and 100 mW receive audio for a one-minute period.

At -10°C the operating life of the battery shall provide a minimum of 16 hours of operation. The battery shall be judged acceptable if the RF power output does not degrade more than 3 dB and the receiver sensitivity does not degrade more than 7 dB at the end of both of these specified operation periods.

3.3.4.4 Tester. A portable, self-contained GO/NO-GO tester shall be provided in the quantity of units specified (see 6.2). The tester shall check the modes of operation (see 3.2.3) and, as a minimum, shall test for compliance with the following equipment characteristics:

a. *RF power output (see 3.3.2.1)*
b. Carrier frequency stability (see 3.3.2.2)
c. Audio distortion (see 3.3.2.4)
d. Sensitivity (see 3.3.3.1)
e. Audio distortion (see 3.3.3.3)
f. Automatic gain control (see 3.3.3.7)

3.3.4.4.1 Construction. The tester shall be constructed in accordance with the drawings in microfilm reel #28653.

3.3.4.4.2 Environmental range. The tester shall operate without any degradation over a temperature range from 0°C to 50°C and at any relative humidity up to 95 percent.

3.4 Workmanship. All workmanship shall be in accordance with Requirement 9 of MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Government verification. All quality assurance operations performed by the contractor will be subject to Government verification at any time. Verification will consist of, but is not limited to, a) Surveillance of the operations to determine that practices, methods, and procedures of the written quality program are being properly applied, b) Government product inspection to measure quality of the product to be offered for acceptance, c) Government inspection of delivered products to assure compliance with all inspection requirements of this specification. Failure of the contractor to promptly correct deficiencies discovered by him or of which he is notified shall be cause for suspension of acceptance until corrective action has been taken or until conformance of the product to prescribed criteria has been demonstrated.

4.1.2 Quality assurance terms and definitions. Quality assurance terms used in this specification shall be as defined in MIL-STD-109.

Source: https://assist.dla.mil -- Downloaded: 20260-20T13:46Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)
   1. Production inspection (see 4.4.1)
   2. Production control inspection (see 4.4.2)
c. Reliability demonstration (see 4.5)
d. Inspection of preparation for delivery (see 4.6)

4.3 First article inspection. Unless otherwise specified (see 6.2), two transceivers with antennas and two testers (if applicable) shall be required for first article inspection. First article inspection shall consist of all examination and testing necessary to determine compliance with the requirements of this specification. First article inspection shall include the tests specified in 4.4.1 through 4.4.3 and the salt fog test of MIL-E-16400.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the following:

a. Production inspection
b. Production control inspection

4.4.1 Production inspection. Production inspection shall be made on every equipment offered for delivery. This inspection shall comprise such examination and testing as will prove the workmanship and reveal the omissions and errors of the production process such as functional and performance tests at a limited number of points in the required range, tests which detect deviations from design, tests of adjustments, and tests which detect hidden defects of material. Production inspection shall consist of the tests specified in 4.4.1.1.

4.4.1.1 Performance tests. Performance tests shall verify compliance with the following requirements:

a. Transceiver:
   1. Control functions (see 3.3.1)
b. Receiver function:
   1. Sensitivity (see 3.3.3.1)
   2. Selectivity (see 3.3.3.2)
   3. Audio output (see 3.3.3.3)
   4. Audio distortion (see 3.3.3.3)
   5. Residual hum and noise (see 3.3.3.5)
   6. Squelch (see 3.3.3.6)
   7. Automatic gain control (see 3.3.3.7)
   8. Frequency stability (see 3.3.3.8)
c. Transmitter function:
   1. RF output power (see 3.3.2.1)
   2. Carrier frequency stability (see 3.3.2.2)
   3. Audio frequency distortion (see 3.3.2.4)
   4. Hum and noise level (see 3.3.2.5)
   5. Modulation capability (see 3.3.2.6)
   6. Sidetone (see 3.3.2.7)
d. Tester:
   1. Characteristic measurements (see 3.3.4.4)

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:46Z
Check the source to verify that this is the current version before use.

4.4.1.2 Equipment conditioning. Equipment conditioning shall be as specified in 4.4.3.

4.4.2 Production control inspection. This inspection shall include the tests specified in 4.4.2.3, 4.4.2.4, and 4.4.2.5. Sampling shall conform to the procedures for special inspection levels of MIL-STD-105. The inspection level shall be S-3 for normal, tightened, and reduced inspection utilizing an acceptable quality level (AQL) of 6.5 percent. Production control inspection shall be performed on inspection lots that have passed production inspection (see 4.4.1). The equipment shall conform to the requirements of production control inspection prior to release for shipment.

4.4.2.1 Noncompliance. If a sample unit fails production control inspections, the contractor shall immediately investigate the cause of failure and shall report to the Government inspector the results thereof and details of the corrective action taken on the process and all units of products which were manufactured with the same conditions, materials, and processes. If the Government inspector does not consider that the corrective action will enable the product to conform to specified requirements, or if the contractor cannot determine the cause of failure, the matter shall be referred to the contracting officer.

4.4.2.2 Re-inspection of conforming sample units. Unless otherwise specified, sample units which have been subjected to and passed production control inspections, may be accepted on contract provided that they are resubjected to and pass production inspection after repair of all damage.

4.4.2.3 The following requirements shall be verified for production control:

a. RF harmonic output (see 3.3.2.3)
b. Audio frequency response (see 3.3.2.4)
c. Overload (see 3.2.15)
d. Audio frequency response (see 3.3.2.4)
e. Battery operating life (see 3.3.4.3.1)

4.4.2.4 Environmental inspection for transceiver. The following environmental tests shall be performed for production control on the transceiver. The test units shall conform to the requirements specified in 4.4.1.1 following these tests:

a. Humidity test of MIL-E-16400
b. Drop test consisting of 10 drops from height of 1.83 m (6 ft) onto 1.27 cm (0.50 (1/2) in) thick steel plate
c. Leakage test shall be in accordance with Test Method 512.1, Procedure 1, of MIL-STD-810 except that water temperature shall be $10^{o}C \pm 5^{o}C$ and the submergence depth shall be 1.83 m (6 ft).

4.4.2.5 Environmental inspection on tester. The following environmental tests shall be performed for production control on the tester equipment. The tested units shall conform to the requirements specified in 4.4.1.1 following these tests.

a. Temperature test of MIL-E-16400, Range 4, operating and non-operating. The hold time low temperature non-operating shall be eight hours instead of three days
b. Humidity test of MIL-E-16400

4.4.3 Equipment conditioning. As an integral part of production inspection, each deliverable equipment shall be subjected to the following environmental test cycle:

a. With the equipment non-operating, reduce the room temperature to $-28^{o}C \pm 2^{o}C$. Maintain this temperature until thermal stabilization occurs.
b. Energize the equipment and measure performance parameters to verify proper operation
c. With the equipment non-operating, increase the room temperature to $+65^{o}C \pm 5^{o}C$. Energize equipment and operate for 24 continuous hours at the high temperature. Vibration shall be applied at 1.0 g $\pm$ 10 percent for 10 minutes out of each operating hour.

Source: https://assist.dla.mil -- Downloaded: 202640-20T13:46Z
Check the source to verify that this is the currentversion before use.

d. Just prior to completion of the high temperature cycle, performance parameters shall be measured to verify proper equipment performance.
e. If failure should occur during any portion of this cycle, appropriate corrective action shall be implemented and the whole test cycle repeated until it is completed without failure.

4.5 Reliability demonstration. The reliability of the transceiver and tester shall be demonstrated to verify conformance to the requirements specified in 3.2.18.

4.5.1 Reliability qualification test. The reliability qualification test shall be performed in accordance with Test Plan XXIC of MIL-STD-781.

4.5.1.1 Reliability qualification test environment. The reliability qualification test shall be performed under the following environmental conditions:

a. Vibration. Sine sweep 4 Hz to 33 Hz to 4 Hz, 0.0508 cm (0.020 in) DA, 10 minutes up and down the spectrum, single axis.
b. Thermal stress. Cycle between 0°C and 50°C so that three hours of operation is accrued at 0°C and three hours of operation is accrued at 50°C during each cycle. The rate of change of temperature between 0°C and 50°C and between 50°C and 0°C shall be the maximum of which the chamber is capable.
c. Moisture. Moisture shall be injected into the chamber so that visible condensation takes place upon the equipment during cool-down.

4.5.1.2 Performance monitoring. Performance monitoring shall be performed at least once per 24-hour period and shall consist of the following:

a. Receiver sensitivity (see 3.3.3.1)
b. Audio output (see 3.3.3.3)
c. Receiver frequency stability (see 3.3.3.8)
d. RF power output (see 3.3.2.1)
e. Carrier frequency stability (see 3.3.2.2)
f. Audio frequency distortion (see 3.3.2.4)
g. Modulation capability (see 3.3.2.6)

4.5.1.3 Failure. Failure shall be any malfunction or parameter deviation that prevents the equipment from performing within the operational requirements specified herein. All failures shall be considered relevant unless determined by the procuring activity to be caused by a condition external to the equipment under test, which is not a test requirement and not encountered in service.

4.6 Inspection of preparation for delivery. Inspection of preparation for delivery shall be performed to verify conformance to the requirements of Section 5.

5. PACKAGING

(The preparation for delivery requirements specified herein apply only for direct Government procurements. Preparation for delivery requirements of referenced documents listed in Section 2 do not apply unless specifically stated in the contract or order. Preparation for delivery requirements for products procured by contractors shall be specified in the individual order.)

5.1 Preservation, packaging, packing, and marking. Unless otherwise specified, preparation for delivery shall be in accordance with the applicable levels of preservation, packaging, packing, and marking specified in MIL-E-17555 (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:46Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The equipment covered by this specification is intended for shipboard and life raft use.

6.2 Ordering data.

6.2.1 Procurement requirements. Procurement documents should specify the following:

a. Title, number, and date of this specification
b. Number of first article samples to be submitted if other than specified in 4.3
c. Quantity of tester units required (see 3.3.4.4)
d. Levels of preservation, packaging, packing, and marking required (see 5.1)

6.2.2 Data requirements. When this specification is used in a procurement which incorporates a DD Form 1423 and invokes the provisions of 7-104.9(n) of the Defense Acquisition Regulation (DAR), the data requirements identified herein will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data specified herein will be delivered by the contractor in accordance with the contract requirements. Deliverable data required by this specification are cited in the following paragraphs:

Paragraph	Data Requirements	Applicable DID
4.5	Plan, Reliability Program	DI-R-2113
4.5	Reports, Reliability Test and Demonstration	DI-R-7034
4.5	Procedures, Reliability Tests	DI-R-7035
4.4.2.1	Plan, Corrective Action	DI-R-7038
4.4.2.1	Report, Failed Item Analysis	DI-R-7039
4.4.3	Report, Burn-In Test	DI-R-7040
4.3	Report, First Article Inspection	UDI-R-22576
4.4.2	Test Procedures	UDI-T-22710

(Copies of data item descriptions required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

6.3 First article. When a first article is required it shall be tested and approved under the appropriate provisions of 7-104.55 of the Defense Acquisition Regulation (DAR). The first article should be first production items. The first article should consist of two units. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, tests, and approval of the first articles.

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Preparing activity:
NAVY-EC
(Project 5820-N721)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T13:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL K-25713A

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

☆ U.S. GOVERNMENT PRINTING OFFICE: 1972—714-853/3404 2-

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:46Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D.C. 20360

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316



COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D.C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-20T13:46Z
Check the source to verify that this is the current version before use.