MILITARY SPECIFICATION

BODY ASSEMBLY, TANK PERISCOPE: 10513620

This amendment forms a part of Military Specification MIL-B-60133(MU) dated 22 January 1965.

Paragraph 3.6: Delete last sentence and substitute: "The incident line of sight shall also emerge parallel to a plane, defined by the 2-inch-long shoulder (generated by the machining of the two pads) adjacent to Valve Assembly 8201751, within 45 minutes of arc."

Paragraph 3.7: Delete paragraph and substitute:

"3.7 Image tilt.- The image of a target line originally perpendicular to a plane, defined by the 2-inch-long shoulder (generated by the machining of the two pads) adjacent to Valve Assembly 8201751, shall emerge perpendicular to the same plane within 45 minutes of arc."

Paragraph 4.5.5: Delete paragraph and substitute:

"4.5.5 Light deviation.- This test shall be performed utilizing an auxiliary telescope, containing a horizontal and vertical reticle line, mounted on a supporting device. The device shall be capable of holding the telescope and body assembly in a position permitting an incident line of sight to be directed from a calibrated target in a collimator projector, through the body assembly to the auxiliary telescope. Utilize the vertical surface of the 2-inch shoulder adjacent to the valve assembly to centrally position the body assembly in the device with the machined top surfaces of the pads on the same plane with the line of sight through the telescope. The target pattern shall consist of a horizontal and vertical cross line with limit marks 45 minutes from the intersection of the cross line. Limit marks shall also be added in each quadrant, offset 45 minutes of arc from the horizontal cross line, to subsequently measure image tilt. The collimating projector shall be positioned in front of the body assembly with the center vertical line of the target in a plane parallel to a plumb line and on the same plane with the vertical surface of the 2-inch shoulder adjacent to the valve assembly. The auxiliary telescope reticle line shall be adjusted parallel to a plumb line. With the body assembly installed in the device, the line of sight shall be determined by viewing through the telescope and observing coincidence between the intersecting point of the auxiliary telescopes reticle and the corresponding interescting point of the collimator target line. This coincidence must be maintained within the limits of the tolerance line of the collimator target to assure conformance with the requirement outlined in 3.6."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 6650-A161Y

FSC 6650

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.