MIL-B-63469 (AR)
AMENDMENT 5
27 September 1985
SUPERSEDING
AMENDMENT 4
31 October 1984

MILITARY SPECIFICATION

BODY ASSEMBLIES, GENERAL PURPOSE GRENADE:
M73 AND M75 (PRACTICE)

This Amendment forms a part of Military Specification MIL-B-63469 (AR), dated 2 August 1982, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, Add:

"MIL-STD-1169 Packaging, Packing, and Marking for Shipment of Inert Ammunition Components".

PAGE 5

TABLE I, Welded Tubing: Add "Hydrostatic Test 1 3.3 4.5.4".

Body, M75: Add "Hardness Test 15 3.2 4.4.2.9".

PAGE 12

4.4.2.5, Add Majors:

"112	Location of Render Safe Notch	.40%	3.2	Gage
113	Width of Render Safe Notch	.40%	3.2	Gage
114	Height of Render Safe Notch	.40%	3.2	Gage"

* Delete Majors 112, 113, and 114 in their entirety.

PAGE 13

4.4.2.6: Delete in its entirety and substitute included Page 2 (13).

PAGE 14

4.4.2.7, Major 102: Delete "Large Inside Diameter" and substitute "Depth to datum diameter".

FSC 1330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9335705
4.4.2.6	Cap				NEXT HIGHER ASSEMBLY 9335704
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Angle		0.40	3.2	Gage
102	Overall Height		0.40%	3.2	Gage
MINOR					
201	Small inside diameter		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

PAGE 15

4.4.2.8, Major 102: Delete "visual" and substitute "4.5.9".

Add Major 108:

"108. Excess paint in fuze cavity 0.40% 3.2 4.5.9".

PAGE 16

4.4.2.9: Add Major 105:

"105. Hardness test 0.40% 3.2 Gage".

Add: "Minor 204 Location of bore rider slot .65% 3.2 Gage".

PAGE 17

4.4.2.10, Major: Delete "None Defined".

Add Major 101 and Minor 206:

"101. Excess paint in fuze cavity 0.40% 3.2 4.5.9".

"206. Lacquer band missing or improper (a) 0.65% 3.2 4.5.9".

Add Note (a): "(a) Minor 206 is not applicable to Simulator Grenade."

PAGE 18

4.5.1, line 21: Delete ".003R" and substitute ".010R".

PAGE 20

4.5.7: Add to second sentence "the body assembly."

Add 4.5.9:

"4.5.9 Paint inspection. Visual standards approved by the government shall be used to determine acceptability. The painted part shall be visually examined and compared with the visual standards. Any part that is outside the range of the visual standards shall be classed defective."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.