MIL-C-60118(MU)
AMENDMENT 2
12 March 1968
SUPERSEDING
AMENDMENT 1
31 May 1967

MILITARY SPECIFICATION

COMPUTER, BALLISTICS: M16

This amendment forms a part of Military Specification MIL-C-60118(MU), dated 4 June 1964.

Paragraph 2.1, Specifications: Delete "MIL-B-60124 - Ballistics Computer Subassembly: 8635412 (Cant Unit)" and substitute "MIL-B-60871 - Ballistics Computer Subassembly: 10552928 (Cant Unit)".

Paragraph 3.4: Delete "Ballistics Computer Subassembly: 8635412 (Cant Unit) MIL-B-60124" and substitute "Ballistics Computer Subassembly: 10552928 (Cant Unit) MIL-B-60871.

Paragraph 3.5.4: Delete "deflections" and substitute "deflection"; delete "tolerations" and substitute "tolerance"; under "TOLERANCES ON VALUES OF TABLE 1 - ELEVATION" delete "450 METERS TO 2000 METERS ± .15 MIL" and substitute "450 METERS TO 1999 METERS ± .15 MIL".

Paragraph 4.1.1: Delete and substitute

"4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109."

Add the following paragraph:

"4.2 First article (initial production) inspection.- When required by the contract, an initial production sample shall be submitted to a Government approved facility in accordance with the contract schedule for test and evaluation. The sample shall consist of three ballistic computers. Testing of the sample shall not commence until all of its subassemblies comply with their applicable specifications specified in 3.4. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures, as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to all requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials. After inspection by the contractor and provisional acceptance

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.

at source by the Government, the sample shall be inspected at a Government facility or such other facility as specified in the contract, for all the requirements of the drawings and specifications."

Paragraph 4.4.2, Item Number 3 Description: Delete "within 0.1 degree" and substitute "within 2 minutes"; Item Number 7 Description: Delete "0.5 volt peak-to-peak" and substitute "0.1 volt peak-to-peak".

Paragraph 4.5.7: Delete and substitute

"4.5.7 Effective full-charge count.- To determine conformance to 3.5.6 actuate the E.F.C. switch 25 actuations with APDS-A1 ammo indicated on a control unit and E.F.C. assembly. The dial shall advance to 100. Actuate the E.F.C. switch 100 times with a control unit switched to APDS-A2. The E.F.C. dial shall advance 100 counts. Proceed for 100 and 25 actuations for the HEP and the HEAT ammos respectively. The dial should advance 10 counts for each of these ammos. During the test, care shall be taken to hold the E.F.C. roller down for at least 2 seconds during each actuation. The E.F.C. counter shall perform as specified, plus or minus one count."

Figure 2, Gearing Mechanism: Delete "19.25 ± .25 REVS OF MOTOR FOR EACH REV OF POTENTIOMETER" and substitute "13.28 ± .25 REVS OF MOTOR FOR EACH REV OF POTENTIOMETER."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A076

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:11Z
Check the source to verify that this is the current version before use.