MILITARY SPECIFICATION

MICROCIRCUIT, DIGITAL, CMOS (LOGIC)

This Amendment forms a part of Military Specification MIL-E-63530(AR), dated 8 March 1982, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Preamble: Delete "Armament Research and Development Command" and substitute "Armament, Munitions and Chemical Command."

PAGE 2

3.4, Environmental and mechanical:

Seal (Fine and gross): Delete "(A & C, respectively)" and substitute "(A or B & C respectively)".

Mechanical Shock: Delete "G" and substitute 'C".

PAGE 3

3.5.1, Operating ratings:

TABLE I, NOTE 1/: Delete "(See 4.5.1.7)" and substitute "(See 4.5.23)".

PAGE 5

3.5.4 (a), Delete paragraph in its entirety and substitute the following:

"(a) Pins 9, 10 and 11. When the temperature varies over the operating range (-55°C to 80°C) and the voltage varies from 4.0 to 5.5 volts, the output period shall not shift more than ±5% from the period at +25°C and V_B = 5.0 volts."

PAGE 6

3.7, Data requirement: Delete "4.5.22" and substitute "4.5.25".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

PAGE 9

TABLE III, First Article Inspection, subgroup a:

LVD temperature coefficient: Delete "4.5.12" and substitute "4.5.17".

NOTES, See page 2: Delete “groups a-f; 25 for group g.” and substitute “groups a-e; 25 for group f.”.

TABLE III, subgroup b:

Seal (fine leak): Delete: “Method 1014, A" and substitute “Method 1014, A or B“.

PAGE 10

TABLE III, First Article Inspection subgroup e:

Seal (fine leak): Delete: “Method 1014, A“ and substitute "Method 1014, A or B“.

PAGE 13

4.4.2.1, Microcircuit, Digital, CMOS:

Seal (fine leak): Delete “Method 1014, A“ and substitute “Method 1014, A or B“.

Burn-in: Delete "4.5.17" and substitute “4.5.23”.

PAGE 17

4.4.3.4, Group B testing: At end of paragraph add “ (See MIL-M-38510 for corrective action)"

4.4.3.5, Group C testing: At end of paragraph add “(See MIL-M-38510 for corrective action)";

PAGE 18

4.5.5, Leakage Current High. Delete first sentence in its entirety and substitute the following:

"Pause at bit time 2768 of function test sequence #7 as shown in Figure 10. Set pin at V_{DD} and measure the current into Pin. 16.”

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project. 1345-A474)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.