
FED SUP CLASS 2915



MS PART NO.	A +.000 -.005 DIA	B +.000 -.010 DIA	C DIA	D ±.005
(a) -1				
MS29534-2	1.495	1.310	1.060	.052
MS29534-3	1.870	1.605	1.438	.080
MS29534-4	2.245	1.980	1.730	.080

(a) NO MS STANDARD DRAWING ON THIS SIZE. FOR CAP THIS SIZE SEE USAF DWG NO. 50B9390.

(E) MATERIAL: ALUMINUM ALLOY, QQ-A-225/5, T4 OR QQ-A-200/3 T4.

FINISH: RED ANODIZE, SPEC MIL-A-8625.

(H) SURFACE TEXTURE USAS B46.1-1962.

REMOVE ALL BURRS AND SHARP EDGES.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS .015.

ALL DIAMETERS SHALL BE CONCENTRIC WITHIN .005 FULL INDICATOR READING.

APPROVED 22 Jun 54 REVISED (A) 31 Mar 55 (B) 6 Feb 69

Review activities:

This military standard is approved by the Department of the Air Force and the Naval Air Systems Command and is mandatory for use by these activities. All other military activities are required to employ this standard where suitable.

P.A. USAF-82 Other Cust Navy-AS	TITLE CAP, FITTING, INTERNAL OUTLET, BOOSTER PUMP	MILITARY STANDARD MS29534 (ASG)
PROCUREMENT SPECIFICATION NONE	SUPERSEDES: USAF DWG 66A9039 AND 52B9097	SHEET 1 OF 1

DD FORM 672-1 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. ☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-341-516/A-4620

ASG use only

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:02Z
Check the source to verify that this is the current version before use.