REVISER: GL MD MI MR PS

USER: MO SM

FED. SUP CLASS
6350

PART NUMBER	PACKAGING
MS36437-1	2 oz can
MS36437-2	6 oz can
MS36437-3	1 qt can
MS36437-4	1 gal can
MS36437-5	5 gal pail
MS36437-6	55 gal drum

SAFETY PRECAUTIONS: DANGER! HARMFUL OR FATAL IF SWALLOWED
WARNING! FLAMMABLE

If swallowed, do not induce vomiting. Avoid prolonged or repeated breathing of vapor. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid contact with eyes; in case of contact, flush with plenty of water for at least 15 minutes and get medical attention. The use of gloves and protective equipment is recommended.

INTENDED USE: For use in cleaning the bores of small arms and automatic aircraft weapons. The compound provides a temporary rust resistant coating for the cleaned surface.

MATERIAL: Liquid. Ready to use.

REQUIREMENTS: Qualification required. Composition not specific, however, compound shall meet all requirements of the procurement specification. Minimum flash point, 120 degrees. At 100 degrees the maximum viscosity shall be 15 centistokes. At minus 20 degrees the maximum viscosity shall be 1500 centistokes. All temperatures are Fahrenheit.

NOTE: 1. Referenced documents shall be of the issue in effect on date of invitations for bid.

APPROVED 12 March 1965 REVISED

This standard has been approved by the Department of the Army and is mandatory for use by the Munitions Command activity. All other military activities are required to employ this standard where suitable.

P.A. MU Other Cust	TITLE CLEANING COMPOUND, SOLVENT bore cleaner	MILITARY STANDARD MS36437(MU)
Procurement Specification MIL-C-372	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 57 672 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T17:40Z
Check the source to verify that this is the current version before use.