
# MS9442 (ASG)

FED SUP CLASS 5306




| PART NUMBER | L | K | APPROX WEIGHT LB/100 | PART NUMBER | L | K | APPROX WEIGHT LB/100 |
|---|---|---|---|---|---|---|---|
| | | | | MS9442-31 | 2 625 | 1.690-1.750 | 6.20 |
| | | | | MS9442-32 | 2.750 | 1 815-1 875 | 6.42 |
| | | | | MS9442-33 | 2.875 | 1 940-2 000 | 6.65 |
| MS9442-04 | .500 | .088- .108 | 2.36 | MS9442-34 | 3.000 | 2.065-2 125 | 6.88 |
| MS9442-05 | .562 | .088- .108 | 2.48 | MS9442-35 | 3.125 | 2.190-2 250 | 7.10 |
| MS9442-06 | .625 | .088- .108 | 2.59 | MS9442-36 | 3.250 | 2.315-2.375 | 7.33 |
| MS9442-07 | .688 | .088- .108 | 2.70 | MS9442-37 | 3 375 | 2.440-2 500 | 7.55 |
| MS9442-08 | .750 | 088- .108 | 2.81 | MS9442-38 | 3.500 | 2.565-2.625 | 7.78 |
| MS9442-09 | .812 | .088- .108 | 2.93 | MS9442-39 | 3.625 | 2.690-2.750 | 8.01 |
| MS9442-10 | .875 | .088- .108 | 3.04 | MS9442-40 | 3.750 | 2.815-2.875 | 8.23 |
| MS9442-11 | .938 | .088- .108 | 3.15 | MS9442-41 | 3.875 | 2.940-3.000 | 8.46 |
| MS9442-12 | 1.000 | .125- .145 | 3.27 | MS9442-42 | 4.000 | 3.065-3.125 | 8.68 |
| MS9442-13 | 1.062 | .128- .188 | 3.38 | MS9442-43 | 4.125 | 3.190-3.250 | 8.91 |
| MS9442-14 | 1.125 | .190- .250 | 3.49 | MS9442-44 | 4.250 | 3.315-3.375 | 9.13 |
| MS9442-15 | 1.188 | .252- .312 | 3.60 | MS9442-45 | 4.375 | 3.440-3.500 | 9.36 |
| MS9442-16 | 1.250 | .315- .375 | 3.72 | MS9442-46 | 4.500 | 3.565-3.625 | 9.59 |
| MS9442-17 | 1.312 | .378- .438 | 3.83 | MS9442-47 | 4.625 | 3.690-3.750 | 9.81 |
| MS9442-18 | 1.375 | .440- .500 | 3.94 | MS9442-48 | 4.750 | 3.815-3.875 | 10.04 |
| MS9442-19 | 1.438 | .508- .562 | 4.06 | MS9442-49 | 4.875 | 3.940-4.000 | 10.26 |
| MS9442-20 | 1.500 | .565- .625 | 4.17 | MS9442-50 | 5.000 | 4.065-4.125 | 10.49 |
| MS9442-21 | 1.562 | .628- .688 | 4.28 | MS9442-51 | 5.125 | 4.190-4.250 | 10.71 |
| MS9442-22 | 1.625 | .690- .750 | 4.39 | MS9442-52 | 5.250 | 4.315-4.375 | 10.94 |
| MS9442-23 | 1.688 | .752- .812 | 4.51 | MS9442-53 | 5.375 | 4.440-4 500 | 11.17 |
| MS9442-24 | 1.750 | .815- .875 | 4.62 | MS9442-54 | 5.500 | 4 565-4 625 | 11 39 |
| MS9442-25 | 1.875 | 940-1.000 | 4 85 | MS9442-55 | 5 625 | 4 690-4 750 | 11.62 |
| MS9442-26 | 2.000 | 1.065-1.125 | 5.07 | MS9442-56 | 5.750 | 4.815-4 875 | 11.84 |
| MS9442-27 | 2.125 | 1.190-1.250 | 5.30 | MS9442-57 | 5 875 | 4 940-5.000 | 12.07 |
| MS9442-28 | 2.250 | 1.315-1.375 | 5.52 | MS9442-58 | 6 000 | 5 065-5.125 | 12.29 |
| MS9442-29 | 2.375 | 1.440-1 500 | 5.75 | | | | |
| MS9442-30 | 2.500 | 1 565-1.625 | 5.97 | | | | |

1. SHANK SHALL BE STRAIGHT WITHIN .003 FIR PER INCH OF BOLT LENGTH
2. THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR
3. THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .015 FIR.
4. INCOMPLETE THREADS NOT TO ENTER FILLET AREA
5. MATERIAL STEEL AMS 6304
6. HARDNESS ROCKWELL C42-46
7. FINISH DIFFUSED NICKEL-CADMIUM PLATE AMS 2416. DIMENSIONS SPECIFIED ARE AFTER PLATING. CONTACT POINTS PERMISSIBLE. PD MAY BE REDUCED .0012 MAXIMUM BEFORE PLATING
8. MANUFACTURING SPECIFICATION AMS 7455 PARTS SUBJECT TO MAGNETIC PARTICLE INSPECTION PER AMS 2640 BEFORE PLATING
9. SURFACE ROUGHNESS AS 291, UNLESS OTHERWISE SPECIFIED SURFACES TO BE 125 MICROINCHES EXCEPT HEXAGON.
10. BREAK SHARP EDGES .003 - 015 UNLESS OTHERWISE SPECIFIED
11. DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED TOLERANCES; LINEAR DIMENSIONS ± .010, ANGULAR DIMENSIONS ± 5°.
12. TRUE POSITION TOLERANCES SPECIFIED ARE FOR MAXIMUM MATERIAL CONDITION.
13. DO NOT USE UNASSIGNED PART NUMBERS

MS Ac.1961 ARE SAE PUBLICATIONS
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE ENGINE AND PROPELLER UTILITY PARTS COMMITTEE OF THE SAE.

REVISED
APPROVED 21 DEC 62

| | | |
|---|---|---|
| PA<br>USAF - AFSC<br>Other Cust<br>NAVY - WEP | TITLE<br>BOLT, MACHINE - STEEL AMS 6304, DIFFUSED NICKEL-CADMIUM PLATED, HEXAGON HEAD, DRILLED, .3125-24 UNJF-3A | MILITARY STANDARD<br>MS9442 (ASG) |
| PROCUREMENT SPECIFICATION<br>NONE | SUPERSEDES: | SHEET 1 OF 1 |

DD FORM 672-1 (Limited coordination)

NOTICE—When Government drawings specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation the United States Government thereby incurs no responsibility nor any obligation whatsoever and the fact that the Government may have formulated furnished, or in any way supplied the said drawings specifications or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture use or sell any patented invention that may in any way be related thereto

This standard has been approved by the Department of the and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable

☆U S GOVERNMENT PRINTING OFFICE 1981 — 703-023/7778

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:17Z
Check the source to verify that this is the current version before use.