MILITARY SPECIFICATION

CARTRIDGE, 60MM, SMOKE, WP, M302A2 ASSEMBLING, MARKING AND PACKING

This Specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements and provides quality assurance provisions for assembling, marking and packing for the cartridge, 60MM, SMOKE, WP, M302A2.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specifications for
MIL-P-60316 - Primer, Percussion, M32, Loading, Assembling and Packing

STANDARDS

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

2.1.2 Other government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

12903088	- Cartridge, 60MM, Smoke, WP, M302A2
9215576	- Container, Ammunition, Fiber M567 for Cartridge, 60MM Smoke, WP, M302A1 and A2 in Jungle Wrap
9215577	- Box, Ammo, packing, Wood, Nailed for Cartridge, 60MM Smoke, WP, M302A1 and A2 Jungle Wrap
9280109	- Container, Ammunition, Metal: PA70 for 60MM Mortar Ammunition

INSPECTION EQUIPMENT DRAWINGS

7256281	- Alignment Check Gage
7256348	- Alignment Gage
7257962	- Limit Check Gage
9246386	- Inspection Equipment for Measuring Leakage of Metal Ammunition Containers

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

3.2 Cartridges. The cartridge shall comply with all requirements specified on Drawing (dwg.) 12903088 and with all requirements specified in applicable specifications.

3.3 Ballistic performance (proving ground). The cartridge shall comply with the following requirements when tested as specified in 4.4.3.2.

3.3.1 Misfire The cartridge shall not fail to fire from the weapon.

3.3.2 Premature burst. There shall be no premature functioning in the mortar tube or within 100 meters travel from the mortar tube.

3.3.3 Impact functioning (duds). There shall be visible evidence of functioning upon impact as indicated by presence of a flash or smoke cloud.

3.3.4 Horizontal range (short rounds). No cartridge shall have a horizontal range less than percent of the average horizontal range when calculated without the short round.

3.3.5 Range standard deviation. The standard deviation in horizontal range shall be no greater than the maximum (max.) lot values shown in Table I for the increment charge indicated.

TABLE I. Standard deviation requirement

Increment Charge Zone	Max. Lot Standard Deviation (Meters)
0	15
4	41

3.3.6 Metal parts separation. There shall be no metal parts separation in the mortar tube or in flight.

3.4 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein. (See 4.3 and 6.2).

3.5 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, rust and other foreign matter. The method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of Section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the components in the quantities described in Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table II specified herein.

4.3.3 Rejection. See MIL-A-48078 and the first article ballistic test shall be rejected per Table II criteria.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:48Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70614 (AR)

PARAGRAPH	TITLE: Cartridge, Assembly and Container		SHEET 1 OF 1		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cartridge (Dwg. 12903088				
	Examination of defects	25		3.2	4.4.2.4/4.4.2.5
	Ballistic test (Proving Ground)	80		3.3	4.4.3.2
	Metal Ammunition Container (Dwg. 9255567)				
	Air leakage test	5		5.1	4.4.3.1

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078. In addition, each inspection lot of ignition cartridges shall contain:

a. WP loaded body filling assemblies from one manufacturer in accordance with the same drawing, same drawing revision, same specification and same specification revision of one loading lot interfix number.

b. Loaded ignition cartridges of one lot interfix number from one manufacturer.

c. Fin assemblies of one lot interfix number from one manufacturer.

d. Loaded primers of one lot interfix number from one manufacturer.

e. Propellant increments of one lot interfix from one manufacturer.

f. Loaded fuzes of one lot interfix number from one manufacturer.

g. Loaded projectiles bursters of one lot interfix number from one manufacturer.

h. Fin extension of one lot inter fix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.1	Body Filling Assembly as Received from WP Loading Facility	1	1	9205339
				NEXT HIGHER ASSEMBLY: 12903088

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	WP leakage or evidence of leakage		100%	3.2	Visual
Major	None defined				
Minor 201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Cartridge, Prior to Inserting Burster	1 OF 1	12903088
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Burster pad missing		100%	3.2	Visual
Major 101	Foreign matter in burster cavity		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Cartridge, Prior to Assembling Fuze	1 OF 1	12903088
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Burster charge missing		0.40%	3.2	Visual
102	Foreign matter in fuze well		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Cartridge, Prior to Assembling Primer	1 OF 1	12903088
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Ignition cartridge missing or inverted		100%	3.2	Visual
Major					
101	Fin or fin extension torque		0.40%	3.2	4.5.1/Test
102	Fuze torque		0.40%	3.2	4.5.1/Test
103	Fin extension to fin and shell body sealing compound missing		0.40%	3.2	Visual
104	Sealing compound improperly located, missing or not full 360 degrees in base of cartridge housing cavity (prior to insertion of ignition cartridge)		0.40%	3.2	Visual
105	Sealing compound bead improperly located missing or not full 360 degrees on red end of ignition cartridge (prior to seating of primer into fin cavity)		0.40%	3.2	Visual
106	Excessive sealing compound on primer pellet closing disc		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.5	Cartridge				12903088
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Primer head above flush with rear surface of fin cartridge container		100%	3.2	Visual
2	Fin damaged or distorted (this characteristic must be gaged after all mechanical handling of the fin		100%	3.2	Gage
3	Fuze safety wire missing or not fully seated		100%	3.2	Visual
Major					
101	Cartridge assembly fails to fully enter the profile and alignment gage		100%	3.2	Gage
102	Total length, max.		0.40%	3.2	Gage
103	Primer stake missing or thread sealing compound does not cover a minimum of one half the number of male primer threads for a full 360 degrees (after disassembly) (as applicable)		0.40%	3.2	Visual
104	Any component damaged or incorrectly assembled (except as described by critical defect 2 above)		0.40%	3.2	Visual
105	Primer fails to withstand reapplication of minimum assembly torque		0.40%	3.2	Test
106	Fuze not fully seated		0.40%	3.2	Visual
NOTES:					

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

MIL-C-70614 (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.5	Cartridge (Cont)				12903088
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Protective coating with total damaged area in excess of 1/4 square inch		0.65%	3.2	Visual
202	Marking misleading, missing or unidentifiable, including incorrect color code		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.5	Visual
	PROVING GROUND TEST (Production ballistic acceptance)	80/ 50		3.3	4.4.3.2/4.5.2

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70614 (AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.6	Unsealed Fiber Container		1 OF 1		9215576
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Propellant increment missing		100%	5.1	Visual
Major					
101	Propellant increment cut or torn		100%	5.1	Visual
102	Ring support missing		0.40%	5.1	Visual
103	Filler assembly missing		0.40%	5.1	Visual
Minor					
201	Glue or asphalt on round		0.65%	5.1	Visual
202	Cartridge improperly assembled into container		0.65%	5.1	Visual
203	Round cannot be removed by hand		0.65%	5.1	Manual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70614 (AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.7	Sealed Fiber Container		1 OF 1	9215576
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Container damaged or cut through all asphalt impregnated layers		0.40%	5.1	Visual
102	Tape incomplete, badly wrinkled or missing		0.40%	5.1	Visual
103	Metal end loose or distorted		0.40%	5.1	Visual-Manual
Minor					
201	Sealing strip improperly applied		0.65%	5.1	Visual
202	Gap between cover and body excessive (exceeds 1/8 inch)		0.65%	5.1	Visual
203	Contents loose		0.65%	5.1	Manual
204	Marking		0.65%	5.3	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Fiber Container Wrapped in Barrier Material Prior to Waxing-Jungle Wrap				9215576
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Barrier material improperly assembled		0.40%	5.1	Visual
102	Barrier material ends improperly folded or taped		0.40%	5.1	Visual
Minor					
201	Marking missing or incomplete		0.65%	5.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Fiber Container After Waxing-Jungle Wrap	1 OF 1	9215576
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wax coating incomplete or damaged		0.40%	5.1	Visual
Minor					
201	Marking missing or unidentifiable		0.65%	5.3	Visual
202	Kraft paper improperly placed on container		0.65%	5.1	Visual
203	Tear tab not visible		0.65%	5.1	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Metal Ammunition Container (Unsealed)				9280109
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any material containing condensate or surface moisture		0.40%	5.1	Visual
102	Spacer missing		0.40%	5.1	Visual
103	Cushion missing		0.40%	5.1	Visual
104	Incorrect number of assemblies		0.40%	5.1	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70614 (AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.11	Metal Ammunition Container (Sealed)		1 OF 1	9280109
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Leakage test		100%	5.1	4.4.3.1/4.5.3
Minor					
201	Marking missing, misleading or unidentifiable		0.65%	5.3	Visual
202	Contents loose		0.65%	5.1	Manual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Sealed Wood Packing Box				9215577
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Contents exposed		0.40%	5.2	Visual
102	DOD symbol missing or incorrect		0.40%	5.2	Visual
103	Board broken or split		0.40%	5.2	Visual
104	Hardware or strapping missing, broken or loose		0.40%	5.2	Visual-Manual
Minor					
201	Hardware improperly engaged		0.65%	5.2	Visual-Manual
202	Car seal missing, unsealed or improperly positioned		0.65%	5.2	Visual-Manual
203	Contents loose		0.65%	5.2	Visual-Manual
204	Handle missing or insecure		0.65%	5.2	Visual-Manual
205	Marking misleading, missing or unidentifiable		0.65%	5.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. The following tests shall be performed in accordance with the provisions of Table II and 4.4.

4.4.3.1 Leakage test (see drawing 9280109) major defect. The sealed metal ammunition container shall be tested 100 percent for leakage. Any container which fails to comply with the applicable requirement shall be classed defective and removed from the lot. The test shall be performed as specified in 4.5.3.

4.4.3.2 Proving ground test. The cartridges shall be observed for the characteristics specified in Table III.

TABLE III. Test characteristics

		Defect Classification	Accept	Reject
(a)	Misfire (see 3.3.1)	Major	1	2
(b)	Premature burst (see 3.3.2)	Critical	0	1
(c)	Impact functioning (dud) (see 3.3.3)	Major	3	4
(d)	Horizontal range (see 3.3.4) less than 80 percent of average horizontal range	Critical	0	1
(e)	Range standard deviation (see 3.3.5)	Major	--	--
(f)	Metal parts separation (see 3.3.6)	Special	0	1

4.4.3.2.1 Initial sampling. Beginning with the first article sample and the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, a sample of 80 cartridges shall be selected from each lot for this test. Acceptance criteria shall be in accordance with Table III. In addition, if the range standard deviation for the sample cartridges fired at charge zone zero or charge zone four exceeds the application maximum limit specified in Table I (see 3.3.5), the lot shall be rejected. The test shall be performed as specified in 4.5.2.

4.4.3.2.2 Production sampling. After three consecutive lots have met the criteria of 4.2.3.3.1, a sample of 50 cartridges shall be selected from each lot for this test. Acceptance criteria shall be in accordance with Table III and in addition, if the standard

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

deviation in zero or charge zone four exceeds the applicable maximum limit specified in Table I (see 3.3.5), the lot shall be rejected. The test shall be performed as specified in 4.5.2.

4.4.3.3 Check test for possible deterioration of Primer, Percussion, M32 (see MIL-P-60316). If the total elasped time between original acceptance of the M32 primer lot and the assembly of that lot into complete round cartridges exceeds two years, or if the M32 primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass, the check test for deterioration specified in MIL-P-60316 before the M32 primer lot is assembled into the cartridges. The test shall be performed by the contractor on assemblies selected by the Government inspector at the facility assembling the complete cartridges.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection euqipment designs in accordance with the terms. of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Torque test. The assembly torque shall be applied to the applicable component while holding the adjacent mating component in such a manner as to avoid possible damage to any component of the assembly.

4.5.2 Proving ground test. The test shall be performed at a Government proving ground in accordance with the applicable Acceptance Test Procedures. The cartridge shall be fired from a 60MM Mortar for which the round is standard. One half of the sample cartridges shall be fired with an ignition cartridge (Charge zone zero) and one half of the sample cartridges shall be fired with an ignition cartridge and four propellant increments (charge zone four). The individual velocities, max pressures and impact ranges shall be obtained and recorded. The standard deviation and the arithmetic average of the impact ranges shall be calculated and recorded.

4.5.3 Leakage test. (For Marine Corps Pack Only.) Each box shall be tested using a partial vacuum system as per envelope dwg. 9246386 utilizing a chamber with minimal clearance between the exterior of the box and interior of the chamber.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. The cartridges shall be preserved and packaged in accordance with dwg's. 9215576 and 9280109.

5.2 Packing. The cartridges shall be packed in accordance with dwg. 9215577.

5.3 Marking. Marking of the wood box shall be in accordance with dwg. 9215577. The fiber container shall be marked in accordance with dwg. 9215576 and the metal container shall be marked in accordance with dug. 9280109.

6. NOTES

6.1 Intended use. The cartridges covered by this specification are intended for use with the 60mm mortar system.

6.2 Ordering data. See MIL-A-48078 (AR).

6.3 Submission of designs for approval. See MIL-A-48078. Submit equipment designs, as required to: Commander, US Army Armament, Munitions and Chemical Command, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.4 Drawings. Drawings listed in Section 2 of this specfiication under the headings U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal or ARRADCOM. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Subject term (key word listing).

Air leak test
Body filling assembly
Burster pad
Cartridge assembly
Torque test

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A382)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-70614	CARTRIDGE, 60MM, SMOKE, WP, M302A2 ASSEMBLING, MARKING AND PACKING

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:48Z
Check the source to verify that this is the current version before use.