INCH-POUND

MIL-C-71043 (AR)
28 November 1991

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, AMPLIFIER: 11784526

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements and tests for the Amplifier Circuit Card Assembly, which is a component in the Electronic Control Unit (ECU). The ECU is a part of the Target Holding Mechanism/Tank Gunnery (THM/TG) (See 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (See 6.2).

SPECIFICATIONS

MILITARY

MIL-F-13926 - Fire Control Materiel, Manufacture and Inspection, General Specification for

MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U.S Army ARDEC, ATTN. SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5999
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-810	-	Environmental Test Methods and Engineering Guidelines
MIL-STD-2000	-	Standard Requirements for Soldered Electrical and Electronic Assemblies

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.4)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

11784526 - Circuit Card Assembly, Amplifier
11784528 - Schematic Diagram, Amplifier

SPECIAL PACKAGING INSTRUCTIONS

PS11784526 - Packaging of Amplifier Circuit Card Assembly

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 11784526 and all associated drawings, and with all requirements specified in applicable specifications and standards. Where applicable, the Amplifier Circuit Card Assembly shall meet the requirements of MIL-F-13926 as follows:

a. Dimensions and tolerances
b. Inorganic protective surface finishings
c. Part identification and marking
d. Workmanship

3.3 Environmental service conditions.

3.3.1 Vibration. The Amplifier Circuit Card Assembly shall not suffer damage and shall meet the requirements of 3.4 and 3.7 after exposure to sinusoidal vibrations for 1 hour along the vertical axis within the frequency range of 10 to 40 hertz (Hz). The rate of change of frequency at each frequency range shall not exceed 1 Hz per second.

Frequency Range	Amplitude
10 to 15 hertz	0.06 inches double amplitude
15 to 25 hertz	0.04 inches double amplitude
25 to 40 hertz	0.02 inches double amplitude

The frequency of vibration shall be swept logarithmically.
The cycling time shall be 60 minutes.
The sweep rate shall be 3.75 minutes ± 10%.
The 10-40-10 hertz sweep time is 2 minutes 30 seconds ± 10%.

3.3.2 Temperature.

3.3.2.1 Operating. The Amplifier Circuit Card Assembly shall meet the requirements of 3.4 and 3.7 when stabilized thermally at any temperature between -25 degrees F and + 125 degrees F.

3.3.2.2 Non-operating (storage). The Amplifier Circuit Card Assembly shall not suffer permanent damage when subjected to the constant temperature extremes of -40 degrees F for a period of 4 hours and +160 degrees F for a period of 4 hours (after temperature stabilization), and shall meet the requirements of 3.4 and 3.7 when returned to room ambient.

3.4 Electrical. The electrical characteristics and continuity of the Amplifier Circuit Card Assembly shall be as specified on the Amplifier Schematic Diagram drawing 11784528. Refer to this schematic diagram for the performance requirements of 3.7, and performance testing of 4.7.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

3.5 Soldering. The circuit board shall be soldered per the requirements of MIL-STD-2000.

3.6 Circuit identification. The contact fingers (Pins) on the circuit board shall have adequate permanent labeling for proper identification of pins in the circuitry.

3.7 Performance.

3.7.1 Functional description. The Amplifier Circuit Card Assembly is the section of the circuitry in the Electronic Control Unit (ECU) that provides sensitivity response from the hit sensors. Up to four (4) hit sensors are attached to a simulated tank target, and are plugged into the ECU. The ECU has four (4) sensitivity settings from low to high based upon the type of ammunition used. The Amplifier Circuit Card Assembly provides hit impulses or hit sensor failure signals as required.

3.7.2 Supply voltage. The Amplifier Circuit Card Assembly shall function when a +12 Volt direct current (Vdc) is connected to Pin S with return to ground contact Pin H.

3.7.3 Normal condition. With + 12 VDC applied at contact Pin S, the following voltage shall be present:

Pin D +12 Vdc ± 0.1 Vdc

3.7.4 Open circuit. With + 12 Vdc applied at contact Pin S and with the resistor disconnected from contact Pin C the following voltage shall be present:

Pin D .000 Vdc to 0.400 Vdc

This voltage at contact Pin D is also required for inputs at Pin E, Pin J, and Pin L (See 4.7.5.1.3).

3.7.5 Short circuit. With + 12 Vdc applied at contact Pin S, and with a short between contacts Pin C and Pin H the following voltage shall be present:

Pin D .000 to 0.400 Vdc

This test is also required at contact Pin E, Pin J, and Pin L with respect to contact Pin H. Under these conditions the following voltages shall be present:

Pin F 0.000 to 0.400 Vdc
Pin K 0.000 to 0.400 Vdc
Pin M 0.000 to 0.400 Vdc

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

3.7.6 Simulated hit sensor signal. Hit sensors 1 through 4 (Pin C, Pin J, Pin E and Pin L) are required to register a hit pulse which occurs at Pin B. The hit pulse shall be +12 Vdc (11.8 Vdc to 12.1 Vdc) in amplitude and of 10 microseconds minimum duration. Hit sensor signal sensitivity response shall comply with Table IV of 4.7.5.1.5.

3.8 First article. When specified in the contract or purchase order, sample shall be subjected to first article inspection in accordance with technical provisions herein (see 4.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contact or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Special sampling inspection (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

4.2.1 Inspection conditions. Unless otherwise specified, all examinations and tests shall be conducted at the following standard ambient conditions:

a.	Temperature	+60 deg to +90 deg F.
b.	Relative humidity	90% RH Max.
c.	Pressure	28 to 32 inches of Hg.

4.3 First article inspection.

4.3.1 First article submission. The contractor shall submit a first article sample as designated by the contracting officer consisting of three (3) Amplifier Circuit Card Assemblies for inspection in accordance with 4.3.2.

4.3.2 Inspections to be performed. First article assemblies, components and test specimens may be subjected by the Government to any or all of the examinations and tests specified in Table I (Functional test) and Table II (Special Sampling) herein and to any or all requirements of the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly, component or test specimen to comply with any of the requirements.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

4.4.2 Examinations and tests.

4.4.2.1 Components, assemblies and subassemblies.

a. The contractor's quality program or detailed inspection plan shall provide assurance of compliance of all characteristics with the applicable drawings and specifications utilizing as a minimum the conformance criteria specified in this document and the Quality Assurance Provisions (QAP) listed in the Technical Data Package (TDP). In the absence of QAP's, the applicable quality assurance provisions of MIL-F-13926 shall apply.

b. Alternative inspection procedures, methods or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the procuring contracting officer for evaluation and approval by the Government. When required the contractor shall demonstrate that the effectiveness of the proposed alternative(s) is equal to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative(s) provide equal assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program plan or detailed inspection system, as applicable.

4.4.2.2 Final acceptance inspection. Subsequent to first article approval, examinations and tests related to Section 3 shall be performed as specified in 4.4.2.3 and 4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

4.4.2.3 Functional tests. The tests in Table I shall be performed on a 100% basis.

TABLE I. Functional tests
(100% Inspection)

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
Critical:	None	N/A
Major:		
101. Electrical	3.4	4.7.2
102 Soldering	3.5	4.7.3
103. Performance	3.7	4.7.5
104. Workmanship	3.2d	Visual
Minor:		
201. Identification	3.6	4.7.4

4.5 Special sampling. One Amplifier Circuit Card Assembly out of the first 50 produced and one out of each 100 produced thereafter shall be selected at random. The sample shall have met the requirements and tests of Table I and shall then meet the tests in Table II. Unless otherwise specified in the contract the items shall be returned to the lot upon successful completion of testing.

TABLE II. Special sampling

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
Critical:	None	N/A
Major:		
105. Vibration	3.3.1	4.7.1.1
106. Temperature	3.3.2	4.7.1.2
Minor:	None	N/A

4.5.1 Failure of sample. Should any one item of a special sampling fail to meet any of the specified test requirements, acceptance of the product shall be suspended by the Government until necessary corrections to all production since the last test as well as to current production has been accomplished in accordance with the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

4.6 Inspection equipment.

4.6.1 Government-furnished inspection equipment. Where the contract provides for Government-furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements of MIL-I-45607.

4.6.2 Contractor-furnished inspection equipment.

4.6.2.1 Government design. Unless otherwise specified in the contract, all inspection equipment identified by drawing number in specifications or QAPs forming a part of the contract shall be supplied by the contractor in accordance with the design specified. The contractor may, however, propose alternatives to Government designs for approval in accordance with 6.3.

4.6.2.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the "Methods of Inspection" specified in 4.7 of this specification and with the components inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926 whenever Government designs are not specified (see 4.6.2.1). Since tolerance of test equipment is normally considered to be within 10 percent of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to ensure that the test equipment will reliably indicate acceptability of a product which does not exceed 90 percent of the prescribed tolerance limit and permit positive rejection when nonconforming. Construction shall be such as to facilitate routine calibration of test equipment. Contractor inspection equipment designs shall be submitted for approval in accordance with 6.3.

4.6.2.3 Test equipment. In conjunction with 4.6.2.1 and 4.6.2.2, the test equipment listed in Table III (Test equipment list), or equivalent meeting minimum requirements, shall be used in the performance of the applicable test methods and procedures as specified in 4.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

TABLE III. Test equipment list

ITEM NUMBER	DESCRIPTION
1. DC Power Supply	+12 Vdc ± 0.1 Vdc. HP Model 6284A or equivalent
2. Oscilloscope	Dual time base with mixed sweep capabilities. Input impedance of 1 megohm or greater, 0 - 15 Vdc range. Tektronix 2235 or equivalent
3. Generator	Produces a 100 kHz ± 5% square wave with an amplitude of 15 Vdc into a 25 ohm load. Wavetek Model 145 or equivalent
4. Digital Multimeter	Accuracy and resolution of ± 0.2 % from 1 - 100 Vdc. Input Impedance 10 megohms or greater. Fluke Model 8060A or equivalent
5. Decade Resistor Box	Provides fixed accurate selectable resistance values having at least resistance ranges of the switches from 0 to 1.0, 0 to 10, 0 to 100, 0 to 1000, and 0 to 10,000. Zero resistance of each decade less than .005 ohms, and the entire unit less than .05 ohms. OHMITE stock No. 3420 or equivalent.
6. Resistors	5.6K 5% ohm 1/8W (4 req'd) 10K 5% ohm 1/8W (1 req'd)
7. Temperature Chamber	-40 deg C to +71 deg C at a rate of ± 6 deg C/minute minimum

4.7 Methods of inspection.

4.7.1 Environmental. Environmental tests shall be conducted in accordance with the test conditions, general test performance guidance, and individual test methods of MIL-STD-810 except as specified herein. Test facilities, chambers and apparatus used in conducting the tests contained in this specification shall be capable of meeting the conditions required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

4.7.1.1 Vibration. The test shall be performed as specified in Method 514, Category 8, Procedure I, of MIL-STD-810 as modified by 3.3.1 herein. In Step 1 of Procedure I only steps 4 through 8 of paragraph II-2.1 apply. The Amplifier Circuit Card Assembly shall be secured to the vibration generator using a suitable fixture in a vertical position with the connector fingers pointing to the left when viewing the component side of the board. After vibration, the Amplifier Circuit Card Assembly shall be tested as specified in 4.7.2 and 4.7.5 herein to determine compliance with 3.3.1. If the requirements are not met, the item shall be rejected.

4.7.1.2 Temperature.

4.7.1.2.1 High (operating and non-operating). This test shall be performed as specified in Procedures I and II, Method 501 of MIL-STD-810 with constant temperature extremes as specified in 3.3.2. The operational checkout shall be as specified in 4.7.2 and 4.7.5 for compliance with 3.3.2. If the requirements are not met, the item shall be rejected.

4.7.1.2.2 Low (operating and non-operating). This test shall be performed as specified in Procedures I and II, Method 502 of MIL-STD-810 with constant temperature extremes as specified in 3.3.2. The operational checkout shall be as specified in 4.7.2 and 4.7.5 for compliance with 3.3.2. If the requirements are not met, the item shall be rejected.

4.7.2 Electrical. Continuity shall be inspected by Standard Measuring Equipment (SME) and visual examination for compliance with 3.4. If the requirements are not met, the item shall be rejected.

4.7.3 Soldering. Soldering processes and workmanship shall be inspected by inspectors to the requirements and acceptance criteria of MIL-STD-2000, as specified by 3.5 herein.

4.7.4 Identification. Visual inspect circuit boards for adequate labeling of contact pins, as required by 3.6 herein.

4.7.5 Performance. The performance of the Amplifier Circuit Card Assembly shall be tested using the equipment listed in Table III. All input and output parameters shall comply with the requirements of 3.7. If the requirements are not met, the item shall be rejected.

4.7.5.1 Step-by-step procedure. The following test procedure shall be conducted in order to comply with the requirements of 3.7. If the requirements are not met, the item shall be rejected.

4.7.5.1.1 Initial conditions. Test set-up

a. Connect a jumper wire across Pins D, P, F, K and M.
b. Connect the 10K resistor from Pin R to Pin S.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

c. Connect the power supply (12 Vdc ± .01) positive output to Pin S and return to ground Pin H.
d. Connect the decade resistor box terminals to Pin N and Pin S.

e. Connect a 5.6K resistor each across Pin C and Pin H, Pin E and Pin H, Pin J and Pin H, and finally Pin L and Pin H.
f. Apply the +12 Vdc power supply at Pin S.

Note: All voltages are measured with respect to ground or power supply return.

4.7.5.1.2 Normal condition. Test to meet the requirement of 3.7.3.

a. Measure the voltage at Pin D with respect to Pin H. The reading shall be +12 Vdc ± 0.1 Vdc.

4.7.5.1.3 Open circuit. Test to meet the requirement of 3.7.4.

a. Remove the 5.6K resistor connected to Pin C. Measure the output at Pin D. The reading shall be .000 Vdc to 0.400 Vdc. Replace the resistor after taking reading.

b. Repeat a above for inputs at Pin E, Pin J, and Pin L measuring the output at Pin D. The reading shall be .000 Vdc to 0.400 Vdc for each test.

4.7.5.1.4 Short circuit. Test to meet the requirements of 3.7.5.

a. Commence test with the 5.6K resistors each connected from input Pin C, Pin E, Pin J, and Pin L to the ground Pin H.

b. Connect a jumper wire (less than 1 OHM) across the resistor between Pin C and Pin H. Measure the output at Pin D with respect to Pin H. The reading shall be 0.000 Vdc to 0.400 Vdc. After measurement remove the jumper wire.

c. Repeat step b above for Pin E, Pin J, and Pin L each connected to Pin H. Measure the output at Pin F, Pin K, and Pin M with respect to Pin H. The reading at each Pin shall be .000 Vdc to .400 Vdc. After measurement remove the jumper wire.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

4.7.5.1.5 Simulated hit sensor signal. Test to meet the requirement of 3.7.6.

a. Commence test with hit sensor 1, which is Pin C. Using Table IV, apply the input from column one (1) to Pin C and Pin H (GND) using a square wave generator. Test for each of four (4) sensitivity settings at each of five (5) frequencies. The input signal shall be an AC sinewave for a 2 millisecond (ms) burst.

b. Using the oscilloscope, determine the lowest input amplitude within a millivolt (Pin C and Pin H GND) at which a hit pulse occurs at Pin B with respect to Pin H. The hit pulse shall be +12 Vdc (11.8 Vdc to 12.1 Vdc) in amplitude, and of 10 microseconds minimum duration. The readings shall comply with column three (3) of Table IV for the sensitivity setting and frequency tested.

c. Repeat step b above for hit sensors 2, 3, and 4 which are at Pin J, Pin E, and Pin L respectively. Apply the required input from column one (1) of the table. Record the hit pulses on Pin B.

TABLE IV. Hit sensor frequency sensitivity voltages

2 ms Burst Frequency	Sensitivity Setting Vs. Decade Resistor Setting	Peak Millivolt Acceptable Range
500 Hz	1 (6.8K)	30 to 75 MV
500 Hz	2 (1.8K)	95 to 140 MV
500 Hz	3 (680)	175 to 225 MV
500 Hz	4 (390)	205 to 255 MV
1000 Hz	1 (6.8K)	10 to 55 MV
1000 Hz	2 (1.8K)	50 to 95 MV
1000 Hz	3 (680)	95 to 140 MV
1000 Hz	4 (390)	115 to 160 MV
2000 Hz	1 (6.8K)	5 to 45 MV
2000 Hz	2 (1.8K)	25 to 70 MV
2000 Hz	3 (680)	55 to 100 MV
2000 Hz	4 (390)	70 to 110 MV
5000 Hz	1 (6.8K)	5 to 50 MV
5000 Hz	2 (1.8K)	25 to 70 MV
5000 Hz	3 (680)	50 to 95 MV
5000 Hz	4 (390)	60 to 105 MV
10,000 Hz	1 (6.8K)	10 to 55 MV
10,000 Hz	2 (1.8K)	35 to 80 MV
10,000 Hz	3 (680)	60 to 105 MV
10,000 Hz	4 (390)	75 to 120 MV

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 General. Preservation, packing, and marking shall be in accordance with Packaging Data Sheet 11784526. The level of protection shall be as specified in the procurement document.

6. NOTES

(This section contains information of a general explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Amplifier Circuit Card Assembly is one of three (3) Circuit Card Assemblies used in the Electronic Control Unit (ECU) of the Target Holding Mechanism/Tank Gunnery (THM/TG).

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).
c. Applicable stock number.
d. First article sample requirements.
e. Packaging requirements, if other than specified in Section 5.
f. Serialization requirements, if applicable.
g. Certification of conformance for each lot of shipment of product.

6.3 Submission of contractor inspection equipment designs for approval. Submit two copies of designs as required to: Commander, U.S. Army AMCCOM, ATTN: SMCAR-QAF-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as, U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

a. Electronic Control Unit (ECU)
b. Target Holding Mechanism/Tank Gunnery (THM/TG)
c. Hit Sensor

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 5999-A122)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1 DOCUMENT NUMBER	2 DOCUMENT DATE (YYMMDD)
	MIL-C-71043 (AR)	28 NOVEMBER 1991

3 DOCUMENT TITLE
CIRCUIT CARD ASSEMBLY, AMPLIFIER. 11784526

4 NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible Attach extra sheets if needed)*

5 REASON FOR RECOMMENDATION

6 SUBMITTER

a NAME (Last, First, Middle Initial)	b ORGANIZATION	
c ADDRESS (Include Zip Code)	d TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7 DATE SUBMITTED (YYMMDD)

8 PREPARING ACTIVITY

a NAME	b TELEPHONE (Include Area Code)	
US ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial (201) 724-6674	(2) AUTOVON 880-6674
ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL,NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:19Z
Check the source to verify that this is the current version before use.