MILITARY SPECIFICATION

FLARE CARTRIDGE ASSEMBLY ALA-17B METAL PARTS FOR

This specification is approved for by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of parts, assembly and packing for one type of flare designated as ALA-17B used in Flare Set AN/ALA-17.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables For Inspection by Attributes

MIL-STD-1169 - Packaging, Packing and Marking For Shipment of Inert Ammunition Components

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1370

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:05Z
Check the source to verify that this is the current version before use.

FEDERAL

FED-STD-151 - Metal, Test Methods

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

PRODUCT AND PACKING DRAWINGS

9395763 - Flare Cartridge, ALA-17B

(Copies of specification, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained form he contracting activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Material shall be in accordance with applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on the applicable drawing (dwg. 9395763) and with all requirements specified in applicable specifications

3.3 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough workmanship like manner and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be free of burrs, chips, sharp edges, cracks, crazes, unblended radii, porosity, warpage, burn marks, checks, deposits, visible raised cement seams, solder splash, corrosion products, and other defects and foreign matter which would affect their serviceability. The cleaning method used shall not be injurious to any part or assembly nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First article inspection
b. Quality conformance inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample (see 6.2b) as designated by the Contracting Officer. For evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shal consist of the following items in sample quanities as indicated below and Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I as specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:05Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60036D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Flare Cartridge, ALA-17B				9395763
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Parts				
	Examination for defects	20 Ea.		3.2	4.4.2.1 thru 4.4.2.14
	Tests				
	Hardness of shorting clip (Dwg. 9234237)	20		3.2	4.5.1

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.1	Washer, Bottom	1	1	9209677
				NEXT HIGHER ASSEMBLY: 9395761

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Diameter of hole		0.65%	3.2	Gage
203	Poor workmanship		1.00%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

MIL-F-60036D(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Felt, Obturator	1 OF 1	9395759
			NEXT HIGHER ASSEMBLY 9395761

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Total length		0.65%	3.2	Gage
202	Width		0.65%	3.2	Gage
203	Poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.3	Case, Bottom				9234238
					NEXT HIGHER ASSEMBLY 9395763
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Minor diameter of thread		0.40%	3.2	Gage
104	Pitch diameter of thread		0.40%	3.2	Gage
105	Width of hold down bar slot		0.40%	3.2	Gage
106	True position of large outside diameter with the inside diameter		0.40%	3.2	Gage
107	True position of small outside diameter with the inside diameter		0.40%	3.2	Gage
108	True position of intermediate diameter with the inside diameter		0.40%	3.2	Gage
109	True position of pitch diameter of thread with the inside diameter		0.40%	3.2	Gage
110	Keyway missing		0.40%	3.2	Visual
111	True position of key way width with inside diameter at plug end		0.40%	3.2	Gage
112	Width of ground key way		0.40%	3.2	Gage
113	Location of ground key way		0.40%	3.2	Gage
114	Depth of ground keyway		0.40%	3.2	Gage
115	Crack, split or dent		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Case, Bottom	2 OF 2	9234238
			NEXT HIGHER ASSEMBLY 9395763

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Outside diameter of plug end		0.65%	3.2	Gage
202	Total length		0.65%	3.2	Gage
203	Distance from plug end to shoulder		0.65%	3.2	Gage
204	Length of crimping surface		0.65%	3.2	Gage
205	Total depth of plug hole		0.65%	3.2	Gage
206	Angle of inside base		0.65%	3.2	Gage
207	Distance from base to thread in plug hole		0.65%	3.2	Gage
208	Radii missing		0.65%	3.2	Visual
209	Finish improper		0.65%	3.2	Visual
210	Poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60036D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Case, Top				9209657
					NEXT HIGHER ASSEMBLY 9395763
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Minor diameter of thread		0.40%	3.2	Gage
103	Pitch diameter of thread		0.40%	3.2	Gage
104	Outside diameter		0.40%	3.2	Gage
105	True position of outside diameter at forward end with inside diameter		0.40%	3.2	Gage
106	True positon of outside diameter with small inside diameter		0.40%	3.2	Gage
107	True position of large outside diameter with inside diameter		0.40%	3.2	Gage
Minor					
201	Outside diameter of plug end		0.65%	3.2	Gage
202	Total length		0.65%	3.2	Gage
203	Distance from plug end to shoulder		0.65%	3.2	Gage
204	Length of crimping surface		0.65%	3.2	Gage
205	Angle of inside base		0.65%	3.2	Gage
206	Distance of crimping surface for bottom case		0.65%	3.2	Gage
207	Crimping arc missing		0.65%	3.2	Visual
208	Radii missing		0.65%	3.2	Visual
209	Crack, split or dent		0.65%	3.2	Visual
210	Finish improper		0.65%	3.2	Visual
211	Poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Disc, Felt	1 OF 1	9209658
			NEXT HIGHER ASSEMBLY: 9395763

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Cap, Top	1 OF 1	9209659
			NEXT HIGHER ASSEMBLY 9395763

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of top case end		0.40%	3.2	Gage
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Diameter of crimping surface for top case		0.65%	3.2	Gage
203	Total length		0.65%	3.2	Gage
204	Chord of crimping arc		0.65%	3.2	Gage
205	Finish improper		0.65%	3.2	Visual
206	Crack, split or dent		0.65%	3.2	Visual
207	Poor workmanship		1.00%	3.4	visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60036D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Plug, Bottom				9209671
					NEXT HIGHER ASSEMBLY 9209670
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Major diameter of thread		0.40%	3.2	Gage
102	Pitch diameter of thread		0.40%	3.2	Gage
103	Diameter of squib recess		0.40%	3.2	GAge
Minor					
201	Diameter of large recess		0.65%	3.2	Gage
202	Depth of large recess		0.65%	3.2	Gage
203	Location of squib recess		0.65%	3.2	Gage
204	Location of hole in squib recess		0.65%	3.2	Gage
205	Diameter of hole in squib recess		0.65%	3.2	Gage
206	Location of wrench holes		0.65%	3.2	Gage
207	Diameter of wrench hole		0.65%	3.2	Gage
208	Depth of recess for squib		0.65%	3.2	Gage
209	Diameter of hole for top squib wire		0.65%	3.2	Gage
210	Finish improper		0.65%	3.2	Visual
211	Poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Plug, Top				9209669
					NEXT HIGHER ASSEMBLY 9209668
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Major diameter of thread		0.40%	3.2	Gage
102	Pitch diameter of thread		0.40%	3.2	Gage
103	Diameter of squib recess		0.40%	3.2	Gage
Minor					
201	Diameter of large recess		0.65%	3.2	Gage
202	Depth of large recess		0.65%	3.2	Gage
203	Location of squib recess		0.65%	3.2	Gage
204	Location of hole in squib recess		0.65%	3.2	Gage
205	Diameter of hole in squib recess		0.65%	3.2	Gage
206	Location of wrench holes		0.65%	3.2	Gage
207	Diameter of wrench holes		0.65%	3.2	Gage
208	Depth of recess for squib		0.65%	3.2	Gage
209	Finish improper		0.65%	3.2	Visual
210	Poor workmanship		100%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Clip, Shorting	1 OF 1	9234237
			NEXT HIGHER ASSEMBLY 9395763

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Hardness	20	0, 1	3.2	4.5.1
102	Location of rectangular hole		0.40%	3.2	Gage
103	Location of shorting contacts		0.40%	3.2	Gage
104	Any shorting contact missing		0.40%	3.2	Visual
105	Distance from outside surface including "lift" tabs		0.40%	3.2	Gage
106	Distance across shorting clip		0.40%	3.2	Gage
107	Distance across curved portion of tab(s) on "lift" tab side, min.		0.40%	3.2	Gage
108	Distance from top surface to end of locking tab(s)		0.40%	3.2	Gage
109	Distance to top of small projection on tab(s) on side opposite "lift" tab min.		0.40%	3.2	Gage
110	Length of tab(s) on side opposite "lift" tab		0.40%	3.2	Gage
111	Point(s) missing from shorting contact		0.40%	3.2	Visual
112	Shorting clip damaged to extent that functioning is impaired		0.40%	3.2	Visual
113	Protective finish missing, incorrect or exposing base metal		0.40%	3.2	Visual
Minor					
201	Marking missing		0.65%	3.2	Visual
202	Poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-60036D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9234234
4.4.2.10	Contact				NEXT HIGHER ASSEMBLY 9234233
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Total length, min.		0.40%	3.2	Gage
103	Finish improper		0.40%	3.2	Visual
Minor					
201	Small outside diameter		0.65%	3.2	Gage
202	Thickness of flange		0.65%	3.2	Gage
203	Depth of hole min.		0.65%	3.2	Gage
204	Diameter of hole, min.		0.65%	3.2	Gage
205	Poor workmanship		1.00%	3.4	Visual
NOTES:					

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Disc				9234235
					NEXT HIGHER ASSEMBLY 9234233
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any contact hole missing		0.40%	3.2	Visual
102	Any ground contact slot missing		0.40%	3.2	Visual
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Distance between slots		0.65%	3.2	Gage
204	Poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Contact, Ground				9234236
					NEXT HIGHER ASSEMBLY 9234233
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any hole missing		0.40%	3.2	Visual
102	Total length		0.40%	3.2	Gage
103	Width		0.40%	3.2	Gage
104	Finish improper		0.40%	3.2	Visual
Minor					
201	Length to tab		0.65%	3.2	Gage
202	Distance between tabs		0.65%	3.2	Gage
203	Poor workmanship		1.00%	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Contact and Wire Assembly				9234233
					NEXT HIGHER ASSEMBLY 9395763
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any contact missing		0.40%	3.2	Visual
102	Any contact inadequately secured to disc		0.40%	3.2	Visual
103	Any wire missing or insecure		0.40%	3.2	Visual/Manual
104	Length of blue and red wires		0.40%	3.2	Gage
105	Length of white wire		0.40%	3.2	Gage
106	Assembly damaged to the extent that functioning is impared		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T00:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Sleeve	1 OF 1	9209666
			NEXT HIGHER ASSEMBLY 9395763

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Puncture or tear		0.40%	3.2	Visual
Minor					
201	Total length		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Poor workmanship		1.00%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

4.4.3 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and Section 6.3 herein.

4.5 Method of inspection.

4.5.1 Hardness of shorting clip. The shorting clip shall be tested as specified in Method 243 of Federal Standard 151. This is a destructive test. Parts so tested shall not be returned to the lot.

5. PACKAGING

5.1 Preservation and packaging.

5.2 Packing.

5.2.1 Level C. Packing shall be in accordance with MIL-STD-1169.

5.3 Marking.

5.3.1 Level C. Marking shall be in accordance with MIL-STD-1169.

6. NOTES

6.1 Intended use. This flare is to be used in Flare Set ALA-17.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification
b. Provisions for submission of first article samples
c. Provisions of MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required to Commander: US Army Armament Research and Development Center, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

6.4 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, US Army Armament Research and Development Center, ATTN: AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island or Picatinny Arsenal U.S. Army Armament Research and Development Command drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the change.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1370-A185)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-60036D	FLARE CARTRIDGE ASSEMBLY ALA-17B METAL PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional

b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional

c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional

8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:05Z
Check the source to verify that this is the current version before use.