MILITARY SPECIFICATION

INERT PROJECTILE ASSEMBLY LESS ESCAPEMENT ASSEMBLY METAL PARTS AND ASSEMBLING AND PACKAGING

This Specification is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the metal parts, loading, assembling and packaging for one type of test vehicle projectile for use in lot acceptance tests for escapement assembly.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified (see 6.2), the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-490	Cleaning Methods for Ferrous Surfaces and Pretreatments for Organic Coating

MILITARY

MIL-A-8625 -	Anodic Coating, for Aluminum and Aluminum Alloys
MIL-A-48078 -	Ammunition, Standard Quality Assurance Provisions, General Specifications for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1310
DISTRIBUTION STATEMENT Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

DRAWINGS (see 6.7)

US ARMY ARMAMENT RESEARCH DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12902879 - Inert projectile assembly less escapement assembly.

(Copies of specifications, standards, handbooks and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Please see page 23 of MIL-STD-961B.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-B117 - Standard Method of Salt Spray (fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the reference cited herein, (except for associated detail specifications, specifications sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification however, shall supersede applicable laws and regulations unless specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

3.2 Parts. The parts shall comply with all requirements specified on drawing (dwg.) 12902879 and with all requirements specified in applicable specifications.

3.3 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3 and 6.6).

3.4 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough and workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Test equipment and inspection facilities. The manufacturer shall insure that test and inspection facilities of sufficient accuracy, quality and quantity are established and maintained to permit performance of required inspections.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (4.3)

b. Quality Conformance Inspection (4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Parts description	Drawings	Quantity
Inert Projectile Assembly Less Escapement Assembly	12902879	25
Body Insert	9399382	25
Ogive Assembly, 40M, M918	9399390	50
Firing Pin Assembly	9399391	50
Firing Pin	9399392	25
Firing Pin Plate	9399393	25
Ogive M918TP	9399394	25
Spring, Anti-creep	9399395	50
Body	9399396	25
Body Assembly	9399402	50

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

MIL-I-70756 (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
	Projectile and Components				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pin, Firing (Dwg. 9399392)				
	Examination for defects	25		3.2	4.4.2.1
	Plate, Firing Pin Dwg. (9399393)				
	Examination for defects	25		3.2	4.4.2.2
	Firing Pin Assembly (Dwg. 9399391)				
	Examination for defects	50		3.2	4.4.2.3
	Push test, firing pin assembly	50		3.2	4.5.1
	Ogive, M918 TP (Dwg. 9399394)				
	Examination for defects	25		3.2	4.4.2.4
	Salt Spray	4		3.2	4.5.2.1
	Insert, Body (Dwg. 9399382)				
	Examination for defects	25		3.2	4.4.2.5

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Projectile and Components	SHEET 2 OF 3		DRAWING NUMBER: SEE BELOW
				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Anti-Creep (Dwg. 9399395)				
	Examination for defects	50		3.2	4.4.2.6
	Load Test	50		3.2	4.5.3
	Ogive Assembly, 40mm, M918 (Dwg.9399390)				
	Examination for defects	50		3.2	4.4.2.7

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70756 (AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
	Projectile and Components				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (Dwg. 9399396)				
	Examination for defects	25		3.2	4.4.2.8
	Body Assembly (Dwg. 9399402)				
	Examination for defects	50		3.2	4.4.2.9 , 4.4.2.10
	Salt Spray	4		3.2	4.5.2.2
	Push test of rotating band	50		3.2	4.5.6
	Inert Projectile Assembly Less Escapement (Dwg. 12902879)				
	Examination for defects	25		3.2	4.4.2.11

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: http://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. Each inspection lots shall contain:

a. Metal parts from one lot interfix number and from one manufacturer.

4.4.2 Examination for defects.

a. Sampling plan. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70756 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Pin, Firing		9399392
			NEXT HIGHER ASSEMBLY 9399391

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Profile of firing pin point		.40	3.2	Gage
102.	Length, firing pin point to backside of shoulder		.40	3.2	Gage
MINOR					
201.	Outside diameter at backside of shoulder		.65	3.2	Gage
202.	Total length		.65	3.2	Gage
203.	Poor workmanship		.65	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70756 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399393
4.4.2.2	Plate, Firing Pin				NEXT HIGHER ASSEMBLY 9399391
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Diameter, outside		.40	3.2	Gage
102.	True position of center hole to outside diameter		.40	3.2	Gage
MINOR					
201.	Diameter, center hole		.65	3.2	Gage
202.	Thickness		.65	3.2	Gage
203.	Flatness		.65	3.2	Gage
204.	Poor workmanship		.65	3.4	Visual

NOTES:

AMSM Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399391
4.4.2.3	Firing Pin Assembly				NEXT HIGHER ASSEMBLY 9399390
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR 101.	Push test, firing pin assembly	80	Acc-1 Rej-2		4.5.1
MINOR 201.	Poor workmanship		.65	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399394
4.4.2.4	Ogive, M918 TP				NEXT HIGHER ASSEMBLY 9399390
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Major diameter, thread		.40	3.2	Gage
102.	Pitch diameter, thread		.40	3.2	Gage
103.	Largest outside diameter		.40	3.2	Gage
104.	Total length		.40	3.2	Gage
105.	True position, largest outside diameter to thread pitch diameter		.40	3.2	Gage
106.	True position, inside diameter to thread pitch diameter		.40	3.2	Gage
107.	Larger, inside diameter		.40	3.2	Gage
108.	Depth to step on inside diameter		.40	3.2	Gage
109.	Salt Spray/Protective finish	4	1/	3.2	4.5.2.1
110	Missing or improperly placed groove		.40	3.2	Visual
MINOR					
201.	Length, full thread		.65	3.2	Gage
202.	Length to shoulder at thread relief		.65	3.2	Gage
203.	Diameter of thread relief		.65	3.2	Gage
204.	Incorrect color		.65	3.2	Visual
205.	Wall thickness		.65	3.2	Gage
206.	Poor workmanship		.65	3.4	Visual

NOTES:

1/ Rejection shall be in accordance with MIL-A-8625.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399382
4.4.2.5	Insert, Body				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Length, body		.40	3.2	Gage
102.	Diameter, outside		.40	3.2	Gage
103.	Parallelism of rear surface with front face		.40	3.2	Gage
104.	True position, setback spring cavity		.40	3.2	Gage
105.	True position, through hole to outside diameter		.40	3.2	Gage
106.	True position, setback spring cavity to setback pin cavity		.40	3.2	Gage
107.	True position, powder cavity to outside diameter		.40	3.2	Gage
108.	Depth of setback pin cavity		.40	3.2	Gage
109.	Depth of setback spring cavity		.40	3.2	Gage
MINOR					
201.	Diameter, powder cavity		.65	3.2	Gage
202.	Depth, powder cavity		.65	3.2	Gage
203.	Angle, outside diameter		.65	3.2	Gage
204.	Location, angle		.65	3.2	Gage
205.	Diameter, through hole		.65	3.2	Gage
206.	Diameter, setback pin cavity		.65	3.2	Gage
207.	Diameter, setback spring cavity		.65	3.2	Gage
208.	Poor workmanship		.65	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70756 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9399395
4.4.2.6	Spring, Anti-Creep		NEXT HIGHER ASSEMBLY 9399390

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Load Test	125	Acc-1 Rej-2		4.5.3
102.	Thickness		.40	3.2	Gage
103.	Outside diameter, min		.40	3.2	Gage
MINOR					
201.	Poor Workmanship		.65	3.4	Visual

NOTES:

AMSM(rm 1570, 1 Feb 85 Rep? s DRSMC-QA (D) Form 160, 1 Aug 83, which may not ' ` used.

Source: https://14.dist.dla.mil -- Downloaded: 202640-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70756 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Ogive Assembly,40mm, M918		9399390
			NEXT HIGHER ASSEMBLY 9399374

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL					
1.	Anti-creep spring missing		100%	3.2	Probe/4.5.7
MAJOR					
101.	Depth to firing pin point		.40	3.2	Gage
102.	Firing pin assembly improperly seated		.40	3.2	Visual
MINOR					
201.	Poor workmanship		.65	3.4	Visual

NOTES:

1/ Assembly shall be inspected in inverted (open end of ogive facing down) position.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Body		9399396
			NEXT HIGHER ASSEMBLY 9399402

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Presence of cracks		100%	3.2	Visual
102.	Pitch diameter of thread		.40	3.2	Gage
103.	Minor diameter of thread		.40	3.2	Gage
104.	Large outside diameter		.40	3.2	Gage
105.	Diameter at end of taper		.40	3.2	Gage
106.	Total runout at indicated lengths on body with pitch diameter (2)		.40	3.2	Gage
107.	Thickness through base center		.40	3.2	Gage
108.	Thickness of groove (6) in base		.40	3.2	Gage
MINOR					
201.	Diameter of rotating band surface (after knurling)		.65	3.2	Gage
202.	Width of rotating band surface		.65	3.2	Gage
203.	Total length		.65	3.2	Gage
204.	Length of effective thread, min		.65	3.2	Gage
205.	Poor workmanship		.65	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70756 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399402
4.4.2.9	Body Assembly, prior to paint				NEXT HIGHER ASSEMBLY 9399374
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Parallelism, back of rotating band with open end		.40	3.2	Gage
102.	Distance from open end to back of rotating band, max		.40	3.2	Gage
103.	Push test of rotating band	50	Acc-0 Rej-1	3.2	4.5.6
104.	Profile of rotating band		.40	3.2	Gage
105.	Runout of indicated point of taper with outside large diameter		.40	3.2	Gage
MINOR					
201.	Poor workmanship		.65	3.4	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-70756 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Body Assembly, After Painting		9399402
			NEXT HIGHER ASSEMBLY 9399374

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Body Diameter max		.40	3.2	Gage
102.	Diameter of rotating band		.40	3.2	Gage
103.	Salt spray/protective finish	1/	1/	3.2	4.5.2.2
104.	Missing or improperly placed markings		.40	3.2	Visual
MINOR					
201.	Incorrect color of body		.65	3.2	Visual
202.	Brown stripe missing or not 360°		.65	3.2	Visual
203.	Poor Workmanship		.65	3.4	Visual

NOTES: 1/ Sampling and rejection shall be in accordance with TT-C-490.

AMSMC rm 1570, 1 Feb 85 Repl ; DRSMC-QA (D) Form 160, 1 Aug 83, which may not used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.11	Inert Projectile Assembly Less Escapement Assembly		1 1		12902879
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined				
MAJOR					
101.	Total length		100%	3.2	Gage
102.	Diameter of rotating band		.40	3.2	Gage
103.	Diameter of Bourrelet		.40	3.2	Gage
104.	Gap between body and ogive		.40	3.2	Gage
105.	True position, rotating band to bourrelet		.40	3.2	Gage
MINOR					
201.	Poor Workmanship		.65	3.4	Visual

NOTES:

Source: http://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the first article and quality conformance inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Push test of firing pin assembly. The firing pin assembly shall be placed in an approved fixture and the push test specified on Dwg. 9399391 shall be applied. This test is a non-destructive test. Parts successfully tested may be returned to the lot.

4.5.2 Salt spray.

4.5.2.1 Ogive, M918 TP. This test shall be conducted in accordance with ASTM-B-117 for 48 hours. Salt solution shall be 5 percent. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.5.2.2 Body assembly. This test shall be conducted in accordance with ASTM-B-117. This test shall be conducted for 48 hours along 1.25 inches of the outside length measured from the open end. The surface area rear of this point may be tested for 24 hours minimum. Salt spray test not required for inside surface body of assembly. The rotating band may be masked off for this test. Salt solution shall be 5 percent. This test is a destructive test. parts so tested may not be returned to the lot.

4.5.3 Load test of anti-creep spring. The anti-creep spring shall be placed in a fixture and the load specified on Dwg. 9399395 shall be applied. This test is a non-destructive test. Parts successfully tested may be returned to the lot.

4.5.4 Assembly torque of ogive assembly prior to sealant cure. The projectile assembly shall be placed in an approved fixture and the torque specified on the applicable drawing shall be applied. Observation shall be made for the applicable requirement. This test is a non-destructive test. Parts successfully tested may be returned to the lot.

Warning: This test is conducted on assemblies containing an explosive element. Test barricades (where used), procedures and equipment shall have prior approval.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.5.5 Air pressure test. The projectile shall be placed in an approved fixture and air applied to produce a specified pressure. Observations shall be made for a drop in pressure indicating a leak. This is a non-destructive test. Parts so tested may be returned to the lot.

4.5.6 Push test of rotating band. The body assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied. Observation shall be made for compliance with the applicable requirement. This is a non-destructive test. Parts so tested may be returned to the lot.

4.5.7 Probe inspection. This inspection shall be performed using automatic inspection equipment designed by the contractor and approved by the Government. See MIL-A-48078.

5. PACKAGING

5.1 Preservation and packing.

5.2 Unitization. Unitization shall be prescribed by the procuring agency as specified in the contract or order.

5.3 Shipping. When shipments of more than one lot are made at one time, such as in a carload, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. This specification covers the metal parts, loading, assembling and packaging for test vehicle projectile for use in lot acceptance tests for escapement assembly.

6.2. Ordering data. See MIL-A-48078.

6.3. Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, US Army ARDEC, AMSMC-QAF-I (D), Picatinny Arsenal, NJ, 07806-5000. Request letter of submittal state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Submission of results of contractor conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examination or tests to Commander, US Army ARDEC, Attn: AMSMC-QAF-S (D), Picatinny Arsenal, NJ 07806-5000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

6.5 Submission of test data. In addition to the normal distribution of records, when the cartridges are procured by ARDC, one copy of all ballistic data and ammunition data cards shall be forwarded to Commander, US Army ARDEC, ATTN: AMSMC-QAF-S (D), Picatinny Arsenal, NJ 07806-5000.

6.6 First article. When a first article inspection is required, the contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, test and approval of the documents for first article.

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, US Army Armament Research and Development Command (ARRADCOM) or US Army Armament Research and Development Center (ARDC) drawings. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.8 Subject term (key word) listing.

M918 TP Cartridge
40mm
MK19 Grenade Launcher
M129 Grenade Launcher
M550 Escapement Assembly

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A442)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-I-70756 (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Picatinny Arsenal, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:58Z
Check the source to verify that this is the current version before use.